

Safety Data Sheet
Spatter Shield

SECTION I - IDENTIFICATION

PRODUCT IDENTIFIER: Spatter Shield
PRODUCT CODE: 7725, 7726, 7727
RECOMMENDED USE: Anti-Spatter
RESTRICTIONS ON USE: None known.
COMPANY NAME: TIFCO Industries, Inc.
COMPANY ADDRESS: P.O. Box 40277 Houston, TX 77240
COMPANY PHONE: 281-571-6000
EMERGENCY PHONE: 800-255-3924

SECTION II – HAZARDS IDENTIFICATION

CLASSIFICATION: Flammable Aerosol: Category 1

Gases Under Pressure: Liquefied Gas

Aspiration Hazard: Category 1

HAZARD STATEMENT(S): DANGER: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways.

This product contains the following percentage of chemicals of unknown toxicity: N/A

PRECAUTIONARY STATEMENTS: Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. **IF SWALLOWED:** Immediately call a poison center or doctor. Do NOT induce vomiting. Dispose of contents and container in accordance with local, state, and national regulations.

SYMBOL:



HAZARDS NOT OTHERWISE CLASSIFIED: N/A

SECTION III – COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	CAS NUMBER	PERCENT
Butane	106-97-8	10-30%
Mineral oil	8042-47-5	7-13%
Propane	74-98-6	5-10%

Trade Secret Information: A specific chemical identity and/or percentage of composition has been withheld as a trade secret.

SECTION IV - FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Seek medical attention if irritation persists.

INGESTION: Do not induce vomiting unless directed by medical authority. Immediately rinse mouth with water. Seek medical attention if irritation develops. Never give anything by mouth to an unconscious person.

INHALATION: Move to fresh air. If breathing is difficult or unconscious, administer oxygen. If not breathing administer artificial respiration. Seek medical attention if irritation persists.

SKIN: Immediately wash with soap and water for 15 minutes. Remove contaminated clothing and shoes immediately. Seek medical attention if irritation develops. Wash contaminated clothing before reuse.

ACUTE HEALTH HAZARDS: Contact with eyes may cause irritation, redness, tearing. Prolonged contact with skin may cause irritation. Inhalation of vapors may cause nausea, dizziness and drowsiness. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

CHRONIC HEALTH HAZARDS: None known.

NOTE TO PHYSICIAN: Treatment of overexposure should be directed at the control of symptoms and the clinical condition. If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately.

Safety Data Sheet
Spatter Shield

SECTION V – FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA: Dry chemical, carbon dioxide, foam, and water fog.

UNSUITABLE EXTINGUISHING MEDIA: Water spray/stream.

SPECIAL FIRE FIGHTING PROCEDURES: Wear NIOSH approved Self Contained Breathing Apparatus with a full face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires. Shut off all sources of Safety Data Sheet MFSCO Pure Slick II PAGE 2 of 4 ignition. Use water spray to disperse vapor and cool fire exposed containers. Prevent run off from entering streams, sewers, or drinking water supply.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Contents under pressure. Exposure to temperatures above 122 °F (50 °C) may cause bursting. Keep away from heat, sparks, open flames and other sources of ignition. Vapors may travel considerable distance to a source of ignition and flash back.

HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon, hydrocarbons.

SECTION VI – ACCIDENTAL RELEASE MEASURES

PERSONAL PROTECTIVE EQUIPMENT: Refer to section VIII for proper Personal Protective Equipment.

SPILL: Eliminate all sources of ignition. Clean up using rag or use some non-combustible material like vermiculite, sand or earth. Prevent spill from entering sewers, storm drains and natural waterways. Place waste in proper containers for disposal.

WASTE DISPOSAL: Dispose of in accordance with local, state and federal regulations. Do not dump in sewers.

RCRA STATUS: Waste likely considered D001 (Ignitable waste), under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION VII – HANDLING AND STORAGE

HANDLING AND STORAGE: Do not use or store near heat, open flames or other sources of ignition. Avoid contact with skin, eyes and clothing. Do not inhale mist or vapor. Do not use or store with strong oxidizers. Protect from sunlight. Store in a well ventilated area. Do not expose to temperatures exceeding 50 °C/122 °F. Pressurized container: Do not pierce or burn, even after use. Store in a cool, dry area.

OTHER PRECAUTIONS: Keep out of the reach of children. Read and follow the directions on the product label. They are the best guide to using the product in the most effective manner. The label also gives you the necessary safety precautions to protect your health.

INCOMPATIBILITY: Strong oxidizing agents, strong reducing agents.

SECTION VIII – EXPOSURE CONTROLS/PERSONAL PROTECTION

HAZARDOUS INGREDIENT	OSHA PEL	ACGIH TLV
Butane	Not Established	1000 ppm
Mineral oil	5 mg/m ³	5 mg/m ³
Propane	1000 ppm	1000 ppm

ENGINEERING CONTROLS / VENTILATION: General ventilation adequate but local exhaust/ventilation preferred.

RESPIRATORY PROTECTION: Not required with normal use. If vapors are present or irritation is experienced, use NIOSH/MSHA approved respirator.

PERSONAL PROTECTIVE EQUIPMENT: Safety glasses/goggles.

ADDITIONAL MEASURES: No smoking or open flames. Wash hands thoroughly after handling.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Aerosol spray.

ODOR: None.

ODOR THRESHOLD: N/D

pH: N/A

MELTING POINT/FREEZING POINT: N/D

INITIAL BOILING POINT AND BOILING RANGE: N/D

FLASH POINT: N/D

EVAPORATION RATE: N/D

FLAMMABILITY (solid/gas): Extremely flammable aerosol.

UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS:

LOWER FLAMMABILITY LIMIT: N/D

UPPER FLAMMABILITY LIMIT: N/D

EXPLOSIVE LIMIT LOWER (%): N/D

Safety Data Sheet

Spatter Shield

EXPLOSIVE LIMIT UPPER (%): N/D
VAPOR PRESSURE (mm Hg): N/D
VAPOR DENSITY (AIR=1): N/D
RELATIVE DENSITY (H₂O=1): N/D
SOLUBILITY(IES): N/D
PARTITION COEFFICIENT: n-OCTANOL/WATER (K_{ow}): N/D
AUTOIGNITION TEMPERATURE: N/D
DECOMPOSITION TEMPERATURE: N/D
VISCOSITY: N/D

SECTION X – STABILITY AND REACTIVITY

REACTIVITY: None known.
CHEMICAL STABILITY: Stable.
POSSIBLE HAZARDOUS REACTIONS: None known.
CONDITIONS TO AVOID: Temperatures greater than 122 °F (50 °C) and sources of ignition. Avoid incompatible materials.
INCOMPATIBLE MATERIALS: Strong oxidizing agents, strong reducing agents.
HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon, hydrocarbons.

SECTION XI – TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION: **Propane** (74-98-6): LC₅₀ (Inhalation, Rat, 4h) 658 mg/L. **Butane** (106-97-8): LC₅₀ (Inhalation, Rat, 4h) 30957 mg/m³. **Mineral oil** (8042-47-5): LD₅₀ (Oral, Rat) > 5000 mg/kg; LD₅₀ (Dermal) > 2000 mg/kg; LC₅₀ (Inhalation Dust/Mist, Rat, 4h) > 5 g/L.
ROUTES OF ENTRY: Eyes, Ingestion, Inhalation, Skin
EYES: May cause irritation, redness, tearing.
INGESTION: Harmful or fatal. Aspiration hazard. May cause gastrointestinal irritation, nausea, vomiting.
INHALATION: May cause respiratory tract irritation, dizziness.
SKIN: May cause irritation.
MEDICAL CONDITION AGGRAVATED: None known.
ACUTE HEALTH HAZARDS: Contact with eyes may cause irritation, redness, tearing. Prolonged contact with skin may cause irritation. Inhalation of vapors may cause nausea, dizziness and drowsiness. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
CHRONIC HEALTH HAZARDS: None known.
CARCINOGENICITY: OSHA: No ACGIH: No NTP: No IARC: 3 - Not classifiable OTHER: N/A

SECTION XII – ECOLOGICAL INFORMATION

ECOTOXICITY: **Mineral oil** (8042-47-5): LC₅₀ (*Oncorhynchus mykiss*, 96h) 5000 mg/L; EC₅₀ (*Daphnia magna*, 48h) 1000 mg/L.
PERSISTENCE AND DEGRADABILITY: No additional information available.
BIOACCUMULATIVE POTENTIAL: No additional information available.
MOBILITY IN SOIL: N/D
OTHER ADVERSE EFFECTS: None known.

SECTION XIII – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Dispose of in accordance with local, state and federal regulations. Do not dump in sewers.
RCRA STATUS: Waste likely considered D001 (Ignitable waste), under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION XIV - TRANSPORT INFORMATION

PROPER SHIPPING NAME: Aerosols, Ltd. Qty.
HAZARD CLASS/DIVISION: 2.1
UN/NA NUMBER: UN1950
PACKING GROUP: N/A

AIR SHIPMENT

PROPER SHIPPING NAME: Aerosols, flammable.
HAZARD CLASS/DIVISION: 2.1
UN/NA NUMBER: UN1950
PACKING GROUP: N/A

Safety Data Sheet
Spatter Shield

SHIPPING BY WATER:

VESSEL (IMO/IMDG)

PROPER SHIPPING NAME: Aerosols.

HAZARD CLASS/DIVISION: 2.1

UN/NA NUMBER: UN1950

PACKING GROUP: N/A

ENVIRONMENTAL HAZARDS WATER: N/A

SECTION XV - REGULATORY INFORMATION

TSCA STATUS: All chemicals are listed or exempt.

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT): None.

SARA 311/312 HAZARD CATEGORIES: Health Hazard and Physical Hazard.

SARA 313 REPORTABLE INGREDIENTS: Propane (74-98-6).

STATE REGULATIONS: California Proposition 65: This product does not contain chemicals regulated by California Proposition 65.

INTERNATIONAL REGULATIONS: Listed or exempt from listing/notification on the following chemical inventories: Domestic Substances List (DSL, Canada).

VOLATILE ORGANIC COMPOUNDS (VOC): 25%

NFPA HEALTH: 3

HMIS HEALTH: 3

NFPA FLAMMABILITY: 3

HMIS FLAMMABILITY: 3

NFPA REACTIVITY: 0

HMIS REACTIVITY: 0

NFPA OTHER: None

HMIS PROTECTION: A

SECTION XVI - OTHER INFORMATION

PREPARATION BY: Craig Bernard

DATE PREPARED: 08/07/2024

REVISION DATE: 09/11/2024

N/A = Not Applicable; N/D = Not Determined

DISCLAIMER: To the best of our knowledge, information contained herein is accurate. However, there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.