

SAFETY DATA SHEET

Issuing date 27-May-2015

Revision Date 26-Aug-2025

Version 1.02

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product name X-TREME SOLV

Other means of identification

Product code 7794, 7795, 7796

Product Type Extremely Flammable Aerosol
Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use MULTI-PURPOSE SOLVENT.

Uses advised against No information available

Manufactured For:

Tifco Industries
21400 Northwest Freeway
Cypress, TX 77429
800-868-4326

Emergency telephone number

Chemical Emergency Phone Number CHEM-TEL, INC. 1-800-255-3924

Company Emergency Phone Number 281-571-6000

2. HAZARDS IDENTIFICATION

Classification

This product is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

| | |
|--|----------------|
| Skin corrosion/irritation | Category 2 |
| Serious eye damage/eye irritation | Category 2A |
| Carcinogenicity | Category 2 |
| Specific target organ toxicity (single exposure) | Category 3 |
| Specific target organ toxicity (repeated exposure) | Category 2 |
| Aspiration toxicity | Category 1 |
| Flammable aerosols | Category 1 |
| Gases under pressure | Compressed gas |

GHS Label elements, including precautionary statements

Emergency Overview

Danger

Hazard Statements

Causes skin irritation
 Causes serious eye irritation
 Suspected of causing cancer
 May cause respiratory irritation. May cause drowsiness or dizziness.
 May cause damage to organs (Eyes, Skin, Respiratory System, Central Nervous System, and Hearing) through prolonged or repeated exposure.
 May be fatal if swallowed and enters airways
 Extremely flammable aerosol
 Contains gas under pressure; may explode if heated



Appearance Clear **Physical state** Aerosol **Odor** Solvent

Precautionary Statements - Prevention

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Wash face, hands and any exposed skin thoroughly after handling
 Wear protective gloves, protective clothing, eye protection, face protection.
 Do not breathe dust, fumes, gas, mist, vapors, spray.
 Use only outdoors or in a well-ventilated area
 Keep away from heat, sparks, open flames, hot surfaces - No smoking.
 Do not spray on an open flame or other ignition source
 Pressurized container: Do not pierce or burn, even after use

Precautionary Statements - Response

If exposed or concerned: Get medical advice, attention.
 Specific treatment (see first aid on this label).
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 If eye irritation persists: Get medical advice, attention.
 IF ON SKIN: Wash with plenty of soap and water
 If skin irritation occurs: Get medical advice, attention.

Take off contaminated clothing and wash before reuse
IF INHALED: Remove person to fresh air and keep comfortable for breathing
Call a POISON CENTER or doctor, physician if you feel unwell.
IF SWALLOWED: Immediately call a POISON CENTER, doctor, physician.
Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up
Store in a well-ventilated place. Keep container tightly closed
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents, container to an approved waste disposal plant.

Hazards not otherwise classified (HNOC)

Not applicable

Other information

0% of mixture consists of ingredients(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name | CAS No. | Weight-% |
|----------------------------|------------|----------|
| PETROLEUM DISTILLATES | 64742-89-8 | 50-60 |
| PROPANE/ISOBUTANE/N-BUTANE | 68476-86-8 | 20-30 |
| XYLENE | 1330-20-7 | 10-20 |
| ETHYL BENZENE | 100-41-4 | 1-10 |
| N-OCTANE | 111-65-9 | 1-10 |
| HEPTANE | 142-82-5 | 1-10 |
| CUMENE | 98-82-8 | <0.1 |
| TOLUENE | 108-88-3 | <0.1 |
| BENZENE | 71-43-2 | <0.1 |
| NAPHTHALENE | 91-20-3 | <0.1 |

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES**Description of first aid measures**

| | |
|-----------------------|--|
| General advice | Avoid contact with eyes, skin, and clothing. Avoid breathing vapors, mist, or gas. |
| Eye contact | Immediately flush with plenty of water for at least 15 minutes. After initial flushing, remove any contact lenses and continue flushing. If eye irritation persists, consult a doctor. |
| Skin contact | Rinse immediately with plenty of water for 15 minutes and seek medical advice if skin irritation persists. |
| Inhalation | Move to fresh air. If not breathing, give artificial respiration. If breathing has stopped, contact emergency medical services immediately. |
| Ingestion | Do NOT induce vomiting. Call a physician immediately. Never give anything by mouth to unconscious person. Risk of product entering the lungs on vomiting after ingestion. |

Most important symptoms and effects, both acute and delayed

Main Symptoms Causes skin and eye irritation. May cause respiratory irritation. May cause dizziness or drowsiness. Harmful and may be fatal if swallowed and enters airways.

Indication of any immediate medical attention and special treatment needed

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water fog.Dry chemical. Foam.Carbon dioxide (CO2). Cool containers/tanks with water spray.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire. Keep away from sources of ignition - No smoking.

Specific hazards arising from the chemical

Extremely Flammable / Flammable. Keep product and empty container away from heat and sources of ignition.

Explosion Data

Sensitivity to Mechanical Impact none.

Sensitivity to Static Discharge Yes.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use shielding to protect fire-fighters from bursting containers. In the event of fire and/or explosion do not breathe fumes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Use with adequate ventilation to keep the exposure levels below the OELS.

Environmental precautions

Environmental precautions Vapors can accumulate in low areas. Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains. Report spills as required by local and federal regulations.

Methods and material for containment and cleaning up

Methods for Containment Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers Prevent further leakage or spillage if safe to do so. Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains.

Methods for cleaning up Soak up with inert absorbent material. Contain liquid and collect with an inter, non-combustible material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly . After cleaning, flush away traces with water. Prevent product from entering drains. Take precautionary measures against static discharges.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Avoid contact with eyes. Avoid breathing vapors or mists. Contents under pressure. Do not puncture or incinerate cans. Do not stick pin or any other sharp object into opening on top of can. Avoid skin contact. Use with adequate ventilation. Keep container away from heat,

flames, and all other sources of ignition. Keep can away from all sources of electricity such as electric motors and batteries. Do not spray on hot surfaces.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions

Keep containers tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Keep in properly labeled containers. Keep out of the reach of children. Store locked up.

Incompatible products

Strong acids, alkalis, oxidizing agents.

Aerosol Level

3

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

| Chemical Name | ACGIH TLV | OSHA PEL | NIOSH |
|--|---|--|--|
| PROPANE/ISOBUTANE/N-BUTANE 68476-86-8 | 74-98-6: TWA: 1000 ppm 106-97-8: STEL: 1000 ppm 75-28-5: STEL: 1000 ppm | 74-98-6: TWA: 1000 ppm TWA: 1800 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m ³ 106-97-8: (vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m ³ | 74-98-6: IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³ 106-97-8: TWA: 800 ppm TWA: 1900 mg/m ³ 75-28-5: TWA: 800 ppm TWA: 1900 mg/m ³ |
| XYLENE 1330-20-7 | TWA: 20 ppm | TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m ³ | Not Established |
| ETHYL BENZENE 100-41-4 | Ototoxicant - potential to cause hearing disorders TWA: 20 ppm | TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m ³ | IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³ |
| HEPTANE 142-82-5 | STEL: 500 ppm TWA: 400 ppm | TWA: 500 ppm TWA: 2000 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 1600 mg/m ³ (vacated) STEL: 500 ppm (vacated) STEL: 2000 mg/m ³ | IDLH: 750 ppm Ceiling: 440 ppm 15 min Ceiling: 1800 mg/m ³ 15 min TWA: 85 ppm TWA: 350 mg/m ³ |
| N-OCTANE 111-65-9 | TWA: 300 ppm | TWA: 500 ppm TWA: 2350 mg/m ³ (vacated) TWA: 300 ppm (vacated) TWA: 1450 mg/m ³ (vacated) STEL: 375 ppm (vacated) STEL: 1800 mg/m ³ | IDLH: 1000 ppm Ceiling: 385 ppm 15 min Ceiling: 1800 mg/m ³ 15 min TWA: 75 ppm TWA: 350 mg/m ³ |
| CUMENE 98-82-8 | TWA: 5 ppm | TWA: 50 ppm TWA: 245 mg/m ³ (vacated) TWA: 50 ppm (vacated) TWA: 245 mg/m ³ (vacated) S* S* | IDLH: 900 ppm TWA: 50 ppm TWA: 245 mg/m ³ |
| TOLUENE 108-88-3 | Ototoxicant - potential to cause hearing disorders TWA: 20 ppm | TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m ³ Ceiling: 300 ppm | IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 560 mg/m ³ |
| BENZENE | STEL: 2.5 ppm | TWA: 10 ppm applies to | IDLH: 500 ppm |

| | | | |
|------------------------|--------------------|--|---|
| 71-43-2 | TWA: 0.5 ppm S* | industry segments exempt from the benzene standard at 29 CFR 1910.1028 TWA: 1 ppm (vacated) TWA: 10 ppm unless specified in 1910.1028 (vacated) STEL: 50 ppm 10 min unless specified in 1910.1028 (vacated) Ceiling: 25 ppm unless specified in 1910.1028 Ceiling: 25 ppm STEL: 5 ppm see 29 CFR 1910.1028 | TWA: 0.1 ppm STEL: 1 ppm |
| NAPHTHALENE 91-20-3 | TWA: 10 ppm S* | TWA: 10 ppm TWA: 50 mg/m ³ (vacated) TWA: 10 ppm (vacated) TWA: 50 mg/m ³ (vacated) STEL: 15 ppm (vacated) STEL: 75 mg/m ³ | IDLH: 250 ppm TWA: 10 ppm TWA: 50 mg/m ³ STEL: 15 ppm STEL: 75 mg/m ³ |

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration)

NIOSH IDLH: Immediately Dangerous to Life or Health

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Measures

Showers, eyewash stations, and ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/Face Protection

Safety glasses with side-shields. Tightly fitting safety goggles.

Skin and body protection

Chemical resistant apron. Protective gloves.

Respiratory protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene measures

Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

| | | | |
|-----------------------------|--------------------------|---------------------------------|---------|
| Physical state | Aerosol | Odor | Solvent |
| Appearance | Clear | Odor Threshold | |
| Color | Colorless | | |
| Property | Values | Remarks • Method | |
| pH | No information available | | |
| Melting/freezing point | No information available | | |
| Boiling point/boiling range | No information available | | |
| Flash Point | > -96.4 °C / > -141 °F | Closed cup: Based on propellant | |
| Evaporation rate | No information available | | |
| Flammability (solid, gas) | No information available | | |
| Flammability Limits in Air | | | |
| upper flammability limit | | | |
| lower flammability limit | No information available | | |
| Vapor pressure | | | |

| | | |
|--|--------------------------|----------------|
| Vapor density | No information available | |
| Specific gravity | 0.730 | |
| Water solubility | Practically insoluble | |
| Partition coefficient: n-octanol/water | | |
| Autoignition temperature | No information available | Not applicable |
| Hyphen | | |
| Viscosity | No information available | |
| Explosive properties | | |

Other information

| | |
|----------------|-----|
| VOC Content(%) | 100 |
|----------------|-----|

10. STABILITY AND REACTIVITY**Reactivity**

Stable under recommended storage conditions No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Extremes of temperature and direct sunlight.

Incompatible materials

Strong acids, alkalis, oxidizing agents.

Hazardous decomposition products

Carbon oxides , Hydrocarbons, Fumes.

11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure****Product Information**

| | |
|--------------|---|
| Inhalation | Avoid inhaling vapors or mists. Harmful if inhaled. May cause irritation to respiratory system. |
| Eye contact | Irritating to eyes. |
| Skin contact | Causes skin irritation. |
| Ingestion | Harmful and may be fatal if swallowed and enters airways. |

Component Information

| Chemical Name | LD50 Oral | LD50 Dermal | LC50 Inhalation |
|-------------------------------------|----------------------|--------------------------|--------------------------|
| PETROLEUM DISTILLATES 64742-89-8 | - | = 3000 mg/kg (Rabbit) | - |
| XYLENE 1330-20-7 | = 3500 mg/kg (Rat) | > 4350 mg/kg (Rabbit) | = 29.08 mg/L (Rat) 4 h |
| ETHYL BENZENE 100-41-4 | = 3500 mg/kg (Rat) | = 15400 mg/kg (Rabbit) | = 17.4 mg/L (Rat) 4 h |
| N-OCTANE 111-65-9 | - | - | > 24.88 mg/L (Rat) 4 h |
| HEPTANE 142-82-5 | - | = 3000 mg/kg (Rabbit) | > 73.5 mg/L (Rat) 4 h |
| CUMENE 98-82-8 | = 1400 mg/kg (Rat) | = 12300 µL/kg (Rabbit) | > 3577 ppm (Rat) 6 h |
| TOLUENE 108-88-3 | = 2600 mg/kg (Rat) | = 12000 mg/kg (Rabbit) | = 12.5 mg/L (Rat) 4 h |

| | | | |
|------------------------|----------------------|-------------------------|--------------------------|
| BENZENE 71-43-2 | = 810 mg/kg (Rat) | > 8200 mg/kg (Rabbit) | = 44.66 mg/L (Rat) 4 h |
| NAPHTHALENE 91-20-3 | = 1110 mg/kg (Rat) | = 1120 mg/kg (Rabbit) | > 0.4 mg/L (Rat) 4 h |

Information on toxicological effects**Symptoms**

Causes skin and eye irritation. May cause respiratory irritation. May cause drowsiness and dizziness. Harmful and may be fatal if ingested and enters airways.

Delayed and immediate effects as well as chronic effects from short and long-term exposure**Skin corrosion/irritation**

Causes skin irritation.

Eye damage/irritation

Causes eye irritation.

Irritation

Causes eye and skin irritation . May cause respiratory irritation.

Sensitization

No information available.

Germ cell mutagenicity

No information available.

Carcinogenicity

The table below indicates whether each agency has evaluated a listed ingredient as a carcinogen.

| Chemical Name | ACGIH | IARC | NTP | OSHA |
|---------------------------|-------|----------|------------------------|------|
| XYLENE 1330-20-7 | - | Group 3 | - | - |
| ETHYL BENZENE 100-41-4 | A3 | Group 2B | - | X |
| CUMENE 98-82-8 | A3 | Group 2B | Reasonably Anticipated | X |
| TOLUENE 108-88-3 | - | Group 3 | - | - |
| BENZENE 71-43-2 | A1 | Group 1 | Known | X |
| NAPHTHALENE 91-20-3 | A3 | Group 2B | Reasonably Anticipated | X |

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

A2 - Suspected Human Carcinogen

IARC: (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

Group 1 - Carcinogenic to Humans

NTP: (National Toxicity Program)

Known - Known Carcinogen

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive toxicity

This product does not contain any known or suspected reproductive hazards.

Specific target organ systemic toxicity (single exposure)

May cause respiratory irritation. May cause drowsiness and dizziness.

Specific target organ systemic toxicity (repeated exposure)

May cause damage to target organs listed below through prolonged or repeated exposure.

Chronic toxicity

Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Chronic hydrocarbon abuse has been associated with irregular heart rhythms and potential cardiac arrest.

Target Organ Effects

Eyes, Skin, Respiratory system, Central nervous system, Hearing.

Aspiration hazard

May be fatal if swallowed and enters airways.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document

| | |
|-------------------------------|----------------------|
| ATEmix (oral) | 10,206.00 mg/kg |
| ATEmix (dermal) | 210,901.10 mg/kg ppm |
| ATEmix (inhalation-vapor) | 6.7402 mg/l |
| ATEmix (inhalation-dust/mist) | 192.80 mg/l |

ATEmix (inhalation-vapor) 637 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

| Chemical Name | Algae/aquatic plants | Fish | Toxicity to microorganisms | Crustacea |
|--|---|--|----------------------------|--|
| PETROLEUM DISTILLATES 64742-89-8 | EC50: =4700mg/L (72h, Pseudokirchneriella subcapitata) | - | - | - |
| PROPANE/ISOBUTANE/N- BUTANE 68476-86-8 | - | - | - | - |
| XYLENE 1330-20-7 | - | LC50: =13.4mg/L (96h, Pimephales promelas) LC50: 2.661 - 4.093mg/L (96h, Oncorhynchus mykiss) LC50: 13.5 - 17.3mg/L (96h, Oncorhynchus mykiss) LC50: 13.1 - 16.5mg/L (96h, Lepomis macrochirus) LC50: =19mg/L (96h, Lepomis macrochirus) LC50: 7.711 - 9.591mg/L (96h, Lepomis macrochirus) LC50: 23.53 - 29.97mg/L (96h, Pimephales promelas) LC50: =780mg/L (96h, Cyprinus carpio) LC50: >780mg/L (96h, Cyprinus carpio) LC50: 30.26 - 40.75mg/L (96h, Poecilia reticulata) | - | EC50: =3.82mg/L (48h, water flea) LC50: =0.6mg/L (48h, Gammarus lacustris) |
| ETHYL BENZENE 100-41-4 | EC50: =4.6mg/L (72h, Pseudokirchneriella subcapitata) EC50: >438mg/L (96h, Pseudokirchneriella subcapitata) EC50: 2.6 - 11.3mg/L (72h, Pseudokirchneriella subcapitata) EC50: 1.7 - 7.6mg/L (96h, Pseudokirchneriella subcapitata) | LC50: 11.0 - 18.0mg/L (96h, Oncorhynchus mykiss) LC50: =4.2mg/L (96h, Oncorhynchus mykiss) LC50: 7.55 - 11mg/L (96h, Pimephales promelas) LC50: =32mg/L (96h, Lepomis macrochirus) LC50: 9.1 - 15.6mg/L (96h, Pimephales promelas) LC50: =9.6mg/L (96h, Poecilia reticulata) | - | EC50: 1.8 - 2.4mg/L (48h, Daphnia magna) |
| N-OCTANE 111-65-9 | - | - | - | EC50: =0.38mg/L (48h, water flea) |
| HEPTANE 142-82-5 | - | LC50: =375.0mg/L (96h, Cichlid fish) | - | - |
| CUMENE 98-82-8 | EC50: =2.6mg/L (72h, Pseudokirchneriella subcapitata) | LC50: 6.04 - 6.61mg/L (96h, Pimephales promelas) LC50: =4.8mg/L (96h, Oncorhynchus mykiss) LC50: =2.7mg/L (96h, Oncorhynchus mykiss) LC50: =5.1mg/L (96h, Poecilia reticulata) | - | EC50: =0.6mg/L (48h, Daphnia magna) EC50: 7.9 - 14.1mg/L (48h, Daphnia magna) |
| TOLUENE 108-88-3 | EC50: >433mg/L (96h, Pseudokirchneriella subcapitata) EC50: =12.5mg/L (72h, Pseudokirchneriella subcapitata) | LC50: 15.22 - 19.05mg/L (96h, Pimephales promelas) LC50: =12.6mg/L (96h, Pimephales promelas) LC50: 5.89 - 7.81mg/L (96h, Oncorhynchus mykiss) LC50: 14.1 - 17.16mg/L (96h, Oncorhynchus mykiss) LC50: =5.8mg/L (96h, Oncorhynchus mykiss) LC50: 11.0 - 15.0mg/L (96h, | - | EC50: 5.46 - 9.83mg/L (48h, Daphnia magna) EC50: =11.5mg/L (48h, Daphnia magna) |

| | | | | |
|------------------------|--|---|---|---|
| | | Lepomis macrochirus) LC50: =54mg/L (96h, Oryzias latipes) LC50: =28.2mg/L (96h, Poecilia reticulata) LC50: 50.87 - 70.34mg/L (96h, Poecilia reticulata) | | |
| BENZENE 71-43-2 | EC50: =29mg/L (72h, Pseudokirchneriella subcapitata) | LC50: 10.7 - 14.7mg/L (96h, Pimephales promelas) LC50: =5.3mg/L (96h, Oncorhynchus mykiss) LC50: =22.49mg/L (96h, Lepomis macrochirus) LC50: =28.6mg/L (96h, Poecilia reticulata) LC50: 22330 - 41160µg/L (96h, Pimephales promelas) LC50: 70000 - 142000µg/L (96h, Lepomis macrochirus) | - | EC50: 8.76 - 15.6mg/L (48h, Daphnia magna) EC50: =10mg/L (48h, Daphnia magna) |
| NAPHTHALENE 91-20-3 | - | LC50: 5.74 - 6.44mg/L (96h, Pimephales promelas) LC50: =1.6mg/L (96h, Oncorhynchus mykiss) LC50: 0.91 - 2.82mg/L (96h, Oncorhynchus mykiss) LC50: =1.99mg/L (96h, Pimephales promelas) LC50: =31.0265mg/L (96h, Lepomis macrochirus) | - | LC50: =2.16mg/L (48h, Daphnia magna) EC50: =1.96mg/L (48h, Daphnia magna) EC50: 1.09 - 3.4mg/L (48h, Daphnia magna) |

Persistence and degradability**Bioaccumulation**

| Chemical Name | Partition coefficient |
|--|-----------------------|
| PROPANE/ISOBUTANE/N-BUTANE 68476-86-8 | 2.8 |
| XYLENE 1330-20-7 | 3.15 |
| ETHYL BENZENE 100-41-4 | 3.6 |
| N-OCTANE 111-65-9 | 5.18 |
| HEPTANE 142-82-5 | 4.66 |
| CUMENE 98-82-8 | 3.55 |
| TOLUENE 108-88-3 | 2.73 |
| BENZENE 71-43-2 | 2.13 |
| NAPHTHALENE 91-20-3 | 3.4 |

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS**Waste treatment**

| | |
|-------------------------------|--|
| Waste Disposal Methods | This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261). Dispose of in accordance with federal, state, and local regulations. |
| Contaminated packaging | Do not re-use empty containers. Pressurized container: Do not pierce or burn, even after use. |

14. TRANSPORT INFORMATION

| | |
|-------------------|---|
| DOT Ground | LIMITED QUANTITY |
| IATA | UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD .QTY. |
| IMDG | UN1950, AEROSOLS, 2.1, LTD.QTY |

15. REGULATORY INFORMATION

International Inventories

| Chemical Name | TSCA | DSL/NDSL | EINECS/ELINCS | ENCS | IECSC | KECL | PICCS | AICS |
|----------------------------|------|----------|---------------|------|-------|------|-------|------|
| PETROLEUM DISTILLATES | X | X | X | X | X | X | X | X |
| PROPANE/ISOBUTANE/N-BUTANE | X | X | X | x | X | X | X | X |
| XYLENE | X | X | X | X | X | X | X | X |
| ETHYL BENZENE | X | X | X | X | X | X | X | X |
| N-OCTANE | X | X | X | X | X | X | X | X |
| HEPTANE | X | X | X | X | X | X | X | X |
| CUMENE | X | X | X | X | X | X | X | X |
| TOLUENE | X | X | X | X | X | X | X | X |
| BENZENE | X | X | X | X | X | X | X | X |
| NAPHTHALENE | X | X | X | X | X | X | X | X |

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
CHINA - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

| Chemical Name | CAS No. | Weight-% | SARA 313 - Threshold Values % |
|--------------------------|-----------|----------|-------------------------------|
| XYLENE - 1330-20-7 | 1330-20-7 | 10-20 | 1.0 |
| ETHYL BENZENE - 100-41-4 | 100-41-4 | 1-10 | 0.1 |
| CUMENE - 98-82-8 | 98-82-8 | <0.1 | 0.1 |
| TOLUENE - 108-88-3 | 108-88-3 | <0.1 | 1.0 |
| BENZENE - 71-43-2 | 71-43-2 | <0.1 | 0.1 |
| NAPHTHALENE - 91-20-3 | 91-20-3 | <0.1 | 0.1 |

SARA 311/312 Hazard Categories

| | |
|-----------------------------------|-----|
| Acute health hazard | Yes |
| Chronic Health Hazard | Yes |
| Fire hazard | Yes |
| Sudden release of pressure hazard | Yes |
| Reactive Hazard | No |

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

| Chemical Name | CWA - Reportable Quantities | CWA - Toxic Pollutants | CWA - Priority Pollutants | CWA - Hazardous Substances |
|---------------------------|-----------------------------|------------------------|---------------------------|----------------------------|
| XYLENE 1330-20-7 | 100 lb | | | X |
| ETHYL BENZENE 100-41-4 | 1000 lb | X | X | X |
| TOLUENE 108-88-3 | 1000 lb | X | X | X |
| BENZENE 71-43-2 | 10 lb | X | X | X |
| NAPHTHALENE 91-20-3 | 100 lb | X | X | X |

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

| Chemical Name | Hazardous Substances RQs | Extremely Hazardous Substances RQs | Reportable Quantity (RQ) |
|---------------------------|--------------------------|------------------------------------|--|
| XYLENE 1330-20-7 | 100 lb | | RQ 100 lb final RQ RQ 45.4 kg final RQ |
| ETHYL BENZENE 100-41-4 | 1000 lb | | RQ 1000 lb final RQ RQ 454 kg final RQ |
| CUMENE 98-82-8 | 5000 lb | | RQ 5000 lb final RQ RQ 2270 kg final RQ |
| TOLUENE 108-88-3 | 1000 lb | | RQ 1000 lb final RQ RQ 454 kg final RQ |
| BENZENE 71-43-2 | 10 lb | | RQ 10 lb final RQ RQ 4.54 kg final RQ |
| NAPHTHALENE 91-20-3 | 100 lb | | RQ 100 lb final RQ RQ 45.4 kg final RQ |

US State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals:



This product can expose you to chemicals including those listed below, which is [are] known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

| Chemical Name | California Proposition 65 |
|--------------------------|------------------------------------|
| ETHYL BENZENE - 100-41-4 | Cancer/ 1-10% |
| CUMENE - 98-82-8 | Cancer / <0.1% |
| TOLUENE - 108-88-3 | Developmental / <0.1% |
| BENZENE - 71-43-2 | Cancer Developmental (Male)/ <0.1% |
| NAPHTHALENE - 91-20-3 | Cancer / <0.1% |

Note

U.S. State Right-to-Know Regulations

| Chemical Name | New Jersey | Massachusetts | Pennsylvania |
|-------------------------------------|------------|---------------|--------------|
| PETROLEUM DISTILLATES 64742-89-8 | | | X |
| XYLENE 1330-20-7 | X | X | X |
| ETHYL BENZENE 100-41-4 | X | X | X |
| N-OCTANE 111-65-9 | X | X | X |
| HEPTANE 142-82-5 | X | X | X |
| CUMENE 98-82-8 | X | X | X |
| TOLUENE 108-88-3 | X | X | X |
| BENZENE 71-43-2 | X | X | X |
| NAPHTHALENE 91-20-3 | X | X | X |

EPA Pesticide Registration Number Not applicable

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

16. OTHER INFORMATION

NFPA

Health hazards 2

Flammability 4

Instability 0

Special hazards -

HMIS

Health hazards 2

Flammability 4

Physical hazards 1

Personal protection B

Chronic Hazard Star Legend

* = Chronic Health Hazard:

Prepared By

Regulatory Affairs

Issuing date

27-May-2015

Revision Date

26-Aug-2025

Revision Note

(M)SDS sections updated 2 3 9 10 11 15

Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet