SECTION I - IDENTIFICATION

PRODUCT IDENTIFIER: Aqua-Lube PRODUCT CODE: 8172, 8405, 9919, 9460 RECOMMENDED USE: Lubricant RESTRICTIONS ON USE: None Known COMPANY NAME: Tifco Industries

COMPANY ADDRESS: P.O. Box 40277, Houston, TX 77240-0277

COMPANY PHONE: 281-469-4800 **EMERGENCY PHONE:** 800-255-3924

SECTION II – HAZARDS IDENTIFICATION

CLASSIFICATION: Dissolved Gas

Skin Irritant: Category 2 Eye Irritant: Category 2A

Specific Target Organ Toxicity (Single Exposure): Category 3

Carcinogenicity: Category 1B Germ Cell Mutagenicity: Category 2 Skin Sensitization: Category 1 Aspiration Hazard: Category 1

HAZARD STATEMENT(S): DANGER: Contains gas under pressure; may explode if heated. Causes skin and serious eye irritation. May cause drowsiness or dizziness. May cause cancer. Suspected of causing genetic defects. May cause an allergic skin reaction. May be fatal if swallowed and enters airways.

This product contains the following percentage of chemicals of unknown toxicity: 0%

PRECAUTIONARY STATEMENTS: Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Wash hands thoroughly after handling. Wear protective gloves, protective clothing, and eye/face protection. If on skin: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. Contaminated work clothing must not be allowed out of the workplace. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Avoid breathing dust/fume/gas/mist/vapor/spray. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. If exposed or concerned: Get medical advice/attention. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. Store in a well-ventilated place. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. Dispose of contents/container in accordance with local, state, and federal law.

SYMBOL:







HAZARDS NOT OTHERWISE CLASSIFIED: N/A

SECTION III - COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	CAS NUMBER	PERCENT
Tetrachloroethylene	127-18-4	30-60%
Petroleum Distillates, Hydrotreated, Light	64742-47-8	10-20%
Trichloroethylene	79-01-6	5-15%
White Mineral Oil	8042-47-5	5-10%
Carbon Dioxide	124-38-9	1-5%

SECTION IV - FIRST AID MEASURES

EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

INGESTION: Rinse mouth with water. Do not induce vomiting unless directed by medical authority. Seek medical attention.

INHALATION: Move to fresh air. If not breathing administer artificial respiration, if breathing is difficult give oxygen.

SKIN: Immediately wash with soap and water for 15 minutes. Remove contaminated clothing and shoes immediately. Seek medical attention if irritation persists.

ACUTE HEALTH HAZARDS: Inhalation: dizziness, drowsiness, weakness, and fatigue

Eye: stinging, tearing, redness

Oral: Vomiting, discomfort, diarrhea

Skin: Prolonged or repeated contact may dry skin

CHRONIC HEALTH HAZARDS: Possible cancer causing agent and overexposure may also include damage to kidneys, liver, dizziness, headache, nausea, mental confusion, visual disturbances, dermatitis, lungs, blood, or central nervous system.

NOTE TO PHYSICIAN: Do not administer adrenaline or epinephrine to a victim of chlorinated solvent poisoning. This product contains ingredients that may be anticipated to be a carcinogen.

SECTION V - FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA: Use appropriate media for surrounding fire.

UNSUITABLE EXTINGUISHING MEDIA: N/A

SPECIAL FIRE FIGHTING PROCEDURES: Wear full protective clothing and NIOSH approved SCBA with full facepiece operated in positive pressure or pressure demand. Use water mist to keep material cool in fire situations.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Keep away from sparks, open flames, and hot surfaces. No smoking. Do not spray on an open flame or other ignition source.

HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon, chlorine, hydrogen chloride and phosgene.

SECTION VI - ACCIDENTAL RELEASE MEASURES

PERSONAL PROTECTIVE EQUIPMENT: Refer to section VIII for proper Personal Protective Equipment.

SPILL: Use absorbent on spill, sweep to clean. Dispose in accordance with local, state and federal laws. Small releases may be wiped up with wiping material.

WASTE DISPOSAL: Dispose of in accordance with federal, state, and local regulations.

RCRA STATUS: Waste solvent likely considered F002, hazardous halogenated solvents, under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION VII - HANDLING AND STORAGE

HANDLING AND STORAGE: Protect from sunlight. Store in a well ventilated place. Do not expose to temperatures exceeding 50°C/122°F. Pressurized container: Do not pierce or burn, even after use. Store locked up.

OTHER PRECAUTIONS: Containers of this material may be hazardous when empty since they retain product residues (vapors, liquid); observe all warning and precautions listed for the product. Keep out of the reach of children

INCOMPATIBILITY: Strong acids, strong alkalis, strong oxidizing agents, chemically active metals, such as aluminum, barium, lithium, sodium, magnesium, potassium, titanium, beryllium, concentrated nitric acid some plastics, rubbers, and coatings.

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

HAZARDOUS INGREDIENT	OSHA PEL	ACGIH TLV
Tetrachloroethylene	100 ppm	25 ppm
Petroleum Distillates, Hydrotreated, Light	500 ppm	500 ppm
Trichloroethylene	10 ppm	25 ppm
White Mineral Oil	5 mg/m3	10 mg/m3
Carbon Dioxide	5000 ppm	5000 ppm

ENGINEERING CONTROLS / VENTILATION: Use only outdoors or in a well-ventilated area.

RESPIRATORY PROTECTION: Wear NIOSH/MSHA approved organic vapor respiratory protection if used in confined, poorly ventilated areas.

Safety Data Sheet

PERSONAL PROTECTIVE EQUIPMENT: Safety glasses, gloves, and synthetic apron.

ADDITIONAL MEASURES: Wash hands thoroughly after handling. Do not breathe vapors. Do not eat, drink, or smoke while using product. Get medical attention if you feel unwell. If exposed or concerned: Get medical advice.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Clear, Colorless to Slight Tint Spray

ODOR: Chlorinated solvent odor **ODOR THRESHOLD:** N/D

pH: N/A

MELTING POINT/FREEZING POINT: N/D

INITIAL BOILING POINT AND BOILING RANGE: N/D

FLASH POINT: N/D

EVAPORATION RATE: > 3 (Fast)

FLAMMABILITY(solid/gas): Not considered a flammable aerosol or an extremely flammable aerosol by OSHA (29CFR 1910.1200)

UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS:

LOWER FLAMMABILITY LIMIT: N/D UPPER FLAMMABILITY LIMIT: N/D EXPLOSIVE LIMIT LOWER (%): N/D EXPLOISVE LIMIT UPPER (%): N/D VAPOR PRESSURE (mm Hg): N/D VAPOR DENSITY (AIR=1): N/D

RELATIVE DENSITY (H2O=1): 1.20-1.30

SOLUBILITY(IES): 0%

PARTITION COEFFICIENT: n-OCTANOL/WATER (Kow): N/D

AUTOIGNITION TEMPERATURE: N/D **DECOMPOSITION TEMPERATURE:** N/D

VISCOSITY: N/D

SECTION X – STABILITY AND REACTIVITY

REACTIVITY: Chemically active metals and bases.

CHEMICAL STABILITY: Stable

POSSIBLE HAZARDOUS REACTIONS: None Known

CONDITIONS TO AVOID: Temperatures greater than 122°F may cause bursting.

INCOMPATIBLE MATERIALS: Strong acids, strong alkalis, strong oxidizing agents, chemically active metals, such as aluminum, barium, lithium, sodium, magnesium, potassium, titanium, beryllium, concentrated nitric acid some plastics, rubbers, and coatings

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon, chlorine, hydrogen chloride and phosgene.

SECTION XI – TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION: Tetrachloroethylene (127-18-4) LD₅₀ (Oral, Rat) 2629 mg/kg; LC₅₀ (Inhalation, Mouse, 8hr) 34200 mg/m3 **Trichloroethylene** (79-01-6) LD₅₀ (Oral, Rat) 4920 mg/kg; LD₅₀ (Dermal, Rabbit) > 20000 mg/kg; LC₅₀ (Inhalation, Mouse, 4hr) 8450 ppm

ROUTES OF ENTRY: Eyes, Ingestion, Inhalation, Skin

EYES: Causes severe irritation, redness, tearing, pain, visual disturbance, may cause eye damage.

INGESTION: Causes gastrointestinal irritation, headaches, nausea, diarrhea, vomitting, abdominal cramps.

INHALATION: Irritation to respiratory tract, dizziness, headache, nausea, depression of central nervous system, prolonged exposure may cause unconsciousness, heart effects, liver effects, kidney effects, and death.

SKIN: Irritation likely, redness and pain. May cause localized defatting, blistering with prolonged skin contact. May be absorbed through the skin.

MEDICAL CONDITION AGGRAVATED: Excessive exposure will aggravate pre-existing disorders of eyes, skin, respiratory, liver, kidney, cardiovascular system, pulmonary illnesses, or central nervous system.

ACUTE HEALTH HAZARDS: Inhalation: dizziness, drowsiness, weakness, and fatigue

Eye: stinging, tearing, redness

Oral: Vomiting, discomfort, diarrhea

Skin: Prolonged or repeated contact may dry skin

Safety Data Sheet

CHRONIC HEALTH HAZARDS: Possible cancer causing agent and overexposure may also include damage to kidneys, liver, dizziness, headache, nausea, mental confusion, visual disturbances, dermatitis, lungs, blood, or central nervous system.

CARCINOGENICITY: OSHA: Yes ACGIH: A2 - Suspected NTP: 2 - Anticipated

IARC: 2A - Probable OTHER: CA Prop 65

SECTION XII - ECOLOGICAL INFORMATION

ECOTOXICITY: Trichloroethylene (79-01-6) LC₅₀ (96hr) Fish: 41 - 67 mg/L.

PERSISTENCE AND DEGRADABILITY: Component or components of this product are not biodegradable. BIOACCUMULATIVE POTENTIAL: Components in this mixture can bioaccumulate in aquatic organisms.

MOBILITY IN SOIL: This product is mobile in soil.

OTHER ADVERSE EFFECTS: This material is toxic to aquatic life.

SECTION XIII - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Dispose of in accordance with federal, state, and local regulations.

RCRA STATUS: Waste solvent likely considered F002, hazardous halogenated solvents, under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION XIV - TRANSPORT INFORMATION

PROPER SHIPPING NAME: Aerosols HAZARD CLASS/DIVISION: 2.2 (6.1) UN/NA NUMBER: UN 1950

PACKING GROUP: N/A

AIR SHIPMENT

PROPER SHIPPING NAME: Aerosols, Non-Flammable, Containing Substances in Division 6.1, Packaging Group III

HAZARD CLASS/DIVISION: 2.2 (6.1) UN 1950 UN/NA NUMBER:

PACKING GROUP: N/A

SHIPPING BY WATER: VESSEL (IMO/IMDG)

PROPER SHIPPING NAME: Aerosols, Toxic

HAZARD CLASS/DIVISION: 2.2 (6.1) UN 1950 **UN/NA NUMBER: PACKING GROUP:** N/A

ENVIRONMENTAL HAZARDS WATER: N/A

SECTION XV - REGULATORY INFORMATION

TSCA STATUS: All Chemicals are listed or exempt.

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT): Trichloroethylene (79-01-6)

Reportable Quantity = 100 lbs **Tetrachloroethylene** (127-18-4) Reportable Quantity = 100 lbs

SARA 311/312 HAZARD CATEGORIES: Acute Health, Chronic Health.

SARA 313 REPORTABLE INGREDIENTS: Tetrachloroethylene (127-18-4); Trichloroethylene (79-01-6)

STATE REGULATIONS: Prop 65: This product can expose you to chemicals including Trichloroethylene which is known to the State of California to cause cancer, birth defects, or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

INTERNATIONAL REGULATIONS: Trichloroethylene, CAS 79-01-6, - EC - yes, Japan – yes, Australia – yes, Korea – yes, Canada DSL – yes, Canada NDSL –no, Philipenes – yes. **Tetrachloroethylene** (127-18-4) WHMIS (Canada) Class D-1B: Material causing immediate and serious toxic effects (TOXIC). Class D-2A: Material causing other toxic effects (VERY TOXIC).

VOLATILE ORGANIC COMPOUNDS (VOC): 0%

NFPA HEALTH: HMIS HEALTH: NFPA FLAMMABILITY: 1 **HMIS FLAMMABILITY:** 1 NFPA REACTIVITY: HMIS REACTIVITY:

C NFPA OTHER: None **HMIS PROTECTION:**

Safety Data Sheet

SECTION XVI - OTHER INFORMATION

PREPARATION BY: Andrew Bach DATE PREPARED: 07/28/2014 REVISION DATE: 06/22/2020

N/A = Not Applicable; N/D = Not Determined

DISCLAIMER: To the best of our knowledge, information contained herein is accurate. However there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.