Aqua-Lube

SECTION I - IDENTIFICATION

PRODUCT IDENTIFIER: Aqua-Lube

PRODUCT CODE: 8172, 9919, 8405, 8181, 9912 **RECOMMENDED USE:** Solvent Degreaser

RESTRICTIONS ON USE: After December 8, 2026 this chemical substance (as defined in TSCA section 3(2))/product cannot be distributed in commerce to retailers for any use. After March 8, 2027, this chemical substance (as defined in TSCA section 3(2))/product is and can only be distributed in commerce or processed with a concentration of PCE equal to or greater than 0.1% by weight for the following purposes: (1) Processing as a reactant/intermediate; (2) Processing into formulation, mixture or reaction product; (3) Processing by repackaging; (4) Recycling; (5) Industrial and commercial use as solvent in closed-loop batch vapor degreasing; (7) Industrial and commercial use in maskant for chemical milling; (8) Industrial and commercial use as a processing aid in catalyst regeneration in petrochemical manufacturing; (9) Industrial and commercial use as a processing aid in sectors other than petrochemical manufacturing; (10) Industrial and commercial use as solvent for cold cleaning of tanker vessels; (11) Industrial and commercial use as energized electrical cleaner; (12) Industrial and commercial use in laboratory chemicals; (13) Industrial and commercial use in solvent-based adhesives and sealants; (14) Industrial and commercial use in dry cleaning in 3rd generation machines until December 20, 2027; (15) Industrial and commercial use in all dry cleaning and related spot cleaning until December 19, 2034; (16) Export; and (17) Disposal.

COMPANY NAME: TIFCO Industries, Inc.

COMPANY ADDRESS: P.O. Box 40277, Houston, TX 77240

COMPANY PHONE: 800-868-4326 **EMERGENCY PHONE:** 800-255-3924

SECTION II – HAZARDS IDENTIFICATION

CLASSIFICATION: Aerosols: Category 3

Skin Irritant: Category 2 Eye Irritant: Category 2A Aspiration Hazard: Category 1

Specific Target Organ Toxicity (Single Exposure): Category 3

Carcinogenicity: Category 2 Skin Sensitization: Category 1

Acute Toxicity, Inhalation: Category 4

HAZARD STATEMENT(S): DANGER: Pressurized container: may burst if heated. Causes skin and serious eye irritation. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. Suspected of causing cancer. May cause an allergic skin reaction. Harmful if inhaled.

This product contains the following percentage of chemicals of unknown toxicity: 0%

PRECAUTIONARY STATEMENTS: Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. -No smoking. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Avoid breathing fumes, mist, vapors, and spray. Wear protective gloves, eye protection, and protective clothing. Wash hands thoroughly after handling. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing and wash before reuse. Contaminated work clothing must not be allowed out of the workplace. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. IF SWALLOWED: Get emergency medical help immediately. Do NOT induce vomiting. IF EXPOSED OR CONCERNED: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get emergency medical help. Store in a well-ventilated place. Dispose of contents and container in accordance with local, state, and national regulations.

SYMBOL:





HAZARDS NOT OTHERWISE CLASSIFIED: N/A

Aqua-Lube

SECTION III - COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	CAS NUMBER	PERCENT
Tetrachloroethylene	127-18-4	60-80%
Mineral Spirits	8052-41-3	10-30%
Mineral Oil	8042-47-5	7-13%
Carbon dioxide	124-38-9	3-7%
Barium Sulfonate	Proprietary	0.1-1%

Trade Secret Information: A specific chemical identity and/or percentage of composition has been withheld as a trade secret.

SECTION IV - FIRST AID MEASURES

EYES: Immediately flush with water for 15 minutes while holding eyelids open. Seek immediate medical attention.

INGESTION: Rinse mouth out with water. Seek medical attention.

INHALATION: Move to fresh air. If not breathing administer artificial respiration, if breathing is difficult give oxygen.

SKIN: Immediately wash with soap and water for 15 minutes. Remove contaminated clothing and shoes immediately. Seek medical attention if irritation persists.

ACUTE HEALTH HAZARDS: Eyes: redness, tearing, blurred vision. Skin: defatting and dermatitis. Inhalation: anesthetic, irritation, central nervous system (CNS) depression. Oral: aspiration risk, abdominal irritation, nausea, vomiting, and diarrhea.

CHRONIC HEALTH HAZARDS: Possible cancer-causing agent. Overexposure may cause dermatitis, dizziness, headache, nausea, mental confusion, and visual disturbances and may damage kidneys, liver, lungs, blood or central nervous system.

NOTE TO PHYSICIAN: Do not administer adrenaline or epinephrine to a victim of chlorinated solvent poisoning. This product contains ingredients that may be anticipated to be a carcinogen.

SECTION V - FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA: Dry chemical, foam or carbon dioxide.

UNSUITABLE EXTINGUISHING MEDIA: Water spray/stream.

SPECIAL FIRE FIGHTING PROCEDURES: Wear NIOSH approved Self Contained Breathing Apparatus with a full face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires. Use water spray only to cool exposed containers.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Keep away from heat, sparks, open flames and hot surfaces. No smoking. HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon, chlorine, hydrogen chloride and phosgene.

SECTION VI – ACCIDENTAL RELEASE MEASURES

PERSONAL PROTECTIVE EQUIPMENT: Refer to section VIII for proper Personal Protective Equipment.

SPILL: Use absorbent on spill, sweep to clean. Dispose in accordance with local, state and federal laws. Small releases may be wiped up with wiping material.

WASTE DISPOSAL: Dispose of in accordance with local, state and federal regulations.

RCRA STATUS: Waste solvent likely considered U210 (Tetrachloroethylene) under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION VII – HANDLING AND STORAGE

HANDLING AND STORAGE: Store in a cool, dry area. Keep drums covered and bung holes tightly shut. Follow label directions. **OTHER PRECAUTIONS:** Containers of this material may be hazardous when empty since they retain product residues (vapors, liquid); observe all warning and precautions listed for the product. Keep out of the reach of children.

INCOMPATIBILITY: Strong acids, strong alkalis, strong oxidizing agents, chemically active metals, such as aluminum, barium, lithium, sodium, magnesium, potassium, titanium, beryllium, concentrated nitric acid some plastics, rubbers, and coatings.

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

HAZARDOUS INGREDIENT	OSHA PEL	ACGIH TLV
Tetrachloroethylene	100 ppm	25 ppm
Mineral Spirits	Not Established	Not Established
Mineral Oil	5 mg/m^3	5 mg/m^3
Barium Sulfonate	Not Established	Not Established
Carbon dioxide	5000 ppm	5000 ppm

Aqua-Lube

ENGINEERING CONTROLS / VENTILATION: Use only outdoors or in a well-ventilated area.

RESPIRATORY PROTECTION: Wear NIOSH/MSHA approved organic vapor respiratory protection.

PERSONAL PROTECTIVE EQUIPMENT: Safety glasses, gloves, protective clothing and vapor respirator.

ADDITIONAL MEASURES: Wash hands thoroughly after handling. Wash hands thoroughly with soap and water after use. Use good industrial hygiene practices.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Clear Aerosol Spray.

ODOR: Chlorinated solvent. **ODOR THRESHOLD:** 1ppm

pH: N/A

MELTING POINT/FREEZING POINT: N/D

INITIAL BOILING POINT AND BOILING RANGE: N/D

FLASH POINT: N/D

EVAPORATION RATE: N/D

FLAMMABILITY (solid/gas): Not considered a flammable aerosol or an extremely flammable aerosol by OSHA (29CFR 1910.1200).

UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS:

LOWER FLAMMABILITY LIMIT: N/D UPPER FLAMMABILITY LIMIT: N/D EXPLOSIVE LIMIT LOWER (%): N/D EXPLOSIVE LIMIT UPPER (%): N/D VAPOR PRESSURE (mm Hg): N/D VAPOR DENSITY (AIR=1): N/D

RELATIVE DENSITY (H2O=1): 1.4-1.6 @ 77°F (25°C)

SOLUBILITY(IES): Negligible.

PARTITION COEFFICIENT: n-OCTANOL/WATER (Kow): N/D

AUTOIGNITION TEMPERATURE: N/D **DECOMPOSITION TEMPERATURE:** N/D

VISCOSITY: N/D

SECTION X – STABILITY AND REACTIVITY

REACTIVITY: None known. **CHEMICAL STABILITY:** Stable.

POSSIBLE HAZARDOUS REACTIONS: None known.

CONDITIONS TO AVOID: Elevated temperatures and excessive heat. Avoid incompatible materials.

INCOMPATIBLE MATERIALS: Strong acids, strong alkalis, strong oxidizing agents, chemically active metals, such as aluminum, barium, lithium, sodium, magnesium, potassium, titanium, beryllium, concentrated nitric acid some plastics, rubbers, and coatings

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon, chlorine, hydrogen chloride and phosgene.

SECTION XI - TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION: Tetrachloroethylene (Perchloroethylene) (127-18-4): LD₅₀ (Oral, Rat) 2629 mg/kg; LC₅₀ (Inhalation, Mouse, 8hr) 34200 mg/m³.

ROUTES OF ENTRY: Eyes, Ingestion, Inhalation, Skin

EYES: Causes severe irritation, redness, tearing, pain, visual disturbance; may cause eye damage.

INGESTION: Causes gastrointestinal irritation, nausea, vomiting, abdominal cramps.

INHALATION: Causes respiratory tract irritation, dizziness, headache, nausea, depression of central nervous system (CNS). Prolonged exposure may cause unconsciousness, heart effects, liver effects, kidney effects and death.

SKIN: Irritation likely, redness and pain. May cause localized defatting, blistering with prolonged skin contact. May be absorbed through the skin.

MEDICAL CONDITION AGGRAVATED: Excessive exposure will aggravate pre-existing disorders of eyes, skin, respiratory, liver, kidney, cardiovascular system, pulmonary illnesses, or central nervous system (CNS).

ACUTE HEALTH HAZARDS: Eyes: redness, tearing, blurred vision. Skin: defatting and dermatitis. Inhalation: anesthetic, irritation, central nervous system (CNS) depression. Oral: aspiration risk, abdominal irritation, nausea, vomiting, and diarrhea.

CHRONIC HEALTH HAZARDS: Possible cancer-causing agent. Overexposure may cause dermatitis, dizziness, headache, nausea, mental confusion, and visual disturbances and may damage kidneys, liver, lungs, blood or central nervous system.

CARCINOGENICITY: OSHA: No Data Available ACGIH: A3 - Animal Carcinogen NTP: 2 - Anticipated

Aqua-Lube

IARC: 2A - Probable OTHER: CA Prop 65

SECTION XII - ECOLOGICAL INFORMATION

ECOTOXICITY: Tetrachloroethylene (Perchloroethylene) (127-18-4): LC₅₀ (Pimephales promelas, 96h) 18.4 mg/L; LC₅₀

 $(\textit{Oncorhynchus mykiss}, 96hr) \ 5 \ mg/L; \ LC_{50} \ (\textit{Lepomis macrochirus}, 96hr) \ 12.9 \ mg/L; \ LC_{50} \ (\textit{Cyprinodon variegatus}, 96h) \ 29.4 \ - 10.0 \ mg/L; \ LC_{50} \ (\textit{Cyprinodon variegatus}, 96hr) \ 29.4 \ - 10.0 \ mg/L; \ LC_{50} \ (\textit{Cyprinodon variegatus}, 96hr) \ 29.4 \ - 10.0 \ mg/L; \ LC_{50} \ (\textit{Cyprinodon variegatus}, 96hr) \ 29.4 \ - 10.0 \ mg/L; \ LC_{50} \ (\textit{Cyprinodon variegatus}, 96hr) \ 29.4 \ - 10.0 \ mg/L; \ LC_{50} \ (\textit{Cyprinodon variegatus}, 96hr) \ 29.4 \ - 10.0 \ mg/L; \ LC_{50} \ (\textit{Cyprinodon variegatus}, 96hr) \ 29.4 \ - 10.0 \ mg/L; \ LC_{50} \ (\textit{Cyprinodon variegatus}, 96hr) \ 29.4 \ - 10.0 \ mg/L; \ LC_{50} \ (\textit{Cyprinodon variegatus}, 96hr) \ 29.4 \ - 10.0 \ mg/L; \ LC_{50} \ (\textit{Cyprinodon variegatus}, 96hr) \ 29.4 \ - 10.0 \ mg/L; \ LC_{50} \ (\textit{Cyprinodon variegatus}, 96hr) \ 29.4 \ - 10.0 \ mg/L; \ LC_{50} \ (\textit{Cyprinodon variegatus}, 96hr) \ 29.4 \ - 10.0 \ mg/L; \ LC_{50} \ (\textit{Cyprinodon variegatus}, 96hr) \ 29.4 \ - 10.0 \ mg/L; \ LC_{50} \ (\textit{Cyprinodon variegatus}, 96hr) \ 29.4 \ - 10.0 \ mg/L; \ LC_{50} \ (\textit{Cyprinodon variegatus}, 96hr) \ 29.4 \ - 10.0 \ mg/L; \ LC_{50} \ (\textit{Cyprinodon variegatus}, 96hr) \ 29.4 \ - 10.0 \ mg/L; \ LC_{50} \ (\textit{Cyprinodon variegatus}, 96hr) \ 29.4 \ - 10.0 \ mg/L; \ LC_{50} \ (\textit{Cyprinodon variegatus}, 96hr) \ 29.4 \ - 10.0 \ mg/L; \ LC_{50} \ (\textit{Cyprinodon variegatus}, 96hr) \ 29.4 \ - 10.0 \ mg/L; \ LC_{50} \ (\textit{Cyprinodon variegatus}, 96hr) \ 29.4 \ - 10.0 \ mg/L; \ LC_{50} \ (\textit{Cyprinodon variegatus}, 96hr) \ 29.4 \ - 10.0 \ mg/L; \ LC_{50} \ (\textit{Cyprinodon variegatus}, 96hr) \ 29.4 \ - 10.0 \ mg/L; \ LC_{50} \ (\textit{Cyprinodon variegatus}, 96hr) \ 29.4 \ - 10.0 \ mg/L; \ LC_{50} \ (\textit{Cyprinodon variegatus}, 96hr) \ 29.4 \ - 10.0 \ mg/L; \ LC_{50} \ (\textit{Cyprinodon variegatus}, 96hr) \ 29.4 \ - 10.0 \ mg/L; \ LC_{50} \ (\textit{Cyprinodon variegatus}, 96hr) \ 29.4 \ - 10.0 \ mg/L; \ LC_{50} \ (\textit{Cyprinodon variegatus}, 96hr) \ 29.4 \ - 10.0 \ mg/L; \ LC_{50} \ (\textit{Cyprinodon variegatus}, 96hr) \ 29.4 \ - 10.0 \ mg/L; \ LC_{50} \$

52.2 mg/L; LC₅₀ (Mysid shrimp, 96h) 10.2 mg/L; EC₅₀ (Daphnia magna, 48h) 18 mg/L.

PERSISTENCE AND DEGRADABILITY: Component or components of this product are not biodegradable.

BIOACCUMULATIVE POTENTIAL: This product is not expected to bioaccumulate.

MOBILITY IN SOIL: This product is mobile in soil.

OTHER ADVERSE EFFECTS: This material is toxic to aquatic life.

SECTION XIII - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Dispose of in accordance with local, state and federal regulations.

RCRA STATUS: Waste solvent likely considered U210 (Tetrachloroethylene) under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION XIV - TRANSPORT INFORMATION

PROPER SHIPPING NAME: Aerosols, Ltd. Qty.

HAZARD CLASS/DIVISION: 2.2 (6.1) UN/NA NUMBER: UN1950 PACKING GROUP: N/A

AIR SHIPMENT

PROPER SHIPPING NAME: Aerosols, non-flammable, containing substances in Division 6.1, Packing Group III.

HAZARD CLASS/DIVISION: 2.2 (6.1) UN/NA NUMBER: UN1950 PACKING GROUP: N/A

SHIPPING BY WATER: VESSEL (IMO/IMDG)

PROPER SHIPPING NAME: Aerosols, toxic. HAZARD CLASS/DIVISION: 2.2 (6.1) UN/NA NUMBER: UN1950

PACKING GROUP: N/A

ENVIRONMENTAL HAZARDS WATER: Marine Pollutant.

SECTION XV - REGULATORY INFORMATION

TSCA STATUS: All chemicals are listed or exempt.

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT): Tetrachloroethylene

(Perchloroethylene) (127-18-4) Reportable Quantity = 100 pounds.

SARA 311/312 HAZARD CATEGORIES: Health Hazard and Physical Hazard.

SARA 313 REPORTABLE INGREDIENTS: Tetrachloroethylene (Perchloroethylene) (127-18-4).

STATE REGULATIONS: California Proposition 65: WARNING: This product can expose you to chemicals including Tetrachloroethylene (Perchloroethylene), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

INTERNATIONAL REGULATIONS: Tetrachloroethylene (127-18-4) WHMIS (Canada) Class D-1B: Material causing immediate and serious toxic effects (TOXIC). Class D-2A: Material causing other toxic effects (VERY TOXIC).

VOLATILE ORGANIC COMPOUNDS (VOC): 16.5%

Tetrachloroethylene (Perchloroethylene or PCE) containing products: After December 8, 2026 this chemical substance (as defined in TSCA section 3(2))/product cannot be distributed in commerce to retailers for any use. After March 8, 2027, this chemical substance (as defined in TSCA section 3(2))/product is and can only be distributed in commerce or processed with a concentration of PCE equal to or greater than 0.1% by weight for the following purposes: (1) Processing as a reactant/intermediate; (2) Processing into formulation, mixture or reaction product; (3) Processing by repackaging; (4) Recycling; (5) Industrial and commercial use as solvent in open-top batch vapor degreasing; (6) Industrial and commercial use as solvent in closed-loop batch vapor degreasing; (7) Industrial and commercial use in maskant for chemical milling; (8) Industrial and commercial use as a processing aid in sectors other than petrochemical manufacturing; (10) Industrial and commercial use as solvent for cold cleaning of tanker vessels; (11) Industrial and commercial use as energized electrical cleaner; (12)

Aqua-Lube

Industrial and commercial use in laboratory chemicals; (13) Industrial and commercial use in solvent-based adhesives and sealants; (14) Industrial and commercial use in dry cleaning in 3rd generation machines until December 20, 2027; (15) Industrial and commercial use in all dry cleaning and related spot cleaning until December 19, 2034; (16) Export; and (17) Disposal.

NFPA HEALTH: 3
NFPA FLAMMABILITY: 1
NFPA REACTIVITY: 0
NFPA OTHER: None
HMIS HEALTH: *3
HMIS FLAMMABILITY: 1
HMIS REACTIVITY: 0
HMIS PROTECTION: C

SECTION XVI - OTHER INFORMATION

PREPARATION BY: Craig Bernard DATE PREPARED: 06/09/2017 REVISION DATE: 08/04/2025

N/A = Not Applicable; N/D = Not Determined

DISCLAIMER: To the best of our knowledge, information contained herein is accurate. However, there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.