

Safety Data Sheet

SECTION I - IDENTIFICATION

PRODUCT NAME: Aqua Lube
PRODUCT CODE: 9460, 8172, 9919, 8405, 8181, 9912
PRODUCT USE: Lubricant
COMPANY NAME: Tifco Industries
COMPANY ADDRESS: PO Box 40277, Houston, TX 77240-0277
COMPANY PHONE: 281-469-4800
EMERGENCY PHONE: 800-255-3924

SECTION II – HAZARDS IDENTIFICATION

CLASSIFICATION: Dissolved Gas
Skin Irritant: Category 2
Eye Irritant: Category 2A
Specific Target Organ Toxicity (Single Exposure): Category 3
Carcinogenicity: Category 1B
Germ Cell Mutagenicity: Category 2

HAZARD STATEMENT(S): DANGER: Contains gas under pressure; May explode if heated. Causes skin and serious eye irritation. May cause drowsiness and dizziness. May cause cancer. Suspected of causing genetic defects.

This product contains the following percentage of chemicals of unknown toxicity: 0%

PRECAUTIONARY STATEMENTS: Keep away from heat, sparks, open flames, and hot surfaces. –No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves, eye protection, and protective clothing. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Store locked up. Dispose of contents and container in accordance with local, state, and national regulations. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. If exposed or concerned: Get medical attention. Avoid breathing fumes, mist, vapors, and spray. Get medical advice or attention if you feel unwell. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell.



SYMBOL:

HAZARDS NOT OTHERWISE CLASSIFIED: N/A

SECTION III – COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	CAS NUMBER	PERCENT
Carbon Dioxide	124-38-9	1-5%
Trichloroethylene	79-01-6	7-13%
Tetrachloroethylene	127-18-4	30-60%
Hydrotreated Heavy Naphthenic Petroleum Distillate	64742-52-5	5-10%
Mineral Spirits	8052-41-3	10-30%

SECTION IV - FIRST AID MEASURES

EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

INGESTION: Rinse mouth with water. Do not induce vomiting unless directed by medical authority. Seek medical attention.

INHALATION: Move to fresh air. If not breathing administer artificial respiration, if breathing is difficult give oxygen.

SKIN: Immediately wash with soap and water for 15 minutes. Remove contaminated clothing and shoes immediately. Seek medical attention if irritation persists.

ACUTE HEALTH HAZARDS: Inhalation: dizziness, drowsiness, weakness, and fatigue

Safety Data Sheet

Eye: Stinging, tearing, redness Oral: Vomiting, discomfort, diarrhea Skin: Prolonged or repeated contact may dry skin
CHRONIC HEALTH HAZARDS: Possible cancer causing agent and overexposure may also include damage to kidneys, liver, dizziness, headache, nausea, mental confusion, visual disturbances, dermatitis, lungs, blood, or central nervous system.
NOTE TO PHYSICIAN: Do not administer adrenaline or epinephrine to a victim of chlorinated solvent poisoning. This product contains ingredients that may be anticipated to be a carcinogen.

SECTION V – FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA: Use appropriate media for surrounding fire. **UNSUITABLE EXTINGUISHING MEDIA:** N/A
SPECIAL FIRE FIGHTING PROCEDURES: Wear full protective clothing and NIOSH approved SCBA with full facepiece operated in positive pressure or pressure demand. Use water mist to keep material cool in fire situations.
UNUSUAL FIRE AND EXPLOSION HAZARDS: Keep away from sparks, open flames, and hot surfaces. No smoking. Do not spray on an open flame or other ignition source.
HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon, chlorine, hydrogen chloride and phosgene.

SECTION VI – ACCIDENTAL RELEASE MEASURES

PERSONAL PROTECTIVE EQUIPMENT: Refer to section VIII for proper Personal Protective Equipment.
SPILL: Use absorbent on spill, sweep to clean. Dispose in accordance with local, state and federal laws. Small releases may be wiped up with wiping material.
WASTE DISPOSAL: Dispose of in accordance with federal, state, and local regulations.
RCRA STATUS: Waste solvent likely considered U228 (Trichloroethylene), hazardous, under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION VII – HANDLING AND STORAGE

HANDLING AND STORAGE: Protect from sunlight. Store in a well ventilated place. Do not expose to temperatures exceeding 50°C/122°F. Pressurized container: Do not pierce or burn, even after use. Store locked up.
OTHER PRECAUTIONS: Containers of this material may be hazardous when empty since they retain product residues (vapors, liquid); observe all warning and precautions listed for the product. Keep out of the reach of children.
INCOMPATIBILITY: Strong acids, strong alkalis, strong oxidizing agents, chemically active metals, such as aluminum, barium, lithium, sodium, magnesium, potassium, titanium, beryllium, concentrated nitric acid some plastics, rubbers, and coatings.

SECTION VIII – EXPOSURE CONTROLS/PERSONAL PROTECTION

HAZARDOUS INGREDIENT	OSHA PEL	ACGIH TLV
Carbon Dioxide	5000 ppm	5000 ppm
Trichloroethylene	10 ppm	25 ppm
Tetrachloroethylene	100 ppm	25 ppm
Hydrotreated Heavy Naphthenic Petroleum Distillate	0.2 mg/m ³	0.2 mg/m ³
Mineral Spirits	500 ppm	500 ppm

ENGINEERING CONTROLS / VENTILATION: Use only outdoors or in a well-ventilated area.
RESPIRATORY PROTECTION: Wear NIOSH/MSHA approved organic vapor respiratory protection if used in confined, poorly ventilated areas.
PERSONAL PROTECTIVE EQUIPMENT: Safety glasses, Gloves, and Synthetic apron.
ADDITIONAL MEASURES: Wash hands thoroughly after handling. Do not breathe vapors. Do not eat, drink, or smoke while using product. Get medical attention if you feel unwell. If exposed or concerned: Get medical advice.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Clear, Colorless to Slight Tint Spray **ODOR:** Chlorinated solvent odor
ODOR THRESHOLD: N/D **BOILING POINT:** >188°F (87°C)
FREEZING POINT: N/D **FLASH POINT:** N/D
FLAMMABILITY: Not considered a flammable aerosol or an extremely flammable aerosol by OSHA (29CFR 1910.1200)
AUTOIGNITION TEMPERATURE: N/D **LOWER FLAMMABILITY LIMIT:** N/D

Safety Data Sheet

UPPER FLAMMABILITY LIMIT: N/D

VAPOR DENSITY (AIR=1): > 2

SPECIFIC GRAVITY (H₂O=1): 1.365

SOLIDS (%): N/A

PARTITION COEFFICIENT: n-OCTANOL/WATER (K_{ow}): N/D

VOLATILE ORGANIC COMPOUNDS (VOC): 26.68%

DECOMPOSITION TEMPERATURE: >400°C

VAPOR PRESSURE (mm Hg): 59

EVAPORATION RATE: > 3 (Fast)

pH: N/A

SOLUBILITY IN WATER: 0%

VOLATILITY INCLUDING WATER (%): 100 %

DIELECTRIC STRENGTH (Volts): N/D

VISCOSITY: N/D

SECTION X – STABILITY AND REACTIVITY DATA

REACTIVITY: Chemically active metals and bases.

CHEMICAL STABILITY: Stable

CONDITIONS TO AVOID: Temperatures greater than 122°F may cause bursting.

INCOMPATIBILITY: Strong acids, strong alkalis, strong oxidizing agents, chemically active metals, such as aluminum, barium, lithium, sodium, magnesium, potassium, titanium, beryllium, concentrated nitric acid some plastics, rubbers, and coatings.

HAZARDOUS DECOMPOSITION OR BY-PRODUCT: Oxides of carbon, chlorine, hydrogen chloride and phosgene.

POSSIBLE HAZARDOUS REACTIONS: None Known

SECTION XI – TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION: Tetrachloroethylene (127-18-4) LD₅₀ (Oral, Rat) 2629 mg/kg; LD₅₀ (Dermal, Rabbit) > 3228 mg/kg; LD₅₀ (IPR, Mouse) 4700 mg/kg; LC₅₀ (Inhalation, Mouse, 4hr) 5200 ppm; LC₅₀ (Inhalation, Rat, 8hr) 34200 mg/m³

Trichloroethylene (79-01-6) LD₅₀ (Oral, Rat) 5,650 mg/kg; Tumorigen, mutagenic reproductive effects in humans.

ROUTES OF ENTRY: Eyes, Ingestion, Inhalation, Skin

EYES: Causes severe irritation, redness, tearing, pain, visual disturbance, may cause eye damage.

INGESTION: Causes gastrointestinal irritation, headaches, nausea, diarrhea, vomiting, abdominal cramps.

INHALATION: Irritation to respiratory tract, dizziness, headache, nausea, depression of central nervous system, prolonged exposure may cause unconsciousness, heart effects, liver effects, kidney effects, and death.

SKIN: Irritation likely, redness and pain. May cause localized defatting, blistering with prolonged skin contact. May be absorbed through the skin.

MEDICAL CONDITION AGGRAVATED: Excessive exposure will aggravate pre-existing disorders of eyes, skin, respiratory, liver, kidney, cardiovascular system, pulmonary illnesses, or central nervous system.

ACUTE HEALTH HAZARDS: Inhalation: dizziness, drowsiness, weakness, and fatigue

Eye: stinging, tearing, redness

Oral: Vomiting, discomfort, diarrhea

Skin: Prolonged or repeated contact may dry skin

CHRONIC HEALTH HAZARDS: Possible cancer causing agent and overexposure may also include damage to kidneys, liver, dizziness, headache, nausea, mental confusion, visual disturbances, dermatitis, lungs, blood, or central nervous system.

CARCINOGENICITY: OSHA: Yes ACGIH: A2 - Suspected NTP: 2 - Anticipated

IARC: 2A - Probable OTHER: CA Prop 65

SECTION XII – ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: Trichloroethylene (79-01-6) LC₅₀ (96hr) Fish: 10 and 100 mg/L. Slightly toxic to aquatic life.

BIODEGRADABILITY: Component or components of this product are not biodegradable.

BIOACCUMULATION: Components in this mixture can bioaccumulate in aquatic organisms.

SOIL MOBILITY: This product is mobile in soil.

OTHER ECOLOGICAL HAZARDS: This material is toxic to aquatic life.

SECTION XIII – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Dispose of in accordance with federal, state, and local regulations.

RCRA STATUS: Waste solvent likely considered U228 (Trichloroethylene), hazardous, under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

Safety Data Sheet

SECTION XIV - TRANSPORTATION INFORMATION

PROPER SHIPPING NAME: Aerosols, Ltd. Qty.
HAZARD CLASS/DIVISION: 2.2
UN/NA NUMBER: UN 1950
PACKAGING GROUP: N/A

AIR SHIPMENT

PROPER SHIPPING NAME: Aerosols, Ltd. Qty.
HAZARD CLASS/DIVISION: 2.2
UN/NA NUMBER: UN 1950

SHIPPING BY WATER:

VESSEL (IMO/IMDG)
PROPER SHIPPING NAME: Aerosols, Ltd. Qty.
HAZARD CLASS/DIVISION: 2.2
UN/NA NUMBER: UN 1950
ENVIRONMENTAL HAZARDS WATER: N/A

SECTION XV - REGULATORY INFORMATION

TSCA STATUS: All Chemicals are listed or exempt.

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT): Trichloroethylene (79-01-6)

Reportable Quantity = 100 lbs

SARA 311/312 HAZARD CATEGORIES: Acute Health, Chronic Health.

SARA 313 REPORTABLE INGREDIENTS: Tetrachloroethylene (127-18-4); Trichloroethylene (79-01-6)

STATE REGULATIONS: Tetrachloroethylene (127-18-4) and Trichloroethylene (79-01-6) are known to the state of California to cause cancer.

Trichloroethylene (79-01-6) Right-to-Know acts for New York, Rhode Island, Pennsylvania, Florida, Minnesota, Massachusetts, Michigan, New Jersey, Tennessee; Spill Reporting for Massachusetts, New Jersey, Louisiana; Connecticut hazardous material survey; Illinois toxic substances disclosure to employee act

INTERNATIONAL REGULATIONS: Trichloroethylene, CAS 79-01-6, - EC - yes, Japan - yes, Australia - yes, Korea - yes, Canada DSL - yes, Canada NDSL -no, Philipenes - yes.

NFPA HEALTH: 2
NFPA FLAMMABILITY: 1
NFPA REACTIVITY: 0
NFPA OTHER: None

HMIS HEALTH: 2
HMIS FLAMMABILITY: 1
HMIS REACTIVITY: 0
HMIS PROTECTION: C

SECTION XVI - ADDITIONAL INFORMATION

PREPARATION BY: Jonathon Jarvis

DATE PREPARED: 07/28/2014

REVISION DATE: 11/18/2014

N/A = Not Applicable; N/D = Not Determined

DISCLAIMER: To the best of our knowledge, information contained herein is accurate. However there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.