



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
US OSHA Hazard Communication Standard (29 CFR 1910.1200)

Revision date 19-Aug-2025

Version 2

1. Identification

Product identifier

Product Name Cummins Apex Red

Other means of identification

Product Code(s) 8222, 9858, 8385

UN/ID no UN1950

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use No information available

Restrictions on use No information available

Details of the supplier of the safety data sheet

Supplier Address

TIFCO Industries, Inc. PO Box
40277 Houston, TX 77240
United States
Phone: (281) 571-6000

Emergency telephone number

800-255-3924

2. Hazard(s) identification

Classification

Flammable aerosols	Category 1
Gases under pressure	Liquefied gas
Acute toxicity - Oral	Category 4
Skin sensitization	Category 1
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1A
Reproductive toxicity	Category 1B

Hazards not otherwise classified (HNOC)

Not applicable

Label elements

**Danger****Hazard statements**

Extremely flammable aerosol. Pressurized container: May burst if heated.
Contains gas under pressure; may explode if heated.
Harmful if swallowed.
May cause an allergic skin reaction.
May cause genetic defects.
May cause cancer.
May damage fertility or the unborn child.

Precautionary Statements - Prevention

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Wear protective gloves/protective clothing/eye protection/face protection.
Wash face, hands and any exposed skin thoroughly after handling.
Do not eat, drink or smoke when using this product.
Avoid breathing dust/fume/gas/mist/vapors/spray.
Contaminated work clothing must not be allowed out of the workplace.
Use only outdoors or in a well-ventilated area.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Do not spray on an open flame or other ignition source.
Pressurized container: Do not pierce or burn, even after use.

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF ON SKIN: Wash with plenty of water and soap.
If skin irritation or rash occurs: Get medical advice/attention.
Wash contaminated clothing before reuse.
IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell.
Rinse mouth.

Precautionary Statements - Storage

Store locked up.
Store in a well-ventilated place. Keep container tightly closed.
Protect from sunlight.
Do not expose to temperatures exceeding 50 °C/122 °F.

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant.

Unknown acute toxicity

30.92389 % of the mixture consists of ingredient(s) of unknown acute oral toxicity.

Other information

No information available.

3. Composition/information on ingredients**Substance**

Not applicable.

Mixture

Chemical name	CAS No.	Weight-%	Trade secret
Propane	74-98-6	20 to <35	*
Propylene Glycol Methyl Ether Acetate	108-65-6	10 to <20	*
Barium sulfate	7727-43-7	10 to <20	*
Butane	106-97-8	5 to <10	*
Methyl N-Propyl Ketone	107-87-9	1 to <5	*
Dimethyl Carbonate	616-38-6	1 to <5	*
Acetone	67-64-1	1 to <5	*
Aromatic 100	64742-95-6	0.1 to <1	*
Hydrodesulfurized heavy pet. naphtha	64742-82-1	0.1 to <1	*
Zirconium octoate	22464-99-9	0.1 to <1	*
Crystalline Silica	14808-60-7	0.1 to <1	*
Methyl Isobutyl Ketone	108-10-1	0.1 to <1	*
Ethyl Benzene	100-41-4	0.1 to <1	*
Methyl Ethyl Ketoxime	96-29-7	0.1 to <1	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid measures

Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get medical advice/attention.
Inhalation	Remove to fresh air.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.
Skin contact	Wash with soap and water. May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a physician. In case of contact with liquefied gas, thaw frosted parts with lukewarm water.
Ingestion	Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. Call a physician.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Wear personal protective clothing (see section 8).

Most important symptoms and effects, both acute and delayed

Symptoms	Itching. Rashes. Hives.
Effects of Exposure	May cause cancer. May cause adverse reproductive effects - such as birth defect, miscarriages, or infertility. Mutagenic effects.

Indication of any immediate medical attention and special treatment needed

Note to physicians	May cause sensitization in susceptible persons. Treat symptomatically.
---------------------------	--

5. Fire-fighting measures

Suitable Extinguishing Media	Dry chemical. Carbon dioxide (CO2). Water spray.
Large Fire	CAUTION: Use of water spray when fighting fire may be inefficient.

Unsuitable extinguishing media	DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.
Specific hazards arising from the chemical	Product is or contains a sensitizer. May cause sensitization by skin contact. Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Cylinders may rupture under extreme heat. Damaged cylinders should be handled only by specialists. Containers may explode when heated. Ruptured cylinders may rocket.
Explosion data	
Sensitivity to mechanical impact	Yes.
Sensitivity to static discharge	Yes.
Special protective equipment and precautions for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions	Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. See section 8 for more information. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take precautionary measures against static discharges. Contents under pressure. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.
Other information	Refer to protective measures listed in Sections 7 and 8. Ventilate the area.

Methods and material for containment and cleaning up

Methods for containment	Stop leak if you can do it without risk. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Flood with water to complete polymerization and scrape off floor.
Methods for cleaning up	Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

7. Handling and storage

Precautions for safe handling

Advice on safe handling	Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Remove contaminated clothing and shoes. Use personal protection equipment. Use with local exhaust ventilation. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use spark-proof tools and explosion-proof equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Keep in an area equipped with sprinklers. Do not puncture or incinerate cans. Contents under pressure. In case of rupture. Avoid contact with skin and eyes. Avoid breathing vapors or mists. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.
--------------------------------	--

Conditions for safe storage, including any incompatibilities

Storage Conditions	Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach of children. Store locked up. Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations.
---------------------------	--

8. Exposure controls/personal protection

Control Parameters

Exposure Limits	The following ingredients are the only ingredients of the product above the cut-off level (or level that contributes to the hazard classification of the mixture) which have an exposure limit applicable in the region for which this safety data sheet is intended or other recommended limit. At this time, the other relevant constituents have no known exposure limits from the sources listed here.
------------------------	--

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Propane 74-98-6	: See Appendix F: Minimal Oxygen Content, explosion hazard	TWA: 1000 ppm TWA: 1800 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m ³	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³
Barium sulfate 7727-43-7	TWA: 5 mg/m ³ inhalable particulate matter particulate matter containing no Asbestos and <1% Crystalline silica	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 10 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Butane 106-97-8	STEL: 1000 ppm explosion hazard	(vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m ³	IDLH: 1600 ppm TWA: 800 ppm TWA: 1900 mg/m ³
Methyl N-Propyl Ketone 107-87-9	STEL: 150 ppm	TWA: 200 ppm TWA: 700 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 700 mg/m ³ (vacated) STEL: 250 ppm (vacated) STEL: 875 mg/m ³	IDLH: 1500 ppm TWA: 150 ppm TWA: 530 mg/m ³
Acetone 67-64-1	STEL: 500 ppm TWA: 250 ppm	TWA: 1000 ppm TWA: 2400 mg/m ³ (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m ³ (vacated) STEL: 2400 mg/m ³ The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors. (vacated) STEL: 1000 ppm	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m ³
Zirconium octoate 22464-99-9	STEL: 10 mg/m ³ Zr TWA: 5 mg/m ³ Zr	TWA: 5 mg/m ³ Zr (vacated) TWA: 5 mg/m ³ Zr (vacated) STEL: 10 mg/m ³ Zr	IDLH: 25 mg/m ³ Zr TWA: 5 mg/m ³ except Zirconium tetrachloride Zr STEL: 10 mg/m ³ Zr
Crystalline Silica 14808-60-7	TWA: 0.025 mg/m ³ respirable particulate matter	TWA: 50 µg/m ³ TWA: 50 µg/m ³ excludes construction work, agricultural operations, and exposures that result from the processing of sorptive clays (vacated) TWA: 0.1 mg/m ³ respirable dust : (250)/(%SiO ₂ + 5) mppcf	IDLH: 50 mg/m ³ respirable dust TWA: 0.05 mg/m ³ respirable dust

		TWA respirable fraction : $(10)/(\%SiO_2 + 2)$ mg/m ³ TWA respirable fraction	
Methyl Isobutyl Ketone 108-10-1	STEL: 75 ppm TWA: 20 ppm	TWA: 100 ppm TWA: 410 mg/m ³ (vacated) TWA: 50 ppm (vacated) TWA: 205 mg/m ³ (vacated) STEL: 75 ppm (vacated) STEL: 300 mg/m ³	IDLH: 500 ppm TWA: 50 ppm TWA: 205 mg/m ³ STEL: 75 ppm STEL: 300 mg/m ³
Ethyl Benzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m ³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³

Biological occupational exposure limits

Chemical name	ACGIH
Acetone 67-64-1	25 mg/L - urine (Acetone) - end of shift
Methyl Isobutyl Ketone 108-10-1	1 mg/L - urine (MIBK) - end of shift
Ethyl Benzene 100-41-4	150 mg/g creatinine - urine (Sum of mandelic acid and phenylglyoxylic acid) - end of shift

Appropriate engineering controls

Engineering controls Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Tight sealing safety goggles.

Hand protection Wear suitable gloves. Impervious gloves.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron. Antistatic boots.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

General hygiene considerations Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and after work.

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state Aerosol
Appearance No information available
Color No information available
Odor No information available
Odor threshold No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No data available	None known
pH (as aqueous solution)		None known
Melting point / freezing point	No data available	None known
Initial boiling point and boiling range	No data available	None known
Flash point	-96.1 °C / -141.0 °F	None known
Evaporation rate	No data available	None known
Flammability	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapor pressure	No data available	None known
Relative vapor density	No data available	None known
Relative density	0.88	None known
Water solubility	No data available	None known
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature		None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known
Other information		
Explosive properties	No information available	
Oxidizing properties	No information available	
Softening point	No information available	
Molecular weight	No information available	
VOC content	No information available	
Liquid Density	7.37 lbs/gal	
Bulk density	No information available	
Percent solids by weight	42.3%	
Percent volatile by weight	57.7%	
Percent solids by volume	23.2%	
Actual VOC (lbs/gal)	4	
Actual VOC (grams/liter)	475	
EPA VOC (lbs/gal)	4.1	
EPA VOC (grams/liter)	494	

10. Stability and reactivity

Reactivity	No information available.
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	None under normal processing.
Conditions to avoid	Heat, flames and sparks. Excessive heat.
Incompatible materials	None known based on information supplied.
Hazardous decomposition products	None known based on information supplied.

11. Toxicological information

Information on likely routes of exposure

Product Information

Inhalation	Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.
-------------------	---

Eye contact	Specific test data for the substance or mixture is not available.
Skin contact	May cause sensitization by skin contact. Specific test data for the substance or mixture is not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components).
Ingestion	Specific test data for the substance or mixture is not available. Harmful if swallowed. (based on components).

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Itching. Rashes. Hives.

Acute toxicity Harmful if swallowed.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	1,917.10 mg/kg
ATEmix (dermal)	8,348.40 mg/kg
ATEmix (inhalation-vapor)	20,883.70 mg/l
ATEmix (inhalation-dust/mist)	5.6232 mg/l

Unknown acute toxicity

30.92389 % of the mixture consists of ingredient(s) of unknown acute oral toxicity

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Propane 74-98-6	-	-	> 800000 ppm (Rat) 15 min
Propylene Glycol Methyl Ether Acetate 108-65-6	= 8532 mg/kg (Rat)	> 5 g/kg (Rabbit)	= 16000 mg/m ³ (Rat) 6 h
Barium sulfate 7727-43-7	= 307000 mg/kg (Rat)	-	-
Butane 106-97-8	-	-	= 658 g/m ³ (Rat) 4 h
Methyl N-Propyl Ketone 107-87-9	= 1600 mg/kg (Rat)	= 6480 mg/kg (Rat)	2000 - 4000 ppm (Rat) 4 h
Dimethyl Carbonate 616-38-6	= 13 g/kg (Rat)	> 5 g/kg (Rabbit)	> 5.36 mg/L (Rat) 4 h
Acetone 67-64-1	= 5800 mg/kg (Rat)	> 15700 mg/kg (Rabbit)	= 50100 mg/m ³ (Rat) 8 h
Aromatic 100 64742-95-6	= 8400 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 3400 ppm (Rat) 4 h
Hydrodesulfurized heavy pet. naphtha 64742-82-1	> 5000 mg/kg (Rat)	> 4 mL/kg (Rat)	-
Zirconium octoate 22464-99-9	> 5000 mg/kg (Rat)	-	-
Crystalline Silica 14808-60-7	> 22,500 mg/kg (Rat)	-	-
Methyl Isobutyl Ketone 108-10-1	= 2080 mg/kg (Rat)	= 3000 mg/kg (Rabbit)	2000 - 4000 ppm (Rat) 4 h
Ethyl Benzene 100-41-4	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.4 mg/L (Rat) 4 h
Methyl Ethyl Ketoxime 96-29-7	= 930 mg/kg (Rat)	1000 - 1800 mg/kg (Rabbit)	> 4.83 mg/L (Rat) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation No information available.

Serious eye damage/eye irritation No information available.

Respiratory or skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity Contains a known or suspected mutagen. Classification based on data available for ingredients. May cause genetic defects.

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Crystalline Silica 14808-60-7	A2	Group 1	Known	X
Methyl Isobutyl Ketone 108-10-1	A3	Group 2B	-	X
Ethyl Benzene 100-41-4	A3	Group 2B	-	X

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity Classification based on data available for ingredients. May damage fertility or the unborn child.

STOT - single exposure No information available.

STOT - repeated exposure No information available.

Target organ effects Respiratory system, Eyes, Skin, Central nervous system.

Aspiration hazard No information available.

Other adverse effects No information available.

Interactive effects No information available.

12. Ecological information

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea

Propylene Glycol Methyl Ether Acetate 108-65-6	-	161: 96 h Pimephales promelas mg/L LC50 static	-	500: 48 h Daphnia magna mg/L EC50
Methyl N-Propyl Ketone 107-87-9	-	1190 - 1290: 96 h Pimephales promelas mg/L LC50 flow-through	-	-
Dimethyl Carbonate 616-38-6	-	100: 96 h Danio rerio mg/L LC50 flow-through	-	-
Acetone 67-64-1	-	4.74 - 6.33: 96 h Oncorhynchus mykiss mL/L LC50 6210 - 8120: 96 h Pimephales promelas mg/L LC50 static 8300: 96 h Lepomis macrochirus mg/L LC50	-	10294 - 17704: 48 h Daphnia magna mg/L EC50 Static 12600 - 12700: 48 h Daphnia magna mg/L EC50
Aromatic 100 64742-95-6	-	9.22: 96 h Oncorhynchus mykiss mg/L LC50	-	6.14: 48 h Daphnia magna mg/L EC50
Methyl Isobutyl Ketone 108-10-1	400: 96 h Pseudokirchneriella subcapitata mg/L EC50	496 - 514: 96 h Pimephales promelas mg/L LC50 flow-through	-	170: 48 h Daphnia magna mg/L EC50
Ethyl Benzene 100-41-4	4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 438: 96 h Pseudokirchneriella subcapitata mg/L EC50 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static	11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 7.55 - 11: 96 h Pimephales promelas mg/L LC50 flow-through 32: 96 h Lepomis macrochirus mg/L LC50 static 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static 9.6: 96 h Poecilia reticulata mg/L LC50 static	-	1.8 - 2.4: 48 h Daphnia magna mg/L EC50
Methyl Ethyl Ketoxime 96-29-7	83: 72 h Desmodesmus subspicatus mg/L EC50	777 - 914: 96 h Pimephales promelas mg/L LC50 flow-through 760: 96 h Poecilia reticulata mg/L LC50 static	-	750: 48 h Daphnia magna mg/L EC50

Persistence and degradability

No information available.

Bioaccumulation**Component Information**

Chemical name	Partition coefficient
Propane 74-98-6	1.09
Propylene Glycol Methyl Ether Acetate 108-65-6	1.2
Butane 106-97-8	2.31
Methyl N-Propyl Ketone 107-87-9	0.857

Dimethyl Carbonate 616-38-6	0.354
Acetone 67-64-1	-0.24
Methyl Isobutyl Ketone 108-10-1	1.9
Ethyl Benzene 100-41-4	3.6
Methyl Ethyl Ketoxime 96-29-7	0.65

Other adverse effects No information available.

13. Disposal considerations

Disposal methods

Waste from residues/unused products Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Do not reuse empty containers.

California Hazardous Waste Status This product contains one or more substances that are listed with the State of California as a hazardous waste.

14. Transport information

DOT

UN/ID no	UN1950
Proper shipping name	Aerosols
Transport hazard class(es)	2.1
Reportable Quantity (RQ)	(Toluene: RQ (kg)= 0.454, Xylene: RQ (kg)= 45.40) Toluene: RQ (lb)= 1, Xylene: RQ (lb)= 100.00
Reportable quantity (kg) (calculated)	Toluene: RQ (kg)= 1380.00, Xylene: RQ (kg)= 8334.00
Reportable quantity (lbs) (calculated)	Toluene: RQ (lb)= 3039.00, Xylene: RQ (lb)= 18357.00
Special Provisions	N82
DOT Marine Pollutant	NP
Description	UN1950, Aerosols, 2.1
Emergency Response Guide Number	126

TDG

UN/ID no	UN1950
Proper shipping name	Aerosols
Transport hazard class(es)	2.1
Special Provisions	80, 107
Description	UN1950, Aerosols, 2.1

MEX

UN/ID no	UN1950
Proper shipping name	Aerosols
Transport hazard class(es)	2.1
Description	UN1950, Aerosols, 2.1
Special Provisions	190, 277, 327, 344, 63, 381

ICAO (air)

UN/ID no	UN1950
Proper shipping name	Aerosols

Transport hazard class(es)	2.1
Description	UN1950, Aerosols, 2.1
Special Provisions	A145, A167
IATA	
UN number or ID number	UN1950
Proper shipping name	Aerosols, flammable
Transport hazard class(es)	2.1
Description	UN1950, Aerosols, flammable, 2.1
Special Provisions	A145, A167, A802
IMDG	
UN number or ID number	UN1950
UN proper shipping name	Aerosols
Transport hazard class(es)	2.1
EmS-No	F-D, S-U
Special Provisions	63,190, 277, 327, 344, 381, 959
Marine pollutant	NP
Description	UN1950, Aerosols, 2.1

15. Regulatory information

International Inventories

TSCA	Complies
-------------	----------

*Contact supplier for details. One or more substances in this product are either not listed on the US TSCA inventory, listed on the confidential US TSCA inventory or are otherwise exempted from inventory listing requirements

DSL/NDSL	Complies
EINECS/ELINCS	Contact supplier for inventory compliance status.
ENCS	Contact supplier for inventory compliance status.
IECSC	.
KECL	Contact supplier for inventory compliance status.
PICCS	Contact supplier for inventory compliance status.
AIIC	Contact supplier for inventory compliance status.
NZIoC	Contact supplier for inventory compliance status.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	SARA 313 - Threshold Values %
Barium sulfate - 7727-43-7	1.0
Methyl Isobutyl Ketone - 108-10-1	0.1
Ethyl Benzene - 100-41-4	0.1

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Ethyl Benzene 100-41-4	1000 lb	X	X	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	Reportable Quantity (RQ)
Acetone 67-64-1	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
Methyl Isobutyl Ketone 108-10-1	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
Ethyl Benzene 100-41-4	1000 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical name	California Proposition 65
Crystalline Silica - 14808-60-7	Carcinogen
Methyl Isobutyl Ketone - 108-10-1	Carcinogen Developmental
Ethyl Benzene - 100-41-4	Carcinogen
Toluene - 108-88-3	Developmental
Carbon Black - 1333-86-4	Carcinogen
Cumene - 98-82-8	Carcinogen
Methanol - 67-56-1	Developmental
Naphthalene - 91-20-3	Carcinogen
Acetaldehyde - 75-07-0	Carcinogen
1,4-Dioxane - 123-91-1	Carcinogen
Benzene(including benzene from gasoline) - 71-43-2	Carcinogen Developmental Male Reproductive
Lead - 7439-92-1	Carcinogen Developmental Female Reproductive Male Reproductive
Mercury - 7439-97-6	Developmental
Nickel - 7440-02-0	Carcinogen
Cadmium - 7440-43-9	Carcinogen Developmental Male Reproductive

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Propane 74-98-6	X	X	X
Barium sulfate	X	X	X

7727-43-7			
Butane 106-97-8	X	X	X
Methyl N-Propyl Ketone 107-87-9	X	X	X
Dimethyl Carbonate 616-38-6	X	X	X
Acetone 67-64-1	X	X	X
Xylene 1330-20-7	X	X	X
1,2,4-Trimethylbenzene 95-63-6	X	X	X
Calcium carbonate 1317-65-3	X	X	X
Crystalline Silica 14808-60-7	X	X	X
Methyl Isobutyl Ketone 108-10-1	X	X	X
Ethyl Benzene 100-41-4	X	X	X
Cobalt 2-ethylhexanoate 136-52-7	X	-	X
Toluene 108-88-3	X	X	X
Propylene Glycol 57-55-6	X	-	X
Isobutyl Alcohol 78-83-1	X	X	X
Stoddard Solvent 8052-41-3	X	X	X
Carbon Black 1333-86-4	X	X	X
Diethylene Glycol Butyl Ether 112-34-5	X	-	X
Nonane 111-84-2	X	X	X
Propionic Acid 79-09-4	X	X	X
Cumene 98-82-8	X	X	X
Methanol 67-56-1	X	X	X
2-Ethylhexanoic acid 149-57-5	X	-	-
Naphthalene 91-20-3	X	X	X
Acetaldehyde 75-07-0	X	X	X
1,4-Dioxane 123-91-1	X	X	X
Benzene(including benzene from gasoline) 71-43-2	X	X	X
Lead 7439-92-1	X	X	X
Mercury 7439-97-6	X	X	X
Nickel 7440-02-0	X	X	X
Arsenic 7440-38-2	X	X	X

Cadmium 7440-43-9	X	X	X
----------------------	---	---	---

U.S. EPA Label Information**EPA Pesticide Registration Number** Not applicable

LIST OF HAZARDOUS AIR POLLUTANTS SUBJECT TO THE PROVISIONS OF THE CLEAN AIR ACT, TITLE I SECTION 112 'National Emission Standards for Hazardous Air Pollutants' (present if listed in Section 3):

Chemical name	Weight % of HAPS in Product	Pounds HAPS / Gal Product
Methyl Isobutyl Ketone 108-10-1	0.14	0.01
Ethyl Benzene 100-41-4	0.14	0.01

16. Other information**Key or legend to abbreviations and acronyms used in the safety data sheet****Legend Section 8: Exposure controls/personal protection**

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation
+	Sensitizers		

Key literature references and sources for data used to compile the SDS

U.S. Agency for Toxic Substances and Disease Registry (ATSDR)

U.S. Environmental Protection Agency ChemView Database

European Food Safety Authority (EFSA)

U.S. Environmental Protection Agency

Acute Exposure Guideline Level(s) (AEGL(s))

U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act

U.S. Environmental Protection Agency High Production Volume Chemicals

Food Research Journal

Hazardous Substance Database

International Uniform Chemical Information Database (IUCLID)

Japan National Institute of Technology and Evaluation (NITE)

Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)

NIOSH (National Institute for Occupational Safety and Health)

National Library of Medicine's ChemID Plus (NLM CIP)

National Library of Medicine's PubMed database (NLM PUBMED)

U.S. National Toxicology Program (NTP)

New Zealand's Chemical Classification and Information Database (CCID)

International Organization for Economic Co-operation and Development (OECD) Environment, Health, and Safety Publications

International Organization for Economic Co-operation and Development (OECD) High Production Volume Chemicals Program

International Organization for Economic Co-operation and Development (OECD) Screening Information Data Set

United Nations World Health Organization (WHO)

Revision date 19-Aug-2025**Revision Note** No information available.**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet