SAFETY DATA SHEET.

Issuing date 11-Nov-2015 Revision Date 24-Sep-2018 Version 1.01

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product name KOOL FOAM

Recommended use of the chemical

and restrictions on use

Product code 8249, 9889, 8426

Product Type Extremely Flammable Aerosol

Synonyms None

Supplier's details

Recommended Use Cutting Oil.

Uses advised against No information available

Manufactured For: Tifco Industries

21400 Northwest Freeway

Cypress, TX 77429 800-868-4326

Emergency telephone number

Chemical Emergency Phone

Number

CHEM-TEL, INC. 1-800-255-3924

2. HAZARDS IDENTIFICATION

Classification

Aspiration toxicity	Category 1
Flammable aerosols	Category 1
Gases under pressure	Compressed Gas

GHS Label elements, including precautionary statements

Emergency Overview

DANGER

Hazard Statements

May be fatal if swallowed and enters airways.

Extremely Flammable Aerosol

Contains gas under pressure; may explode if heated



Appearance Opaque

Physical state Aerosol

Odor Solvent

Precautionary Statements - Prevention

Keep away from heat, sparks, open flames, hot surfaces - No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Precautionary Statements - Response

IF SWALLOWED: Immediately call a POISON CENTER, doctor, physician. Do NOT induce vomiting.

Precautionary Statements - Storage

Store locked up.

Protect from sunlight. Store in a well-ventilated place

Do not expose to temperatures exceeding 122°F (50°C)

Precautionary Statements - Disposal

Dispose of contents, container to an approved waste disposal plant.

Hazards not otherwise classified (HNOC)

None

Other information

0% of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %*
---------------	--------	-----------

KOOL FOAM

MINERAL OIL	8042-47-5	40-50
PROPANE/ISOBUTANE/N-BUTANE	68476-86-8	10-20
NAPHTHENIC OIL, SEVERLY HYDROT	64742-52-5	10-20
SULFURIZED HYDROCARBON	PROPRIETARY	1-10
CHLORINATED ESTERS	68440-29-9	1-10

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First aid measures for different exposure routes

General advice Avoid contact with eyes, skin, and clothing. Avoid breathing vapors, mist, or gas.

Eye contact Immediately flush with plenty of water for at least 15 minutes. After initial flushing, remove

any contact lenses and continue flushing. If eye irritation persists, consult a doctor.

Skin contact Wash off with soap and plenty of water. If skin irritation persists, call a physician. Remove

and wash contaminated clothing before re-use.

Inhalation Move to fresh air. If not breathing, give artificial respiration. If breathing has stopped,

contact emergency medical services immediately.

Ingestion Do NOT induce vomiting. Call a physician immediately. Never give anything by mouth to

unconscious person. Risk of product entering the lungs on vomiting after ingestion.

Most important symptoms/effects, acute and delayed

Main Symptoms May be fatal if swallowed and enters airways.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water fog.Dry chemical. Foam.Carbon dioxide (CO2). Cool containers/tanks with water spray.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire. Keep away from sources of ignition - No smoking.

Specific hazards arising from the chemical

Extremely Flammable / Flammable. Keep product and empty container away from heat and sources of ignition. In the event of fire and/or explosion do not breathe fumes. In the event of fire, cool tanks with water spray.

Explosion Data

Sensitivity to Mechanical Impact none. Sensitivity to Static Discharge Yes.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use shielding to protect fire-fighters from bursting containers.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions

Use with adequate ventiliation to keep the exposure levels below the OELS. Follow safe

handling advice and personal protective equipment recommendations.

Environmental precautions

Environmental precautions Vapors can accumulate in low areas. Report spills as required by local and federal

regulations. Do not allow material to contaminate ground water system. Do not flush into surface water or sanitary sewer system. Should not be released into the environment.

Methods and materials for containment and cleaning up

Methods for Containment Absorb with earth, sand or other non-combustible material and transfer to containers for

later disposal. Prevent further leakage or spillage if safe to do so. Do not allow material to

contaminate ground water system. Prevent product from entering drains.

Methods for cleaning up Soak up with inert absorbent material. Contain liquid and collect with an inter,

non-combustible material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly. After cleaning, flush away traces with water. Prevent product from entering drains. Take precautionary measures against static discharges.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Avoid breathing vapors or mists. Avoid contact with skin, eyes and clothing. Keep away

from open flames, hot surfaces and sources of ignition. Contents under pressure. Do not puncture or incinerate cans. Handle in accordance with good industrial hygiene and safety

practice. Take precautionary measures against static discharges.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage

conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from open

flames, hot surfaces, and sources of ignition. Keep in properly labeled containers. Keep out of the reach of children. Store locked up.

Incompatible products Strong acids, alkalis, oxidizing agents.

Aerosol Level 3

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH		
PROPANE/ISOBUTANE/N-BUTANE	74-98-6: TWA: 1000 ppm	74-98-6:TWA: 1000 ppm	74-98-6:IDLH: 2100 ppm		
68476-86-8	106-97-8: STEL: 1000 ppm 75-28-5: STEL: 1000 ppm	TWA: 1800 mg/m ³ (vacated) TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m ³		
	•••	(vacated) TWA: 1800 mg/m ³	106-97-8:TWA: 800 ppm		
		106-97-8: (vacated) TWA: 800 ppm	TWA: 1900 mg/m ³ 75-28-5:TWA: 800 ppm		
		(vacated) TWA: 1900 mg/m³	TWA: 1900 mg/m ³		

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration) NIOSH IDLH: Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Exposure controls

KOOL FOAM Revision Date 24-Sep-2018

Engineering Measures Ventilation systems. Use adequate ventilation to keep the exposure levels below the

occupational exposure limits. Showers, eyewash stations, and ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Safety glasses with side-shields.

Skin and body protection Chemical resistant apron. Protective gloves.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

Odor

Based on propellant

Solvent

provided in accordance with current local regulations.

Handle in accordance with good industrial hygiene and safety practice. Hygiene measures

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical properties

Physical state Aerosol **Appearance** Opaque

Color Dark Amber **Odor Threshold**

Property Values Remarks • Methods

No information available

pН No information available Melting/freezing point No information available

Boiling point/boiling range

Flash Point -96.4 °C / -141 °F

Evaporation rate No information available Flammability (solid, gas) No information available

Flammability Limits in Air upper flammability limit lower flammability limit

Vapor pressure Vapor density

Specific Gravity 0.818

Water solubility No information available

Partition coefficient: n-octanol/water

Autoignition temperature

Decomposition temperature

Viscosity

No information available

Explosive properties

Other information

VOC Content(%) 19.36

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Extremes of temperature and direct sunlight.

Revision Date 24-Sep-2018

KOOL FOAM

Incompatible Materials

Strong acids, alkalis, oxidizing agents.

Hazardous Decomposition Products

Carbon oxides, Hydrocarbons, Fumes.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation Respiratory irritation may occur if excessive exposure to product by inhalation.

Eye contact Eye irritation may occur if excessive exposure to product occurs.

Skin contact Skin irritation may occur if person excessively exposes product to the skin.

Ingestion May be fatal if swallowed and enters airways.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
MINERAL OIL	> 5000 mg/kg (Rat)	-	-
8042-47-5			
PROPANE/ISOBUTANE/N-BUTAN	-	-	=31mg/L (Rat) 4 hr
E			
68476-86-8			

Information on toxicological effects

Symptoms May be fatal if swallowed and enters airways.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization Germ Cell MutagenicityNot a known sensitizer.
Not a germ cell mutagen.

Carcinogenicity There are no known carcinogenic chemicals in this product.

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

A2 - Suspected Human Carcinogen

IARC: (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

Group 1 - Carcinogenic to Humans

OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive toxicityThis product does not contain any known or suspected reproductive hazards.

Specific target organ systemic No known effect based on information supplied.

toxicity (single exposure)
Specific target organ systemic toxicity (repeated exposure)

toxicity (repeated exposure)
Chronic toxicity

No known effect based on information supplied.

Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Chronic hydrocarbon abuse has been associated with irregular heart rhythms and

potential cardiac arrest.

Target Organ Effects Eyes, Skin, Respiratory System.

Neurological effects Intentional misuse by deliberately concentrating and inhaling contents may be harmful or

fatal.

Aspiration hazard May be fatal if swallowed and enters airways.

Numerical measures of toxicity - Product Information

Unknown Acute Toxicity 0% of the mixture consists of ingredient(s) of unknown toxicity.

The following values are calculated based on chapter 3.1 of the GHS document .

KOOL FOAM

ATEmix (oral) 15501 mg/kg
ATEmix (dermal) 13109 mg/kg
ATEmix (inhalation-gas) 826742 mg/l
ATEmix (inhalation-dust/mist) 120.6 mg/l
ATEmix (inhalation-vapor) 286201 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates
MINERAL OIL 8042-47-5	-	10000 mg/L LC50 Lepomis macrochirus 96h	-	-
PROPANE/ISOBUTANE/N- BUTANE 68476-86-8	-	-	-	-
NAPHTHENIC OIL, SEVERLY HYDROT 64742-52-5	-	5000 mg/L LC50 Oncorhynchus mykiss 96h	-	1000 mg/L EC50 Daphnia magna 48h

Persistence and degradability

.

Bioaccumulation

Chemical Name	log Pow
MINERAL OIL	>6
8042-47-5	
PROPANE/ISOBUTANE/N-BUTANE	<=2.8
68476-86-8	

Other adverse effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment

Waste Disposal Methods This material, as supplied, is a hazardous waste according to federal regulations (40 CFR

261). Dispose of in accordance with federal, state, and local regulations. Dispose of in accordance with federal, state, and local regulations. This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261.) Dispose of in accordance

with federal, state, and local regulations.

Contaminated packaging Do not re-use empty containers.

14. TRANSPORT INFORMATION

DOT Ground CONSUMER COMMODITY ORM-D

or

LIMITED QUANTITY

IATA UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD.QTY.

UN1950, AEROSOLS, 2.1, LTD.QTY

15. REGULATORY INFORMATION

International Inventories

Chemical Name	TSCA	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
MINERAL OIL	Х	Х	Х	Not listed	Х	Х	Х	Х
PROPANE/ISOBUTA NE/N-BUTANE	Х	Х	Х	Х	Х	Х	Х	Х
NAPHTHENIC OIL, SEVERLY HYDROT	Х	Х	Х	Not listed	Х	Х	Х	Х
CHLORINATED ESTERS	Х	Х	Х	Not listed	Х	Х	Х	Х

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

CHINA - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Acute Health Hazard Yes
Chronic Health Star Hazard Yes
Fire Hazard Yes
Sudden Release of Pressure Hazard Yes
Reactive Hazard No

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

U.S. State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

KOOL FOAM Revision Date 24-Sep-2018

EPA Pesticide Registration Number Not applicable

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

16. OTHER INFORMATION

NFPA Health Hazard 2 Flammability 4 Instability 0 Physical and chemical

hazards -

<u>HMIS</u> Health Hazard 2* Flammability 4 Physical Hazard 1 Personal protection B Chronic Hazard Star Legend Chronic Health Star Hazard Repeated or prolonged exposure may cause central nervous system

damage

Prepared ByRegulatory AffairsIssuing date11-Nov-2015Revision Date24-Sep-2018

Revision Note

(M)SDS sections updated

Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet