Reviewed on 03/05/2019

Safety Data Sheet acc. to OSHA HCS

Printing date 03/06/2019

1 Identification

- Product identifier

- Trade name: Tif-Lock Threadlocker Gel-Red

- **Part number:** 8529, 8527
- Application of the substance / the mixture Thread Locking

- Details of the supplier of the safety data sheet

Supplier: Tifco Industries, Inc P.O. Box 40277 Houston, TX 77240 USA Telephone: +1-281-571-6000 Email: tifco@tifco.com Website: www.tifco.com

- Emergency telephone number:

United States: 1-800-424-9300

2 Hazard(s) identification

- Classification of the substance or mixture

GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



- Skin Irrit. 2 H315 Causes skin irritation.
- Eye Irrit. 2A H319 Causes serious eye irritation.
- Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- Label elements

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms



- Signal word Warning

 Hazard-determining components of labeling: methacrylic acid, monoester with propane-1,2-diol 2-(2-methylprop-2-enoyloxy)ethyl 2-methylprop-2-enoate dimethylbenzyl hydroperoxide octadecyl methacrylate 2'-phenylacetohydrazide

- Hazard statements

- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H317 May cause an allergic skin reaction.
- H351 Suspected of causing cancer.
- H335 May cause respiratory irritation.
- H373 May cause damage to organs through prolonged or repeated exposure.
- Precautionary statements
- P260 Do not breathe dust/fume/gas/mist/vapors/spray.
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray
- P264 Wash face, hands and any exposed skin thoroughly after handling.

Safety Data Sheet acc. to OSHA HCS

Printing date 03/06/2019

Trade name: Tif-Lock Threadlocker Gel


(Contd. of page 1)

Reviewed on 03/05/2019

	(Contd. o	of page 1
P271	Use only outdoors or in a well-ventilated area.	
P272	Contaminated work clothing must not be allowed out of the workplace.	
P280	Wear protective gloves/protective clothing/eye protection/face protection.	
P280	Wear protective gloves.	
P280	Wear eve protection / face protection.	
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
P305+P351+P338	B If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to	o do.
	Continue rinsing.	
P308+P313	IF exposed or concerned: Get medical advice/attention.	
P312	Call a poison center/doctor if you feel unwell.	
P314	Get medical advice/attention if you feel unwell.	
P362+P364	Take off contaminated clothing and wash it before reuse.	
P332+P313	If skin irritation occurs: Get medical advice/attention.	
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.	
P321	Specific treatment (see on this label).	
P337+P313	If eye irritation persists: Get medical advice/attention.	
P363	Wash contaminated clothing before reuse.	
P403+P233	Store in a well-ventilated place. Keep container tightly closed.	
P405	Store locked up.	
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.	
	• •	

Classification system:

- NFPA ratings (scale 0 - 4)



- HMIS-ratings (scale 0 - 4)

HEALTH12Health = *2FIRE1Fire = 1REACTIVITY0Reactivity = 0

- Other hazards

- Results of PBT and vPvB assessment

- **PBT:** Not applicable.

- vPvB: Not applicable.

3 Composition/information on ingredients

- Chemical characterization: Mixtures

- Description: Mixture of the substances listed below with nonhazardous additions.

- Dangerous	components:	
CAS: 25852-47-5	2-(2-methylprop-2-enoyloxy)ethyl 2-methylprop-2-enoate	30 – 39%
	Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	
CAS: 27813-02-1	methacrylic acid, monoester with propane-1,2-diol	20 – 29%
	Eye Irrit. 2A, H319; Skin Sens. 1, H317	
	Acrylic polymer	10 – 19%
	Combustible Dust	
CAS: 67762-90-7	Amorphous Silica	5 – 9%
	Combustible Dust	
CAS: 80-15-9	dimethylbenzyl hydroperoxide	1 – 4%
	Self-react. F, H242; Org. Perox. E, H242; Acute Tox. 3, H311; STOT RE 2, H373; Asp. Tox. 1, H304; Eye Dam. 1, H318; Acute Tox. 4, H302; STOT SE 3, H335; Flam. Liq. 4, H227	
CAS: 32360-05-7	octadecyl methacrylate	≤ 1%
	Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	
CAS: 114-83-0	2'-phenylacetohydrazide	≤ 1%
	Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317; STOT SE 3, H335	
CAS: 98-82-8	cumene	≤ 1%
	Flam. Liq. 3, H226; Carc. 2, H351; Asp. Tox. 1, H304; Acute Tox. 4, H302; STOT SE 3, H335	
First-aid meas	sures	

- Description of first aid measures

- After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air; consult doctor in case of complaints.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.

Trade name: Tif-Lock Threadlocker Gel

(Contd. of page 2)

Reviewed on 03/05/2019

- Information for doctor:

- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Fire-fighting measures

- Extinguishing media

Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- CO2, sand, extinguishing powder. Do not use water.
- For safety reasons unsuitable extinguishing agents: Water
- Special hazards arising from the substance or mixture No further relevant information available.

- Advice for firefighters

- Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
 Ensure adequate ventilation
 Wear protective clothing.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Dispose of the collected material according to regulations.

- Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

7 Handling and storage

- Handling:

- Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

No special precautions are necessary if used correctly.

- Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- Conditions for safe storage, including any incompatibilities

- Storage:

- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
- Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.

- Control parameters

- Components with limit values that require monitoring at the workplace:
- The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

WEEL Long-term value: 6 mg/m³, 1 ppm

Skin

CAS: 98-82-8 cumene

PEL Long-term value: 245 mg/m³, 50 ppm

Skin

Printing date 03/06/2019

Trade name: Tif-Lock Threadlocker Gel

Reviewed on 03/05/2019

	(Contd. of page 3)
REL	Long-term value: 245 mg/m ³ , 50 ppm
	Skin
TLV	Long-term value: (246) NIC-0.5 mg/m ³ , (50) NIC-0.1 ppm
	NIC-A3
	- Additional information: The lists that were valid during the creation were used as basis.

- Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- Breathing equipment:

Not required.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation


- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. Nitrile rubber, NBR

- Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eye protection:



- Body protection: Protective work clothing

9 Physical and chemical properties		
 Information on basic physical and che General Information Appearance: 	mical properties	
- Form:	Fluid	
- Color:	Red	
- Odor:	Characteristic	
 Odor threshold: 	Not determined.	
- pH-value:	Not determined.	
 Change in condition Melting point/Melting range: Boiling point/Boiling range: 	Undetermined. ≥ 200 °C (≥ 392 °F)	
- Flash point:	95 °C (203 °F)	
- Flammability (solid, gaseous):	Not applicable.	
- Decomposition temperature:	Not determined.	
- Auto igniting:	Product is not selfigniting.	
- Danger of explosion:	Product does not present an explosion hazard.	
- Explosion limits: - Lower: - Upper:	Not determined. Not determined.	
- Vapor pressure at 20 °C (68 °F):	≤ 0.1 hPa (≤ 0.1 mm Hg)	
- Density at 20 °C (68 °F):	~ 1.1 g/cm³ (~ 9.1795 lbs/gal)	

(Contd. of page 4)

Printing date 03/06/2019

Trade name: Tif-Lock Threadlocker Gel

Reviewed on 03/05/2019

- Relative density	Not determined.
- Vapor density	Not determined.
- Evaporation rate	Not determined.
- Solubility in / Miscibility with	h
- Water:	Not miscible or difficult to mix.
- Partition coefficient (n-octa	nol/water): Not determined.
- Viscosity:	
- Dynamic:	Not determined.
- Kinematic:	Not determined.
- Solvent content:	
 Organic solvents: 	0.9 %
- Water:	0.4 %
- VOC content:	0.90 %
	~ 9.9 g/l / ~ 0.08 lb/gal
0.11.1	
- Solids content:	68.3 %

10 Stability and reactivity

- Reactivity No further relevant information available.

- Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- Hazardous decomposition products: Aldehyde

Hydrocarbons

11 Toxicological information

- Information on toxicological effects

- Acute toxicity:

Acute toxicity.		
- LD/LC50 values that are relevant for classification:		
ATE (Acut	e Toxicity	r Estimate)
Oral	LD50	17,420 mg/kg (rat)
Dermal	LD50	31,328 mg/kg (rat)
Inhalative	LC50/4 h	13,784 mg/l (rat)
CAS: 80-1	5-9 dimet	hylbenzyl hydroperoxide
Oral	LD50	382 mg/kg (rat)
Dermal	LD50	500 mg/kg (rat)
Inhalative	LC50/4 h	220 mg/l (rat)
CAS: 114-	83-0 2'-ph	enylacetohydrazide
Oral	LD50	270 mg/kg (mouse)
CAS: 98-8	2-8 cume	ne
Oral	LD50	1,400 mg/kg (rat)
Dermal	LD50	12,300 mg/kg (rabbit)
Inhalative	LC50/4 h	24.7 mg/l (mouse)
Π.	des services	itant affect:

- Primary irritant effect:

- on the skin: Irritant to skin and mucous membranes.

- on the eye: Irritating effect.

- Sensitization: Sensitization possible through skin contact.

- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

- Carcinogenic categories

 IARC (International Agency 	v for Research on Cancer)
--	---------------------------

	- (
CAS: 98-82-8	cumene	2B	
CAS: 91-20-3	naphthalene	2B	

Printing date 03/06/2019

Trade name: Tif-Lock Threadlocker Gel

Reviewed on 03/05/2019

	ade name: III-LOCK IIIIeaulockei Gei			
		(Contd. of page 5)		
CAS: 1330-20-7	xylene	3		
- NT	P (National Toxicology Program)			
CAS: 98-82-8	cumene	R		
CAS: 130-15-4	1,4-naphthoquinone	R		
CAS: 91-20-3	naphthalene	R		
- OSHA-Ca (Occupational Safety & Health Administration)				
None of the ingredients is listed.				

12 Ecological information

- Toxicity

Aquatic toxicity: No further relevant information available.

- Persistence and degradability No further relevant information available.

- Behavior in environmental systems:
 - Bioaccumulative potential No further relevant information available.

- Mobility in soil No further relevant information available.

- Additional ecological information:

General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- Results of PBT and vPvB assessment

- PBT: Not applicable.
- vPvB: Not applicable.

- Other adverse effects No further relevant information available.

13 Disposal considerations

Waste treatment methods

Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packagings:

- Recommendation: Disposal must be made according to official regulations.

14 Transport information

- UN-Number - DOT, ADN, IMDG, IATA	not regulated	
 - UN proper shipping name - DOT, ADN, IMDG, IATA 	not regulated	
- Transport hazard class(es)		
- DOT, ADN, IMDG, IATA - Class	not regulated	
 Packing group DOT, IMDG, IATA 	not regulated	
 Environmental hazards: Marine pollutant: 	No	
- Special precautions for user	Not applicable.	
 Transport in bulk according to Annex II c and the IBC Code 	of MARPOL73/78 Not applicable.	
- UN "Model Regulation":	not regulated	

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture - Sara

 Section 355 (extremely hazardous substances): 		
None of the ingr	None of the ingredients is listed.	
- Section 313 (Specific toxic chemical listings):		
CAS: 80-15-9	CAS: 80-15-9 dimethylbenzyl hydroperoxide	
CAS: 98-82-8	cumene	

Reviewed on 03/05/2019

Printing date 03/06/2019

Trade name: Tif-Lock Threadlocker Gel

040.01.00.0		(Contd. of page
CAS: 91-20-3	naphthalene	
CAS: 1330-20-7		
•	Toxic Substances Control Act):	
All ingredients a		
	A new (21st Century Act): (Substances not listed)	
CAS: 25852-47-	5 2-(2-methylprop-2-enoyloxy)ethyl 2-methylprop-2-enoate	
CAS: 114-83-0	2'-phenylacetohydrazide	
- Haz	ardous Air Pollutants	
CAS: 98-82-8	cumene	
CAS: 130-15-4	1,4-naphthoquinone	
CAS: 91-20-3	naphthalene	
CAS: 1330-20-7	-	
- Propos		
- Che	micals known to cause cancer:	
CAS: 98-82-8 ct	umene	
CAS: 91-20-3 na	aphthalene	
- Che	micals known to cause reproductive toxicity for females:	
None of the ingre	edients is listed.	
- Che	micals known to cause reproductive toxicity for males:	
None of the ingre	edients is listed.	
- Che	micals known to cause developmental toxicity:	
None of the ingre	edients is listed.	
- Carcino	ogenic categories	
- EPA	(Environmental Protection Agency)	
CAS: 98-82-8	cumene	D, CBI
CAS: 91-20-3	naphthalene	C, CBE
CAS: 1330-20-7	xylene	1
- TLV	(Threshold Limit Value established by ACGIH)	
CAS: 91-20-3	naphthalene	A
CAS: 1330-20-7	xylene	A
- NIO	SH-Ca (National Institute for Occupational Safety and Health)	I
None of the ingre		
0	ety assessment: A Chemical Safety Assessment has not been carried out.	
Other inform		
	is based on our present knowledge. However, this shall not constitute a guarantee for any	

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing SDS: ND Industries, Inc. - Safety, Health and Environmental Affaires

- Contact: Safety, Health and Environmental Affaires

- Date of preparation / last revision 03/06/2019 / 34

- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IMDC: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) NEPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health TLV: Threshold Limit Value

PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Flam. Liq. 3: Flammable liquids – Category 3 Flam. Liq. 4: Flammable liquids – Category 4 Self-react. F: Self-reactive substances and mixtures – Type E/F Org. Perox. E: Organic peroxides – Type E/F Acute Tox. 4: Acute toxicity – Category 4 Acute Tox. 3: Acute toxicity – Category 3

PEL: Permissible Exposure Limit

Printing date 03/06/2019

Trade name: Tif-Lock Trheadlocker Gel

(Contd. of page 7)

Reviewed on 03/05/2019

Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A Skin Sens. 1: Skin sensitisation – Category 1 Carc. 2: Carcinogenicity – Category 2 STOT SE 3: Specific target organ toxicity (repeated exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1

- * Data compared to the previous version altered.

- Disclaimer

The information set forth is based on information that ND Industries, Incorporated believes to be accurate. No warranty, expressed or implied, is intended. The information is provided solely for your information and consideration and ND Industries Inc. assumes no legal responsibility for use or reliance thereon. In the event of a discrepancy between the information on the non-English document and its English counterpart, the English version shall supersede.

®ND and ND Industries, Inc. are registered trademarks of ND Industries Incorporated, ®Vibra-TITE is a registered trademark of ND Industries, Inc.