

Safety Data Sheet
KLEEN-SOLV

SECTION I - IDENTIFICATION

PRODUCT IDENTIFIER: KLEEN-SOLV
PRODUCT CODE: 9612, 9895, 8432
RECOMMENDED USE: Energized Electrical Equipment Cleaner
RESTRICTIONS ON USE: None known.
COMPANY NAME: TIFCO Industries, Inc.
COMPANY ADDRESS: 21400 Northwest Freeway, Cypress Tx 77429
COMPANY PHONE: 281-571-6000
EMERGENCY PHONE: 800-255-3924

SECTION II – HAZARDS IDENTIFICATION

CLASSIFICATION: Gases Under Pressure: Dissolved Gas
Skin Irritant: Category 2
Eye Irritant: Category 2A
Specific Target Organ Toxicity (Single Exposure): Category 3
Carcinogenicity: Category 1B
Germ Cell Mutagenicity: Category 2
Skin Sensitization: Category 1

HAZARD STATEMENT(S): DANGER: Contains gas under pressure; may explode if heated. Causes skin and serious eye irritation. May cause drowsiness or dizziness. May cause cancer. Suspected of causing genetic defects. May cause an allergic skin reaction.

This product contains the following percentage of chemicals of unknown toxicity: N/A

PRECAUTIONARY STATEMENTS: Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/120 °F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves, eye protection and protective clothing. If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. If exposed or concerned: Get medical advice or attention. Avoid breathing fumes, mist, vapors, and spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Contaminated work clothing must not be allowed out of the workplace. Dispose of contents and container in accordance with local, state, and national regulations.

SYMBOL:



HAZARDS NOT OTHERWISE CLASSIFIED: N/A

SECTION III – COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	CAS NUMBER	PERCENT
Trichloroethylene	79-01-6	45-55%
Tetrachloroethylene	127-18-4	45-55%
Carbon dioxide	124-38-9	1-5%

SECTION IV - FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Seek medical attention if irritation persists.

INGESTION: Rinse mouth with water. Do not induce vomiting unless directed by medical authority. Seek medical attention. Never give anything by mouth to an unconscious person.

Safety Data Sheet

KLEEN-SOLV

INHALATION: Move to fresh air. If breathing is difficult, administer oxygen. If not breathing administer artificial respiration or at any sign of loss of consciousness seek immediate medical attention.

SKIN: Immediately wash with soap and water for 15 minutes. Remove contaminated clothing and shoes immediately. Seek medical attention if irritation persists.

ACUTE HEALTH HAZARDS: Causes skin irritation including redness, burning and drying/cracking. Causes eye irritation including redness, tearing, and pain. May cause respiratory irritation and central nervous system (CNS) depression. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

CHRONIC HEALTH HAZARDS: Possible cancer causing agent and overexposure may also include damage to skin, kidneys, liver, lungs, blood, reproductive or central nervous systems. May cause dizziness, headache, nausea, mental confusion, or visual disturbances.

NOTE TO PHYSICIAN: Do not administer adrenaline or epinephrine to a victim of chlorinated solvent poisoning. This product contains ingredients that may be anticipated to be a carcinogen.

SECTION V – FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA: Dry chemical, carbon dioxide, water spray, alcohol-resistant foam.

UNSUITABLE EXTINGUISHING MEDIA: Water jets or streams.

SPECIAL FIRE FIGHTING PROCEDURES: Wear NIOSH approved Self Contained Breathing Apparatus with a full face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires. Use water spray only to cool exposed containers.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Contents under pressure. Exposure to temperatures above 122 °F (50 °C) may cause bursting. Keep away from heat, sparks, open flames and other sources of ignition.

HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon, chlorine, hydrogen chloride and phosgene.

SECTION VI – ACCIDENTAL RELEASE MEASURES

PERSONAL PROTECTIVE EQUIPMENT: Refer to section VIII for proper Personal Protective Equipment.

SPILL: Use absorbent on spill, sweep to clean. Dispose in accordance with local, state and federal laws. Small releases may be wiped up with wiping material.

WASTE DISPOSAL: Dispose of in accordance with local, state and federal regulations. Do not dump in sewers. Wrap container and place in trash collection. Do not puncture, incinerate, or reuse container.

RCRA STATUS: Waste solvent likely considered U228 (Trichloroethylene), hazardous, under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION VII – HANDLING AND STORAGE

HANDLING AND STORAGE: Wear proper personal protective equipment when using this product. Avoid contact with skin, eyes and clothing. Do not inhale mist or vapor. Do not use or store with strong oxidizers. Protect from sunlight. Store in a well ventilated area. Do not expose to temperatures exceeding 50 °C/122 °F. Pressurized container: Do not pierce or burn, even after use. Store in a cool, dry area. Do not use or store near heat, open flames or other sources of ignition. Wash contaminated clothing and shoes thoroughly before reuse. Wash hands thoroughly after handling.

OTHER PRECAUTIONS: Keep out of the reach of children. Read and follow the directions on the product label. They are the best guide to using the product in the most effective manner. The label also gives you the necessary safety precautions to protect your health. Containers of this material may be hazardous when empty since they retain product residues (vapors, liquid); observe all warning and precautions listed for the product.

INCOMPATIBILITY: Strong acids, strong alkalis, strong oxidizing agents, chemically active metals, such as aluminum, barium, lithium, sodium, magnesium, potassium, titanium, beryllium, concentrated nitric acid some plastics, rubbers, and coatings.

SECTION VIII – EXPOSURE CONTROLS/PERSONAL PROTECTION

HAZARDOUS INGREDIENT	OSHA PEL	ACGIH TLV
Trichloroethylene	100 ppm	10 ppm
Tetrachloroethylene	100 ppm	25 ppm
Carbon dioxide	5000 ppm	5000 ppm

ENGINEERING CONTROLS / VENTILATION: Material is heavier than air. Material may concentrate in low lying areas. Normal, forced ventilation required to meet TLV requirements. Local exhaust ventilation is generally preferred.

RESPIRATORY PROTECTION: Avoid breathing vapor. If exposure levels are exceeded then organic vapor cartridge respirator or SCBA will be needed.

PERSONAL PROTECTIVE EQUIPMENT: Safety glasses/goggles, chemical resistant gloves and synthetic apron.

Safety Data Sheet

KLEEN-SOLV

ADDITIONAL MEASURES: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective clothing to prevent repeated or prolonged contact with product. Contaminated work clothing must not be allowed out of the workplace. Avoid contact with skin or eyes and avoid breathing vapors. Wash hands after use. If clothing becomes contaminated, immediately remove and wash.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Clear, colorless to slight tint spray.

ODOR: Chlorinated solvent.

ODOR THRESHOLD: N/D

pH: N/A

MELTING POINT/FREEZING POINT: N/D

INITIAL BOILING POINT AND BOILING RANGE: > 188 °F (87 °C).

FLASH POINT: N/D

EVAPORATION RATE: > 3 (Fast)

FLAMMABILITY (solid/gas): Not considered a flammable aerosol or an extremely flammable aerosol by OSHA (29CFR 1910.1200).

UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS:

LOWER FLAMMABILITY LIMIT: N/D

UPPER FLAMMABILITY LIMIT: N/D

EXPLOSIVE LIMIT LOWER (%): N/D

EXPLOSIVE LIMIT UPPER (%): N/D

VAPOR PRESSURE (mm Hg): N/D

VAPOR DENSITY (AIR=1): N/D

RELATIVE DENSITY (H₂O=1): 1.52-1.54 @ 77 °F (25 °C).

SOLUBILITY(IES): 0% in water.

PARTITION COEFFICIENT: n-OCTANOL/WATER (K_{ow}): N/D

AUTOIGNITION TEMPERATURE: N/D

DECOMPOSITION TEMPERATURE: N/D

VISCOSITY: N/D

SECTION X – STABILITY AND REACTIVITY

REACTIVITY: Chemically active metals and acids.

CHEMICAL STABILITY: Stable.

POSSIBLE HAZARDOUS REACTIONS: None known.

CONDITIONS TO AVOID: Temperatures greater than 122 °F may cause bursting. Avoid incompatible materials.

INCOMPATIBLE MATERIALS: Strong acids, strong alkalis, strong oxidizing agents, chemically active metals, such as aluminum, barium, lithium, sodium, magnesium, potassium, titanium, beryllium, concentrated nitric acid some plastics, rubbers, and coatings.

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon, chlorine, hydrogen chloride and phosgene.

SECTION XI – TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION: **Trichloroethylene** (79-01-6): LD₅₀ (Oral, Rat) 4920 mg/kg; LD₅₀ (Dermal, Rabbit) > 20000 mg/kg; LC₅₀ (Inhalation, Mouse, 4h) 8450 ppm. **Tetrachloroethylene (Perchloroethylene)** (127-18-4): LD₅₀ (Oral, Rat) 2629 mg/kg; LC₅₀ (Inhalation, Mouse, 8hr) 34200 mg/m³. **Carbon dioxide** (124-38-9): LC₅₀ (Inhalation, Rat, 30m) 470,000 ppm.

ROUTES OF ENTRY: Eyes, Inhalation, Skin

EYES: Causes irritation, burning, redness, tearing.

INGESTION: Not a likely route of exposure under normal product handling conditions. Causes gastrointestinal irritation, headaches, nausea, diarrhea, vomiting, abdominal cramps.

INHALATION: Causes respiratory tract irritation, dizziness, headache, nausea, depression of central nervous system (CNS). Prolonged exposure may cause unconsciousness, heart effects, liver effects, kidney effects and death.

SKIN: Irritation likely, redness and pain. May cause localized defatting, blistering with prolonged skin contact. May be absorbed through the skin.

MEDICAL CONDITION AGGRAVATED: Excessive exposure will aggravate pre-existing disorders of eyes, skin, respiratory, liver, kidney, cardiovascular system, pulmonary illnesses, or central nervous system (CNS).

ACUTE HEALTH HAZARDS: Causes skin irritation including redness, burning and drying/cracking. Causes eye irritation including redness, tearing, and pain. May cause respiratory irritation and central nervous system (CNS) depression. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Safety Data Sheet

KLEEN-SOLV

CHRONIC HEALTH HAZARDS: Possible cancer causing agent and overexposure may also include damage to skin, kidneys, liver, lungs, blood, reproductive or central nervous systems. May cause dizziness, headache, nausea, mental confusion, or visual disturbances.

CARCINOGENICITY: OSHA: No ACGIH: A2 - Suspected NTP: 2 – Anticipated IARC: 2A - Probable OTHER: CA Prop 65

SECTION XII – ECOLOGICAL INFORMATION

ECOTOXICITY: Toxic to aquatic life with long lasting effects. **Trichloroethylene** (79-01-6): LC₅₀ (*Pimephales promelas*, 96h) 41 - 67 mg/L; LC₅₀ (Mollusk shrimp, 96h) 2 mg/L; EC₅₀ (Daphnia, 48h) 2.2 - 100 mg/L. **Tetrachloroethylene (Perchloroethylene)** (127-18-4): LC₅₀ (*Pimephales promelas*, 96h) 18.4 mg/L; LC₅₀ (*Oncorhynchus mykiss*, 96hr) 5 mg/L; LC₅₀ (*Lepomis macrochirus*, 96hr) 12.9 mg/L; LC₅₀ (*Cyprinodon variegatus*, 96h) 29.4 - 52.2 mg/L; LC₅₀ (Mysid shrimp, 96h) 10.2 mg/L; EC₅₀ (*Daphnia magna*, 48h) 18 mg/L.

PERSISTENCE AND DEGRADABILITY: Component or components of this product are not biodegradable.

BIOACCUMULATIVE POTENTIAL: Components in this mixture can bioaccumulate in aquatic organisms.

MOBILITY IN SOIL: This product is mobile in soil.

OTHER ADVERSE EFFECTS: None known.

SECTION XIII – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Dispose of in accordance with local, state and federal regulations. Do not dump in sewers. Wrap container and place in trash collection. Do not puncture, incinerate, or reuse container.

RCRA STATUS: Waste solvent likely considered U228 (Trichloroethylene), hazardous, under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION XIV - TRANSPORT INFORMATION

PROPER SHIPPING NAME: Aerosols, Ltd. Qty.

HAZARD CLASS/DIVISION: 2.2 (6.1)

UN/NA NUMBER: UN1950

PACKING GROUP: N/A

AIR SHIPMENT

PROPER SHIPPING NAME: Aerosols, non-flammable, containing substances in Division 6.1, Packing Group III.

HAZARD CLASS/DIVISION: 2.2 (6.1)

UN/NA NUMBER: UN1950

PACKING GROUP: N/A

SHIPPING BY WATER:

VESSEL (IMO/IMDG)

PROPER SHIPPING NAME: Aerosols, toxic.

HAZARD CLASS/DIVISION: 2.2 (6.1)

UN/NA NUMBER: UN1950

PACKING GROUP: N/A

ENVIRONMENTAL HAZARDS WATER: Marine Pollutant.

SECTION XV - REGULATORY INFORMATION

TSCA STATUS: All chemicals are listed or exempt.

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT): **Trichloroethylene** (79-01-6)

Reportable Quantity = 100 pounds. **Tetrachloroethylene (Perchloroethylene)** (127-18-4) Reportable Quantity = 100 pounds.

SARA 311/312 HAZARD CATEGORIES: Gas under pressure. Skin corrosion or irritation. Serious eye damage or eye irritation.

Respiratory or skin sensitization. Germ cell mutagenicity. Carcinogenicity. Specific target organ toxicity (single or repeated exposure).

SARA 313 REPORTABLE INGREDIENTS: **Trichloroethylene** (79-01-6). **Tetrachloroethylene (Perchloroethylene)** (127-18-4).

CLEAN WATER ACT: **Tetrachloroethylene (Perchloroethylene)** (127-18-4) is a priority pollutant and a toxic pollutant.

STATE REGULATIONS: **California Proposition 65: WARNING:** This product can expose you to chemicals including Trichloroethylene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov. **Trichloroethylene (79-01-6):** Included on State Hazardous Substances Inventories, Right-to-Know lists and/or Air Quality or Air Pollutants lists for the following states: CA, DE, ME, MA, MN, NJ, NY, PA, RI, WV. **Tetrachloroethylene (Perchloroethylene)** (127-18-4): Included on State Hazardous Substances Inventories,

Safety Data Sheet

KLEEN-SOLV

Right-to-Know lists and/or Air Quality or Air Pollutants lists for the following states: CA, DE, ID, IL, ME, MN, NJ, NY, PA, RI, WV, WI.

INTERNATIONAL REGULATIONS: Listed or exempt from listing/notification on the following chemical inventories: Australian Inventory of Industrial Chemicals (AIIC, Australia); Domestic Substances List (DSL, Canada); Inventory of Existing Chemical Substances in China (IECSC, China); Existing and New Chemical Substances (ENCS, Japan); Korean Existing Chemicals Inventory (KECI, Korea); New Zealand Inventory of Chemicals (NZIoC, New Zealand); Philippine Inventory of Chemicals and Chemical Substances (PICCS, Philippines); Taiwan Chemical Substance Inventory (TCSI, Taiwan).

VOLATILE ORGANIC COMPOUNDS (VOC): 50%

NFPA HEALTH: 2

NFPA FLAMMABILITY: 1

NFPA REACTIVITY: 0

NFPA OTHER: None

HMIS HEALTH: *2

HMIS FLAMMABILITY: 1

HMIS REACTIVITY: 0

HMIS PROTECTION: C

SECTION XVI - OTHER INFORMATION

PREPARATION BY: Craig Bernard

DATE PREPARED: 12/13/2013

REVISION DATE: 06/13/2024

N/A = Not Applicable; N/D = Not Determined

DISCLAIMER: To the best of our knowledge, information contained herein is accurate. However, there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.