

SAFETY DATA SHEET

Lubrilinek 8175, 9487, 9922, 8408

Version 1.0

Revision Date 02/25/2015

Print Date 05/28/2015

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : Lubrilinek
Material number : 8175, 9487, 9922, 8408

Manufacturer or supplier's details

Company : Tifco Industries, Inc.
Address : PO Box 40277
Houston, TX 77240
Telephone : 281-571-6000

Emergency telephone number: Chem-Tel 800-255-3924

SECTION 2. HAZARDS IDENTIFICATION


Emergency Overview

Appearance	Aerosol containing a liquefied gas
Colour	black, green
Odour	solvent-like

GHS Classification

Flammable aerosols : Category 2
Gases under pressure : Liquefied gas

GHS Label element

Hazard pictograms : 

Signal word : Warning

Hazard statements : H223 Flammable aerosol.
H280 Contains gas under pressure; may explode if heated.

Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container: Do not pierce or burn, even after use.
Storage:
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

SAFETY DATA SHEET

Lubrilink 8175, 9487, 9922, 8408

Version 1.0

Revision Date 02/25/2015

Print Date 05/28/2015

Potential Health Effects

Carcinogenicity:

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
ACGIH	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.
OSHA	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical Name	CAS-No.	Concentration [%]
propane	74-98-6	>= 10 - < 20
butane	106-97-8	>= 5 - < 10
Stoddard solvent	8052-41-3	>= 1 - < 5
Mineral Oil Mixture	Not Assigned	>= 1 - < 5
acetone	67-64-1	>= 1 - < 5

SECTION 4. FIRST AID MEASURES

General advice	: Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended. Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	: If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	: If skin irritation persists, call a physician. If on clothes, remove clothes. Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.
In case of eye contact	: Remove contact lenses. Flush eyes with water at least 15 minutes. Get medical

SAFETY DATA SHEET

Lubrilink 8175, 9487, 9922, 8408

Version 1.0

Revision Date 02/25/2015

Print Date 05/28/2015

attention if eye irritation develops or persists.
Keep eye wide open while rinsing.

Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Carbon dioxide (CO₂)
Carbon monoxide
Smoke

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.

SAFETY DATA SHEET

Lubrilink 8175, 9487, 9922, 8408

Version 1.0

Revision Date 02/25/2015

Print Date 05/28/2015

If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.
Do not breathe vapours or spray mist.
Always replace cap after use.
- Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.
No smoking.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Keep in a cool, well-ventilated place.
Electrical installations / working materials must comply with the technological safety standards.
- Materials to avoid : Oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
propane	74-98-6	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,800 mg/m ³	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m ³	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m ³	OSHA P0
butane	106-97-8	TWA	800 ppm 1,900 mg/m ³	NIOSH REL
		TWA	800 ppm 1,900 mg/m ³	OSHA P0
Stoddard solvent	8052-41-3	TWA	100 ppm	ACGIH
		TWA	350 mg/m ³	NIOSH REL

SAFETY DATA SHEET

Lubrilink 8175, 9487, 9922, 8408

Version 1.0

Revision Date 02/25/2015

Print Date 05/28/2015

		C	1,800 mg/m3	NIOSH REL
		TWA	500 ppm 2,900 mg/m3	OSHA Z-1
		TWA	100 ppm 525 mg/m3	OSHA P0
acetone	67-64-1	TWA	500 ppm	ACGIH
		STEL	750 ppm	ACGIH
		TWA	250 ppm 590 mg/m3	NIOSH REL
		TWA	1,000 ppm 2,400 mg/m3	OSHA Z-1
		TWA	750 ppm 1,800 mg/m3	OSHA P0
		STEL	1,000 ppm 2,400 mg/m3	OSHA P0

Biological occupational exposure limits

Component	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
2-PROPANONE	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	50 mg/l	ACGIH BEI

Personal protective equipment

- Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.
- Hand protection
Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Eye protection : Ensure that eyewash stations and safety showers are close to the workstation location.
Tightly fitting safety goggles
- Skin and body protection : impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : Aerosol containing a liquefied gas
- Colour : black, green

SAFETY DATA SHEET

Lubrilink 8175, 9487, 9922, 8408

Version 1.0

Revision Date 02/25/2015

Print Date 05/28/2015

Odour	: solvent-like
Odour Threshold	: no data available
pH	: not applicable
Melting point/freezing point	: no data available
Boiling point	: no data available
Flash point	: no data available
Evaporation rate	: no data available
Upper explosion limit	: no data available
Lower explosion limit	: no data available
Vapour pressure	: no data available
Density	: no data available
Solubility(ies)	
Water solubility	: insoluble
Partition coefficient: n-octanol/water	: no data available
Auto-ignition temperature	: not determined
Thermal decomposition	: no data available
Viscosity	
Viscosity, kinematic	: no data available
Heat of combustion	: 46.08 kJ/g

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air. No decomposition if stored and applied as directed.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	: Hydrocarbons Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

SAFETY DATA SHEET

Lubrilink 8175, 9487, 9922, 8408

Version 1.0

Revision Date 02/25/2015

Print Date 05/28/2015

Acute toxicity

no data available

Skin corrosion/irritation

Product:

Remarks: May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Respiratory or skin sensitisation

no data available

Germ cell mutagenicity

no data available

Carcinogenicity

no data available

Reproductive toxicity

no data available

propane:

butane:

Stoddard solvent:

Mineral Oil Mixture:

acetone:

STOT - single exposure

no data available

STOT - repeated exposure

no data available

Aspiration toxicity

no data available

Further information

Product:

Remarks: no data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

no data available

Persistence and degradability

SAFETY DATA SHEET

Lubrilink 8175, 9487, 9922, 8408

Version 1.0

Revision Date 02/25/2015

Print Date 05/28/2015

no data available

Bioaccumulative potential

Product:

Partition coefficient: n-octanol/water : Remarks: no data available

Components:

butane :

Partition coefficient: n-octanol/water : Pow: 2.89

Mobility in soil

no data available

Other adverse effects

no data available

Product:

Regulation

40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues

: The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.

Contaminated packaging

: Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA): ORM-D, CONSUMER COMMODITY

Transportation Regulation: IMDG (Vessel):

SAFETY DATA SHEET

Lubrilink 8175, 9487, 9922, 8408

Version 1.0

Revision Date 02/25/2015

Print Date 05/28/2015

UN1950, AEROSOLS, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air):
UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air):
UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada):
UN1950, AEROSOLS, 2.1, - Limited quantity

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
acetone	67-64-1	5000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Fire Hazard
Sudden Release of Pressure Hazard
Chronic Health Hazard

SARA 302 : SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop 65 This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

The components of this product are reported in the following inventories:

TSCA On TSCA Inventory
DSL This product contains one or several components that are not on the Canadian DSL nor NDSL.
AICS Not in compliance with the inventory
NZIoC Not in compliance with the inventory
PICCS Not in compliance with the inventory
IECSC Not in compliance with the inventory

SAFETY DATA SHEET

Lubrilink 8175, 9487, 9922, 8408

Version 1.0

Revision Date 02/25/2015

Print Date 05/28/2015


Inventory Acronym and Validity Area Legend:

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

NFPA:



HMIS III:

HEALTH	3
FLAMMABILITY	3
PHYSICAL HAZARD	2

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

OSHA GHS Label Information:

Hazard pictograms



Signal word

Hazard statements

Precautionary statements

- : **Warning:**
: Flammable aerosol. Contains gas under pressure; may explode if heated.
: **Prevention:** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.
: **Storage:** Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.