# SAFETY DATA SHEET MaxxGrip Multipurpose Tape

Identity (As used on label and list):	
6206, 6207, 6208, 6209	
Manufacturer's Name:	Emergency Telephone Number:
Tifco Industries	1-800-255-3924
Address: 21400 Northwest Freeway, Cypress,	Telephone Number for
TX 77429	Information: 281-571-6000
	Date Prepared:2016/1/22
	Signature of Preparer (Optional)

# Section II-Hazards Identification

Polyvinyl chloride tapes. Odorless.

Not a fire hazard in open areas.

Water fog, foam, CO<sub>2</sub> and dry chemicals can be used on fires.

# Section III- Composition and Information on Ingredients

Chemical Name	Weight %	CAS No.
Rubber Adhesive	8-12	
PVC resin	54-58	[9002-86-2]
Plasticizers	23-29	[117-81-7]
Lead compound	30 PPM ↓	
Pigments (organic or /and inorganic)	0-5	
Filler	5-12	
Cd compound	10 <b>PPM</b> ↓	
Toluene	0-1	[108-88-3]

# Section IV- First -Aid Measures

Eye contact: Immediately flush with copious amounts of water for at least 15 minutes. Get medical attention.

Skin contact: No potential health effects are anticipated.

Inhalation: No adverse effects anticipated by this route of exposure incidental to proper industrial handling.

If Swallowed: Drink two glasses of water. Call a physician.

Note to physicians: Treat symptomatically. Treatment may vary with condition of victim and specifics of incident.

# Section V- Fire-fighting Measures:

Flash Point (Method Used): N/A Flammable Limits: N/A

Extinguishing Media: water, dry chemical foam, CO<sub>2</sub>

# **Special Fire Fighting Procedures:**

Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes

# **Unusual Fire and Explosion Hazards:**

Any vinyl and adhesive can be forced to burn by continuous application of intense Heat

# Section VI - Accidental Release Measures

Sweep up and discard.

# Section VII - Handling and Storage

**Handling:** Caution with edge of sheet. After using this sheets, wash hands.

Storage: Keep dry and cool (below 25°C) and away from direct sunlight for quality.

# Section VIII- Exposure controls/Personal Protection

**Engineering Controls :** Good general ventilation should be sufficient for most conditions. When processing at elevated temperature, provide local exhaust.

**Personal protective equipment(PPE):** Respiratory Protection: For most conditions, no respiratory protection should be needed. When processing at elevated temperature, use an approved respiratory protection.

# Section IX- Physical / Chemical Characteristics

Boiling Point	N/A	Specific Gravity (H <sub>2</sub> O=1)	1.3~1.4
Vapor Pressure (mm Hg)	N/A	Softening Point	>80°C
Vapor Density (Air=1)	N/A	Evaporation Rates (Butyl Acetates=1)	N/A
Solubility in Water	N/A	Decomposition Temperature	260(°C)/500°F

Appearance and Odor

#### Section X - Stability and Reactivity :a

Stability: Stable

Incompatibility ( Materials to Avoid): Not Know

Hazardous Decomposition of By-Products: CO2, CO, HCl & some toxic gases

Hazardous Polymerization: Hazardous polymerization will not occur.

# Section XI- Toxicological Information

No information available

# Section XII- Ecological Information

No information available

#### Section XIII- Disposal Considerations

Dispose of materials in compliance with governmental regulations.

# Section XIV- Transport Information

Not a hazardous material for DOT shipping.

# Section XV- Regulation Information:

Chemical Inventories: The products are defined as an article by REACH regulations, and therefore are exempt from the inventory listing requirements.

Other Regulations: please contact for more information

# Section XVI- Other Information

The information in this material safety data sheet presented herein was prepared for your reference to the best of our knowledge. It is given in good faith but we make no warranties, expressed on implied.

#### Data Prepared by

Mr. Sman Lin Product Research Dept. Researcher

Tel: 886-3-4723111 Ext.3607