SAFETY DATA SHEET.

Issuing date 01-Jun-2015 Revision Date 01-Jun-2015 Version 1

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product name Purge III

Recommended use of the chemical

and restrictions on use

Product code 8183, 9884, 9885, 8414

Product Type Extremely flammable aerosol

Synonyms None

Supplier's details

Recommended Use Brake Cleaner. PARTS CLEANER.

Uses advised against No information available

Manufactured For: Tifco Industries PO Box 40277 Houston, TX 77240

Emergency telephone number

Chemical Emergency Phone CHEM-TEL, INC. 1-800-255-3924

Number

Company Phone 281-571-6000

Number

2. HAZARDS IDENTIFICATION

Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Carcinogenicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
Flammable aerosols	Category 1
Gases under pressure	Compressed Gas

GHS Label elements, including precautionary statements

Emergency Overview

DANGER

Hazard Statements

Causes skin irritation

Causes serious eye irritation

Suspected of causing cancer

May cause drowsiness or dizziness

May be fatal if swallowed and enters airways

Extremely flammable aerosol

Contains gas under pressure; may explode if heated



Appearance No information available

Physical state Aerosol

Odor Light Vanilla Scent

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Wear protective gloves/protective clothing/eye protection/face protection

Wash face, hands and any exposed skin thoroughly after handling

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Do not spray on an open flame or other ignition source

Pressurized container: Do not pierce or burn, even after use

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention

Specific treatment (see first aid on this label)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention

IF ON SKIN: Wash with plenty of soap and water.

Take off contaminated clothing and wash before reuse

If skin irritation occurs: Get medical advice/attention

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER or doctor/physician if you feel unwell

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

None

Other information

· Toxic to aquatic life with long lasting effects

9.84E-06% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %*
ACETONE	67-64-1	70-80
METHYL ACETATE	79-20-9	1-10
CARBON DIOXIDE	124-38-9	1-10
XYLENE	1330-20-7	1-10
ETHYL BENZENE	100-41-4	1-10

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First aid measures for different exposure routes

General advice Avoid contact with eyes,skin, and clothing.Avoid breathing, vapors,mist,or gas.

Eye contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Seek immediate medical attention/advice.

Skin contact Wash off immediately with soap and plenty of water. Remove and wash contaminated

clothing before re-use. Get medical attention immediately if symptoms occur.

Inhalation Move to fresh air. If not breathing, give artificial respiration. If breathing has stopped,

contact emergency medical services immediately.

Ingestion Do NOT induce vomiting. Call a physician immediately. Never give anything by mouth to an

unconscious person. Risk of product entering the lungs on vomiting after ingestion.

Most important symptoms/effects, acute and delayed

Main Symptoms Causes skin irritation. Causes eye irritation. May cause respiratory irritation.May be harmful

if swallowed.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media Decomposition by contact with water may generate vapors which can be ignited by heat or

open flame.

Specific hazards arising from the chemical

No information available.

Explosion Data

Sensitivity to Mechanical Impact none. Sensitivity to Static Discharge none.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Absorb with sand, clay, or other suitable material. Hard surfaces may be mopped with

water. Remove all sources of ignition. Avoid contact with the skin and the eyes. Evacuate personnel to be safe areas. Keep people away from and upwind of spill/leak. Contents under pressure. Do not puncture or incinerate cands. Wear protective gloves/clothing and

eye/face protection.

Environmental precautions

Environmental precautions Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in

low areas. Prevent further leakage or spillage if safe to do so. Do not allow material to

contaminate ground water system. Prevent product from entering drains.

Methods and materials for containment and cleaning up

Methods for Containment Absorb or cover with dry earth, sand or other non-combustible material and transfer to

containers. Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers. Soak up with inert absorbent material.

Clean contaminated surface thoroughly. After cleaning, flush away traces with water. Take

precautionary measures against static discharges.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Avoid contact with eyes. Avoid breathing vapors or mists. Contents under pressure. Do not

puncture or incinerate cans. Do not stick pin or any other sharp object into opening on top

of can.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage

conditions

Keep away from direct sun exposure and temperatures over 120 °F (49 °C). Do not

puncture, incinerate, or dispose of in household trash compactor.

Incompatible products Strong acids, alkalis, or oxidizing agents.

Aerosol Level 2

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
ACETONE 67-64-1	STEL: 750 ppm TWA: 500 ppm	TWA: 1000 ppm TWA: 2400 mg/m³ (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m³ (vacated) STEL: 2400 mg/m³ The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors (vacated) STEL: 1000 ppm	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m³
METHYL ACETATE 79-20-9	STEL: 250 ppm TWA: 200 ppm	TWA: 200 ppm TWA: 610 mg/m³ (vacated) TWA: 200 ppm (vacated) TWA: 610 mg/m³ (vacated) STEL: 250 ppm (vacated) STEL: 760 mg/m³	IDLH: 3100 ppm TWA: 200 ppm TWA: 610 mg/m³ STEL: 250 ppm STEL: 760 mg/m³
CARBON DIOXIDE 124-38-9	STEL: 30000 ppm TWA: 5000 ppm	TWA: 5000 ppm TWA: 9000 mg/m³ (vacated) TWA: 10000 ppm (vacated) TWA: 18000 mg/m³ (vacated) STEL: 30000 ppm (vacated) STEL: 54000 mg/m³	IDLH: 40000 ppm TWA: 5000 ppm TWA: 9000 mg/m³ STEL: 30000 ppm STEL: 54000 mg/m³
XYLENE 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m³	-
ETHYL BENZENE 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m³ (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m³ STEL: 125 ppm STEL: 545 mg/m³

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration) NIOSH IDLH: Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Exposure controls

Engineering Measures Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Safety glasses with side-shields.

Skin and body protection Chemical resistant apron. Protective gloves.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

Hygiene measures Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical properties

Physical state Aerosol

AppearanceNo information availableOdorLight Vanilla ScentColorNo information availableOdor ThresholdNo information available

Property Values Remarks • Methods

Hq

Melting/freezing pointNo information availableBoiling point/boiling rangeNo information availableFlash PointNo information availableEvaporation rateNo information availableFlammability (solid, gas)No information available

Flammability Limits in Air

upper flammability limit
lower flammability limit
Vapor pressure
Vapor density
Specific Gravity
Water solubility
No information available
No information available
No information available
No information available
Practically insoluble

Partition coefficient: n-octanol/waterNo information available
Autoignition temperature

No information available

Decomposition temperatureNo information availableViscosityNo information availableExplosive propertiesNo information available

Other information

VOC Content(%) 9

10. STABILITY AND REACTIVITY

Not applicable

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Extremes of temperature and direct sunlight.

Incompatible Materials

Strong acids, alkalis, or oxidizing agents.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation Vapors may irritate throat and respiratory system. May cause drownsiness and dizziness

based on components. May cause irritation of respiratory tract. Avoid breathing vapors or

mists.

Eve contact Irritating to eyes. Avoid contact with eyes.

Skin contact Irritating to skin. Repeated exposure may cause skin dryness or cracking. Prolonged skin

contact may defat the skin and produce dermatitis. Avoid contact with skin.

Ingestion May be harmful or fatal if swallowed. Aspiration into the lungs during swallowing may

cause serious lung damage which may be fatal.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation	
ACETONE 67-64-1	= 5800 mg/kg	20,000 mg/kg (Rabbit)	= 50100 mg/m ³ (Rat) 8 h	
METHYL ACETATE 79-20-9	> 5000 mg/kg (Rat)	> 5 g/kg(Rabbit)	= 16000 ppm (Rat) 4 h	
XYLENE 1330-20-7	= 3500 mg/kg (Rat)	> 4350 mg/kg(Rabbit)	= 29.08 mg/L (Rat) 4 h	
ETHYL BENZENE 100-41-4	-	= 15400 mg/kg(Rabbit)	-	

Information on toxicological effects

Symptoms Inhalation may cause nose, throat , and respiratory tract irritation. Irritation to skin and eyes.

May be harmful if swallowed.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Eye damage/irritationIrritating to skin.

Irritating to eyes.

Irritation Irritating to eyes, respiratory system and skin.

SensitizationNone known.Germ Cell MutagenicityNone known.

Carcinogenicity The table below indicates whether each agency has evaluated a listed ingredient as a

carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
XYLENE	-	Group 3	-	-
1330-20-7		·		
ETHYL BENZENE 100-41-4	A3	Group 2B	-	-

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive toxicity
Specific target organ systemic
toxicity (single exposure)
Specific target organ systemic
toxicity (repeated exposure)

Target Organ Effects

Neurological effects

This product does not contain any known or suspected reproductive hazards.

May cause respiratory irritation. May cause drowsiness and dizziness.

No information available.

Chronic toxicity Intentional misuse by deliberately concentrating and inhaling contents may be harmful or

fatal. Chronic hydrocarbon abuse has been associated with irregular heart rhythms and potential cardiac arrest. Prolonged skin contact may defat the skin and produce dermatitis. Central nervous system, Eyes, Respiratory system, Skin, Central Vascular System (CVS). Intentional misuse by deliberately concentrating and inhaling contents may be harmful or

fatal.

Aspiration hazard May be fatal if swallowed and enters airways.

Numerical measures of toxicity - Product Information

Unknown Acute Toxicity 9.84E-06% of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (dermal) 15266 mg/kg
ATEmix (inhalation-dust/mist) 16.8 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to	Toxicity to daphnia and
			microorganisms	other aquatic invertebrates
ACETONE	-	4.74 - 6.33 mL/L LC50	-	10294 - 17704 mg/L EC50
67-64-1		Oncorhynchus mykiss 96h		Daphnia magna 48h Static
		6210 - 8120 mg/L LC50		12600 - 12700 mg/L EC50
		Pimephales promelas 96h		Daphnia magna 48h
		static 8300 mg/L LC50		
AAETING AGETATE	400 # 5050	Lepomis macrochirus 96h		1000 7 # F050 D 1
METHYL ACETATE	120 mg/L EC50	250 - 350 mg/L LC50	-	1026.7 mg/L EC50 Daphnia
79-20-9	Desmodesmus subspicatus	Brachydanio rerio 96h static		magna 48h
	72h	295 - 348 mg/L LC50		
		Pimephales promelas 96h		
		flow-through		
XYLENE	-	13.1 - 16.5 mg/L LC50	-	0.6 mg/L LC50 Gammarus
1330-20-7		Lepomis macrochirus 96h		lacustris 48h 3.82 mg/L
		flow-through 13.5 - 17.3		EC50 water flea 48h
		mg/L LC50 Oncorhynchus mykiss 96h 2.661 - 4.093		
		mg/L LC50 Oncorhynchus		
		mykiss 96h static 23.53 -		
		29.97 mg/L LC50		
		Pimephales promelas 96h		
		static 30.26 - 40.75 mg/L		
		LC50 Poecilia reticulata 96h		
		static 7.711 - 9.591 mg/L		
		LC50 Lepomis macrochirus		
		96h static 13.4 mg/L LC50		
		Pimephales promelas 96h		
		flow-through 19 mg/L LC50		
		Lepomis macrochirus 96h		
		780 mg/L LC50 Cyprinus		
		carpio 96h semi-static 780		
		mg/L LC50 Cyprinus carpio		
		96h		
ETHYL BENZENE	4.6 mg/L EC50	11.0 - 18.0 mg/L LC50	-	1.8 - 2.4 mg/L EC50
100-41-4	Pseudokirchneriella	Oncorhynchus mykiss 96h		Daphnia magna 48h
	subcapitata 72h 438 mg/L	static 7.55 - 11 mg/L LC50		
	EC50 Pseudokirchneriella	Pimephales promelas 96h		
	subcapitata 96h 2.6 - 11.3	flow-through 9.1 - 15.6 mg/L		
	mg/L EC50	LC50 Pimephales promelas		
	Pseudokirchneriella	96h static 32 mg/L LC50		
	subcapitata 72h static 1.7 -	Lepomis macrochirus 96h		
	7.6 mg/L EC50	static 4.2 mg/L LC50		
	Pseudokirchneriella	Oncorhynchus mykiss 96h		
	subcapitata 96h static	semi-static 9.6 mg/L LC50		
		Poecilia reticulata 96h static		

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical Name	log Pow
ACETONE 67-64-1	-0.24
METHYL ACETATE 79-20-9	0.18

Purge III-8183, 9884, 9885, 8414

Revision Date 01-Jun-2015

XYLENE 1330-20-7	3.15
ETHYL BENZENE 100-41-4	3.118

Other adverse effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment

Waste Disposal Methods This material, as supplied, is a hazardous waste according to federal regulations (40 CFR

261).

Contaminated packaging Do not re-use empty containers.

14. TRANSPORT INFORMATION

DOT Ground CONSUMER COMMODITY ORM-D

or

LIMITED QUANTITY

IATA UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD. QTY.

IMDG UN1950, AEROSOLS, 2.1, LTD. QTY.

15. REGULATORY INFORMATION

International Inventories

Chemical Name	TSCA	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
ACETONE	Х	X	Х	Х	Х	Х	X	Х
METHYL ACETATE	Х	X	Х	Х	Х	Х	Х	Х
CARBON DIOXIDE	Х	Х	Х	Х	Х	Х	Х	Х
XYLENE	Х	Х	Х	Х	Х	Х	Х	Х
ETHYL BENZENE	Х	Х	Х	Х	Х	Х	Х	Х

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

CHINA - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %*	SARA 313 - Threshold Values %
XYLENE - 1330-20-7	1330-20-7	1-10	1.0
ETHYL BENZENE - 100-41-4	100-41-4	1-10	0.1

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	Yes
Reactive Hazard	no

Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
XYLENE 1330-20-7	100 lb			Х
ETHYL BENZENE 100-41-4	1000 lb	Х	Х	Х

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances	RQ
		RQs	
ACETONE	5000 lb		RQ 5000 lb final RQ
67-64-1			RQ 2270 kg final RQ
XYLENE	100 lb		RQ 100 lb final RQ
1330-20-7			RQ 45.4 kg final RQ
ETHYL BENZENE	1000 lb		RQ 1000 lb final RQ
100-41-4			RQ 454 kg final RQ

U.S. State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical Name	California Prop. 65	
ETHYL BENZENE - 100-41-4	Carcinogen	

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
ACETONE 67-64-1	X	X	Х
METHYL ACETATE 79-20-9	X	X	Х
CARBON DIOXIDE 124-38-9	X	X	Х
XYLENE 1330-20-7	X	X	Х
ETHYL BENZENE 100-41-4	X	X	Х

EPA Pesticide Registration Number Not applicable

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

16. OTHER INFORMATION

NFPA Health Hazard 2 Flammability 4 Instability 0 Physical and chemical

hazards -

HMIS Health Hazard 2 Flammability 4 Physical Hazard 1 Personal protection B

Prepared By Regulatory Affairs Issuing date 01-Jun-2015 Revision Date 01-Jun-2015

Revision Note

No information available

Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet