SAFETY DATA SHEET

Date Prepared: 11/13/2014 **Date Revised**: 11/13/2014

Revision No: 1

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Spurt

GENERAL USE: Granular Drain Opener & Maintainer

PRODUCT CODE: 9675, 9676, 677

GIDD@9F

Tifco Industries, Inc.

PO 40277

Houston, TX 77240

24 HR. EMERGENCY TELEPHONE NUMBER

Chem-Tel 800-255-3924

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Health:

Skin Corrosion, Category 1 A Serious Eye Damage, Category 1

GHS LABEL

This chemical is considered hazardous according to the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200)



Corrosion

SIGNAL WORD: DANGER HAZARD STATEMENTS

H314: Causes severe skin burns and eye damage.

H333: May be harmful if inhaled.

PRECAUTIONARY STATEMENTS

Prevention:

P234: Keep only in original container.

P260: Do not breathe dust/fume/gas/mist/vapours/spray.

P264: Wash face, hands and any exposed skin thoroughly after handling.

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

Response:

P301+P330+P331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340: IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310: Immediately call a POISON CENTER or doctor/physician.

P321: Specific treatment (see supplemental first aid instructions on this label).

P363: Wash contaminated clothing before reuse.

P390: Absorb spillage to prevent material damage.

Storage:

P405: Store locked up.

Disposal:

P501: Dispose of contents/container to an approved waste disposal plant.

EMERGENCY OVERVIEW

PHYSICAL APPEARANCE: Colored Pearls

POTENTIAL HEALTH EFFECTS

EYES: Contact causes severe eye irritation. **SKIN:** Corrosive, causes skin burning.

INGESTION: Toxic if swallowed.

INHALATION: Over exposure can be toxic

3. COMPOSITION / INFORMATION ON INGREDIENTS

| Chemical Name | Wt.% | CAS |
|------------------|------|-----------|
| Sodium Hydroxide | < 65 | 1310-73-2 |

4. FIRST AID MEASURES

EYES: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. Continue rinsing eyes during transport to hospital.

SKIN: Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower. Call a POISON CENTER or doctor / physician. Remove and wash contaminated clothing before re-use.

INGESTION: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

INHALATION: If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

5. FIRE FIGHTING MEASURES

FLAMMABLE CLASS: Product does not burn

EXTINGUISHING MEDIA: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

FIRE FIGHTING EQUIPMENT: As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SENSITIVE TO STATIC DISCHARGE: None

SENSITIVITY TO IMPACT: None

6. ACCIDENTAL RELEASE MEASURES

GENERAL PROCEDURES: No action should be taken involving and personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. put on appropriate personal protective equipment.

RELEASE NOTES: Take Steps to avoid release into the environment, if safe to do so.

SPECIAL PROTECTIVE EQUIPMENT: Avoid breathing vapors and provide adequate ventilation. As conditions warrant, wear a NIOSH approved self-contained breathing apparatus, or respirator, and appropriate personal protection (rubber boots, safety goggles, and heavy rubber gloves).

7. HANDLING AND STORAGE

HANDLING: Ensure adequate ventilation. Wear personal protective equipment as required based on a risk assessment. Do not get in eyes, on skin, or on clothing. Do not breathe vapors or spray mist. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

STORAGE: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials and food or drink. Separate from acids. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

| <u> </u> | | | | | |
|---------------------------------------------|------|-----------------------|-------|--------|-------|
| OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200) | | | | | |
| | | EXPOSURE LIMITS | | | |
| | | OSHA PEL Supplier OEL | | er OEL | |
| Chemical Name | | ppm | mg/m³ | ppm | mg/m³ |
| Codium I hidroxida | TWA | | 2 | NL | NL |
| Sodium Hydroxide | STEL | | | NL | NL |

ENGINEERING CONTROLS: Use only with adequate ventilation. use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. Recommended: splash goggles with the use of any liquid products.

SKIN: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

RESPIRATORY: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

WORK HYGIENIC PRACTICES: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

OTHER USE PRECAUTIONS: Facilities storing or utilizing this material or any chemical should be equipped with an eyewash and safety shower. Always wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Solid / Beads

ODOR: Fragranced

APPEARANCE: Colored Pearls

pH: 13 to 14

FLASH POINT AND METHOD: NA = Not Applicable

FLAMMABLE LIMITS: No data available

AUTOIGNITION TEMPERATURE: No data available

VAPOR PRESSURE: No data available

VAPOR DENSITY: 1.38 (Air =1)

BOILING POINT: NA = Not Applicable **FREEZING POINT:** NA = Not Applicable **MELTING POINT:** 318°C (604°F) lit.

POUR POINT: NA = Not Applicable

THERMAL DECOMPOSITION: No data available SOLUBILITY IN WATER: 1260 g/l at 20°C (68°F)

EVAPORATION RATE: No data available

SPECIFIC GRAVITY: 2.13 g/cm3 VISCOSITY: No data available

OXIDIZING PROPERTIES: No data available

10. STABILITY AND REACTIVITY

STABLE: Yes

HAZARDOUS POLYMERIZATION: No

STABILITY: Stable under recommended storage conditions.

POLYMERIZATION: None

CONDITIONS TO AVOID: No data available

POSSIBILITY OF HAZARDOUS REACTIONS: No data available HAZARDOUS DECOMPOSITION PRODUCTS: No data available

INCOMPATIBLE MATERIALS: Strong oxidizing agents, Strong acids, Organic materials

11. TOXICOLOGICAL INFORMATION

EYE EFFECTS: Causes serious eye irritation. **SKIN EFFECTS:** Causes severe skin burns.

CHRONIC: No data available SUBCHRONIC: No data available

CARCINOGENICITY

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by OSHA.

REPEATED DOSE EFFECTS: No data available

SENSITIZATION: Will not occur.

NEUROTOXICITY: No data available

GENETIC EFFECTS: No data available

REPRODUCTIVE EFFECTS: No data available

TARGET ORGANS: No data available

TERATOGENIC EFFECTS: No data available

MUTAGENICITY: No data available

SYNERGISTIC MATERIALS: No data available

12. ECOLOGICAL INFORMATION

GENERAL COMMENTS: Avoid release into the environment. Runoff from fire control or dilution water may cause pollution.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

EMPTY CONTAINER: Do not re-use empty containers.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Corrosive Solids, N.O.S. **TECHNICAL NAME:** (Contains: Sodium Hydroxide)

PRIMARY HAZARD CLASS/DIVISION: 8

UN/NA NUMBER: UN1759 PACKING GROUP: II

REPORTABLE QUANTITY (RQ) UNDER CERCLA: 1000 lbs

LABEL: Corrosive

OTHER SHIPPING INFORMATION: All products offered for domestic ground transportation that meet the following Exceptions for Class 8 (corrosive materials) will be packaged and shipped as "Limited Qty".

- (1) For corrosive materials in Packing Group II, inner packagings not over 1.0 L (0.3 gallon) net capacity each for liquids or not over 1.0 kg (2.2 lbs) net capacity each for solids, packed in a strong outer packaging with a gross package weight of 66 lbs or less.
- (2) For corrosive materials in Packing Group III, inner packagings not over 5.0 L (1.3 gallon) net capacity each for liquids or not over 5.0 kg (11 lbs) net capacity each for solids, packed in a strong outer packaging with a gross package weight of 66 lbs or less.

15. REGULATORY INFORMATION

UNITED STATES

DOT LABEL SYMBOL AND HAZARD CLASSIFICATION







Ground

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: Acute Health Hazard

313 REPORTABLE INGREDIENTS: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

CERCLA (COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION, AND LIABILITY ACT)

| Chemical Name | Wt.% | CERCLA RQ |
|------------------|------|--------------|
| Sodium Hydroxide | < 65 | 1,000 |

TSCA (TOXIC SUBSTANCE CONTROL ACT)

| Chemical Name | CAS |
|------------------|-----------|
| Sodium Hydroxide | 1310-73-2 |


CALIFORNIA PROPOSITION 65: This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

CLEAN WATER ACT: Sodium Hydroxide

16. OTHER INFORMATION

PREPARED BY: Kevin E Hall **Date Revised:** 11/13/2014 **REVISION SUMMARY:** This SDS replaces the 11/13/2014 SDS.

| HMIS RATING | |
|---------------------|---|
| HEALTH | 3 |
| FLAMMABILITY | 0 |
| PHYSICAL HAZARD | 0 |
| PERSONAL PROTECTION | С |



MANUFACTURER DISCLAIMER: The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. the information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.