

# SAFETY DATA SHEET.

Issuing date 27-May-2015

Revision Date 28-May-2015

Version 1

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

### Product identifier

**Product name** X-Treme Solv

### Recommended use of the chemical and restrictions on use

**Product code** 7794, 7795, 7796

**Product Type** Extremely flammable aerosol  
**Synonyms** None

### Supplier's details

**Recommended Use** MULTI-PURPOSE SOLVENT.  
**Uses advised against** No information available

### **Manufactured For:**

Tifco Industries  
PO Box 40277  
Houston, TX 77240

### Emergency telephone number

**Chemical Emergency Phone Number** CHEM-TEL, INC. 1-800-255-3924  
**Company Phone Number** 281-571-6000

## 2. HAZARDS IDENTIFICATION

### Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Carcinogenicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
Flammable aerosols	Category 1
Gases under pressure	Compressed Gas

### GHS Label elements, including precautionary statements

#### Emergency Overview

#### DANGER

#### Hazard Statements

Causes skin irritation  
 Causes serious eye irritation  
 Suspected of causing cancer  
 May cause respiratory irritation. May cause drowsiness or dizziness  
 May be fatal if swallowed and enters airways  
 Extremely flammable aerosol  
 Contains gas under pressure; may explode if heated



**Appearance** Clear

**Physical state** Aerosol

**Odor** Solvent

#### Precautionary Statements - Prevention

Obtain special instructions before use  
 Wear protective gloves/protective clothing/eye protection/face protection  
 Do not handle until all safety precautions have been read and understood  
 Wash face, hands and any exposed skin thoroughly after handling  
 Avoid breathing dust/fume/gas/mist/vapors/spray  
 Use only outdoors or in a well-ventilated area  
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
 Do not spray on an open flame or other ignition source  
 Pressurized container: Do not pierce or burn, even after use

#### Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention  
 Specific treatment (see first aid on this label)  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 If eye irritation persists: Get medical advice/attention  
 IF ON SKIN: Wash with plenty of soap and water.  
 Take off contaminated clothing and wash before reuse  
 If skin irritation occurs: Get medical advice/attention  
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 Call a POISON CENTER or doctor/physician if you feel unwell  
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
 Do NOT induce vomiting

**Precautionary Statements - Storage**

Store locked up  
 Store in a well-ventilated place. Keep container tightly closed  
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

None

**Other information**

• Toxic to aquatic life with long lasting effects

0% of the mixture consists of ingredient(s) of unknown toxicity

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %*
PETROLEUM DISTILLATES	64742-89-8	60-70
PROPANE/ISOBUTANE/N-BUTANE	68476-86-8	20-30
XYLENE	1330-20-7	10-20
ETHYL BENZENE	100-41-4	1-10

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

**First aid measures for different exposure routes**

<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
<b>Inhalation</b>	Move to fresh air. If breathing is difficult, give oxygen. Artificial respiration and/or oxygen may be necessary. If breathing has stopped, contact emergency medical services immediately.
<b>Ingestion</b>	Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Drink plenty of water. Call a physician or Poison Control Center immediately.

**Most important symptoms/effects, acute and delayed**

**Main Symptoms** Causes skin irritation. Causes eye irritation. May cause respiratory irritation. May be harmful if swallowed.

**Indication of immediate medical attention and special treatment needed, if necessary**

**Notes to physician** Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

**Suitable Extinguishing Media**

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Unsuitable Extinguishing Media** Decomposition by contact with water may generate vapors which can be ignited by heat or open flame.

**Specific hazards arising from the chemical**

No information available.

**Explosion Data**

**Sensitivity to Mechanical Impact** none.

**Sensitivity to Static Discharge** Yes.

**Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures****Personal precautions**

Absorb with sand, clay, or other suitable material. Hard surfaces may be mopped with water. Remove all sources of ignition. Avoid contact with the skin and the eyes. Evacuate personnel to be safe areas. Keep people away from and upwind of spill/leak. Contents under pressure. Do not puncture or incinerate cans. Wear protective gloves/clothing and eye/face protection.

**Environmental precautions****Environmental precautions**

Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas. Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains.

**Methods and materials for containment and cleaning up****Methods for Containment**

Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up**

Pick up and transfer to properly labeled containers. Soak up with inert absorbent material. Clean contaminated surface thoroughly. After cleaning, flush away traces with water. Take precautionary measures against static discharges.

## 7. HANDLING AND STORAGE

**Precautions for safe handling****Advice on safe handling**

Avoid contact with eyes. Avoid breathing vapors or mists. Contents under pressure. Do not puncture or incinerate cans. Do not stick pin or any other sharp object into opening on top of can.

**Conditions for safe storage, including any incompatibilities****Technical measures/Storage conditions**

Keep container tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Keep in properly labeled containers. Keep out of the reach of children. Store locked up.

**Incompatible products**

Strong acids, alkalis, or oxidizing agents.

**Aerosol Level**

3

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Control parameters****Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	74-98-6: TWA: 1000 ppm 106-97-8: STEL: 1000 ppm 75-28-5: STEL: 1000 ppm	74-98-6: TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup> (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m <sup>3</sup> 106-97-8: (vacated) TWA: 800 ppm ppm (vacated) TWA: 1900 mg/m <sup>3</sup>	74-98-6: IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup> 106-97-8: TWA: 800 ppm TWA: 1900 mg/m <sup>3</sup> 75-28-5: TWA: 800 ppm TWA: 1900 mg/m <sup>3</sup>
XYLENE 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m <sup>3</sup> (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m <sup>3</sup>	-
ETHYL BENZENE 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m <sup>3</sup> (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m <sup>3</sup>	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm STEL: 545 mg/m <sup>3</sup>

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety &amp; Health Administration)

NIOSH IDLH: Immediately Dangerous to Life or Health

**Other Exposure Guidelines**

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

**Exposure controls****Engineering Measures**Showers  
Eyewash stations  
Ventilation systems.**Individual protection measures, such as personal protective equipment****Eye/Face Protection**

Safety glasses with side-shields.

**Skin and body protection**

Chemical resistant apron. Protective gloves.

**Respiratory protection**

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

**Hygiene measures**

Handle in accordance with good industrial hygiene and safety practice.

**9. PHYSICAL AND CHEMICAL PROPERTIES****Physical and chemical properties****Physical state**

Aerosol

**Appearance**

Clear

**Color**

clear

**Odor**

Solvent

**Odor Threshold**

No information available

**Property****Values****Remarks • Methods****pH**

No information available

**Melting/freezing point**

No information available

**Boiling point/boiling range**

No information available

**Flash Point**

&gt; -97 °C / &gt; -143 °F

Closed cup: Based on propellant

<b>Evaporation rate</b>	No information available	
<b>Flammability (solid, gas)</b>	No information available	
<b>Flammability Limits in Air</b>		
<b>upper flammability limit</b>	No information available	
<b>lower flammability limit</b>	No information available	
<b>Vapor pressure</b>	No information available	
<b>Vapor density</b>	No information available	
<b>Specific Gravity</b>	.729	
<b>Water solubility</b>	Practically insoluble	
<b>Partition coefficient: n-octanol/water</b>	No information available	
<b>Autoignition temperature</b>	No information available	Not applicable
<b>Decomposition temperature</b>	No information available	
<b>Viscosity</b>	No information available	
<b>Explosive properties</b>	No information available	

**Other information**

VOC Content(%) 100

## 10. STABILITY AND REACTIVITY

**Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

None under normal processing.

**Conditions to Avoid**

Extremes of temperature and direct sunlight.

**Incompatible Materials**

Strong acids, alkalis, or oxidizing agents.

**Hazardous Decomposition Products**

None known based on information supplied.

## 11. TOXICOLOGICAL INFORMATION

**Information on likely routes of exposure****Product Information**

<b>Inhalation</b>	Vapors may irritate throat and respiratory system. May cause drowsiness and dizziness based on components. May cause irritation of respiratory tract. Avoid breathing vapors or mists.
<b>Eye contact</b>	Irritating to eyes. Avoid contact with eyes.
<b>Skin contact</b>	Irritating to skin. Repeated exposure may cause skin dryness or cracking. Prolonged skin contact may defat the skin and produce dermatitis. Avoid contact with skin.
<b>Ingestion</b>	Harmful if swallowed. Aspiration into the lungs during swallowing may cause serious lung damage which may be fatal.

**Component Information**

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
PETROLEUM DISTILLATES 64742-89-8	-	= 3000 mg/kg ( Rabbit )	-

XYLENE 1330-20-7	= 3500 mg/kg ( Rat )	> 4350 mg/kg ( Rabbit )	= 29.08 mg/L ( Rat ) 4 h
ETHYL BENZENE 100-41-4	-	= 15400 mg/kg ( Rabbit )	-

**Information on toxicological effects**

**Symptoms** Symptoms of overexposure may be headache, dizziness, tiredness, nausea, and vomiting. Causes eye and skin irritation. Prolonged or repeated exposure may cause dermatitis. May cause respiratory system irritation. May be fatal if swallowed and enters airways.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Sensitization** None known.  
**Germ Cell Mutagenicity** None known.  
**Carcinogenicity** The table below indicates whether each agency has evaluated a listed ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
XYLENE 1330-20-7	-	Group 3	-	-
ETHYL BENZENE 100-41-4	A3	Group 2B	-	-

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

OSHA: (Occupational Safety & Health Administration)

X - Present

**Reproductive toxicity** This product does not contain any known or suspected reproductive hazards.  
**Specific target organ systemic toxicity (single exposure)** May cause respiratory irritation. May cause drowsiness and dizziness.  
**Specific target organ systemic toxicity (repeated exposure)** None under normal use conditions.  
**Target Organ Effects** Central nervous system, Eyes, Respiratory system, Skin.  
**Aspiration hazard** May be fatal if swallowed and enters airways.

**Numerical measures of toxicity - Product Information**

**Unknown Acute Toxicity** 0% of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (dermal) 7117 mg/kg

ATEmix (inhalation-dust/mist) 7.8 mg/l

**12. ECOLOGICAL INFORMATION****Ecotoxicity**

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates
PETROLEUM DISTILLATES 64742-89-8	4700 mg/L EC50 Pseudokirchneriella subcapitata 72h	-	-	-
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	-	-	-	-

XYLENE 1330-20-7	-	13.1 - 16.5 mg/L LC50 Lepomis macrochirus 96h flow-through 13.5 - 17.3 mg/L LC50 Oncorhynchus mykiss 96h 2.661 - 4.093 mg/L LC50 Oncorhynchus mykiss 96h static 23.53 - 29.97 mg/L LC50 Pimephales promelas 96h static 30.26 - 40.75 mg/L LC50 Poecilia reticulata 96h static 7.711 - 9.591 mg/L LC50 Lepomis macrochirus 96h static 13.4 mg/L LC50 Pimephales promelas 96h flow-through 19 mg/L LC50 Lepomis macrochirus 96h 780 mg/L LC50 Cyprinus carpio 96h semi-static 780 mg/L LC50 Cyprinus carpio 96h	-	0.6 mg/L LC50 Gammarus lacustris 48h 3.82 mg/L EC50 water flea 48h
ETHYL BENZENE 100-41-4	4.6 mg/L EC50 Pseudokirchneriella subcapitata 72h 438 mg/L EC50 Pseudokirchneriella subcapitata 96h 2.6 - 11.3 mg/L EC50 Pseudokirchneriella subcapitata 72h static 1.7 - 7.6 mg/L EC50 Pseudokirchneriella subcapitata 96h static	11.0 - 18.0 mg/L LC50 Oncorhynchus mykiss 96h static 7.55 - 11 mg/L LC50 Pimephales promelas 96h flow-through 9.1 - 15.6 mg/L LC50 Pimephales promelas 96h static 32 mg/L LC50 Lepomis macrochirus 96h static 4.2 mg/L LC50 Oncorhynchus mykiss 96h semi-static 9.6 mg/L LC50 Poecilia reticulata 96h static	-	1.8 - 2.4 mg/L EC50 Daphnia magna 48h

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

Chemical Name	log Pow
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	2.8
XYLENE 1330-20-7	3.15
ETHYL BENZENE 100-41-4	3.118

**Other adverse effects**

No information available

**13. DISPOSAL CONSIDERATIONS****Waste treatment****Waste Disposal Methods**

This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

**Contaminated packaging**

Do not re-use empty containers.

**14. TRANSPORT INFORMATION**



**DOT Ground** CONSUMER COMMODITY ORM-D  
or  
LIMITED QUANTITY

**IATA** UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD. QTY.

**IMDG** UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD. QTY.

## 15. REGULATORY INFORMATION

### International Inventories

Chemical Name	TSCA	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
PETROLEUM DISTILLATES	X	X	X	Not listed	X	X	X	X
PROPANE/ISOBUTA NE/N-BUTANE	X	X	X	Not listed	X	X	X	X
XYLENE	X	X	X	X	X	X	X	X
ETHYL BENZENE	X	X	X	X	X	X	X	X

### Legend:

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**CHINA** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

### U.S. Federal Regulations

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %*	SARA 313 - Threshold Values %
XYLENE - 1330-20-7	1330-20-7	10-20	1.0
ETHYL BENZENE - 100-41-4	100-41-4	1-10	0.1

#### **SARA 311/312 Hazard Categories**

<b>Acute Health Hazard</b>	Yes
<b>Chronic Health Hazard</b>	Yes
<b>Fire Hazard</b>	Yes
<b>Sudden Release of Pressure Hazard</b>	Yes
<b>Reactive Hazard</b>	no

#### **Clean Water Act**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
XYLENE 1330-20-7	100 lb			X

ETHYL BENZENE 100-41-4	1000 lb	X	X	X
---------------------------	---------	---	---	---

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
XYLENE 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
ETHYL BENZENE 100-41-4	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

**U.S. State Regulations****California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical Name	California Prop. 65
ETHYL BENZENE - 100-41-4	Carcinogen

**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
PETROLEUM DISTILLATES 64742-89-8			X
XYLENE 1330-20-7	X	X	X
ETHYL BENZENE 100-41-4	X	X	X

**EPA Pesticide Registration Number** Not applicable

**Canada**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

## 16. OTHER INFORMATION

**NFPA** Health Hazard 2 Flammability 4 Instability 0 Physical and chemical hazards -

**HMIS** Health Hazard 2\* Flammability 4 Physical Hazard 1 Personal protection B  
*Chronic Hazard Star Legend* *Chronic Health Hazard: Aromatic solvents* *Severe overexposure may cause liver or kidney damage*  
*Repeated or prolonged exposure may cause central nervous system damage*

**Prepared By** Regulatory Affairs  
**Issuing date** 27-May-2015  
**Revision Date** 28-May-2015  
**Revision Note**  
 No information available

**Disclaimer**

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of Safety Data Sheet**