SAFETY DATA SHEET.

Issuing date 29-May-2015 Revision Date 29-May-2015 Version 1

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product name X-Treme Solv Liquid

Recommended use of the chemical

and restrictions on use

<u>Product code</u> 7730, 7731

<u>Product Type</u> Highly Flammable Liquid and Vapor

Synonyms None

Supplier's details

Recommended Use MULTI-PURPOSE SOLVENT. Uses advised against No information available

Manufactured For: Tifco Industries PO Box 40277 Houston, TX 77240

Emergency telephone number

Chemical Emergency Phone CHEM-TEL, INC. 1-800-255-3924

Number

Company Phone 281-571-6000

Number

2. HAZARDS IDENTIFICATION

Classification

Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2B
Carcinogenicity	Category 2
Aspiration toxicity	Category 1
Flammable Liquids	Category 2

GHS Label elements, including precautionary statements

Emergency Overview

DANGER

Hazard Statements

Harmful if inhaled

Causes skin irritation

Causes eye irritation

Suspected of causing cancer

May be fatal if swallowed and enters airways

Highly flammable liquid and vapor



Appearance Clear Physical state Liquid Odor Solvent

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Wear protective gloves/protective clothing/eye protection/face protection

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Wash face, hands and any exposed skin thoroughly after handling

Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Keep container tightly closed

Ground/Bond container and receiving equipment

Use explosion-proof electrial/ventilating/lighting /equipment.

Use only non-sparking tools

Take precautionary measures against static discharge

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention

Specific treatment (see first aid on this label)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

If skin irritation occurs: Get medical advice/attention

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER or doctor/physician if you feel unwell

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep cool

Keep cool.

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

None

Other information

· Toxic to aquatic life with long lasting effects

0% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %*
PETROLEUM DISTILLATES	64742-89-8	70-80
XYLENE	1330-20-7	20-30
ETHYL BENZENE	100-41-4	1-10

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First aid measures for different exposure routes

General advice Avoid contact with eyes, skin, and clothing. Avoid breathing, vapors, mist, or gas.

Eye contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Seek immediate medical attention/advice.

Skin contact Wash off immediately with soap and plenty of water. Remove and wash contaminated

clothing before re-use. Get medical attention immediately if symptoms occur.

Inhalation Move to fresh air. If not breathing, give artificial respiration. If breathing has stopped,

contact emergency medical services immediately.

Ingestion Do NOT induce vomiting. Call a physician immediately. Never give anything by mouth to an

unconscious person. Risk of product entering the lungs on vomiting after ingestion.

Most important symptoms/effects, acute and delayed

Main Symptoms May cause skin and eye irritation. Harmful if inhaled. Harmful if swallowed and enters

airways.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media Decomposition by contact with water may generate vapors which can be ignited by heat or open flame.

Specific hazards arising from the chemical

No information available.

Explosion Data

Sensitivity to Mechanical Impact none. Sensitivity to Static Discharge Yes.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with the skin and the eyes. Evacuate personnel to safe areas. Ensure

adequate ventilation. Avoid dust formation. Remove all sources of ignition. Keep people away from and upwind of spill/leak. Take precautionary measures against static discharges.

Environmental precautions

Environmental precautions Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in

low areas. Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains. Local authorities

should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up

Methods for ContainmentAbsorb with earth, sand or other non-combustible material and transfer to containers for

later disposal. Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers. Soak up with inert absorbent material.

Clean contaminated surface thoroughly. After cleaning, flush away traces with water. Take

precautionary measures against static discharges.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Avoid contact with skin, eyes and clothing. Handle in accordance with good industrial

hygiene and safety practice. Remove and wash contaminated clothing before re-use. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures

against static discharges. Avoid breathing vapors or mists.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage

conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Keep in properly labeled containers. Keep out

of the reach of children. Store locked up.

Incompatible products Strong acids, alkalis, or oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
XYLENE	STEL: 150 ppm	TWA: 100 ppm	-
1330-20-7	TWA: 100 ppm	TWA: 435 mg/m ³	
		(vacated) TWA: 100 ppm	
		(vacated) TWA: 435 mg/m ³	
		(vacated) STEL: 150 ppm	
		(vacated) STEL: 655 mg/m ³	
ETHYL BENZENE	TWA: 20 ppm	TWA: 100 ppm	IDLH: 800 ppm
100-41-4		TWA: 435 mg/m ³	TWA: 100 ppm
		(vacated) TWA: 100 ppm	TWA: 435 mg/m ³
		(vacated) TWA: 435 mg/m ³	STEL: 125 ppm
		(vacated) STEL: 125 ppm	STEL: 545 mg/m ³
		(vacated) STEL: 545 mg/m ³	-

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration) NIOSH IDLH: Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Exposure controls

Engineering Measures Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Safety glasses with side-shields.

Skin and body protection Chemical resistant apron. Protective gloves.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

Closed cup (based on components)

provided in accordance with current local regulations.

Hygiene measures Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical properties

Physical state Liquid Appearance Clear

AppearanceClearOdorSolvent

ColorOdor ThresholdNo information available

Property Values Remarks • Methods

pH No information available
Melting/freezing point No information available
Boiling point/boiling range
Flash Point No information available
No information available
> 16 °C / > 60 °F

Evaporation rate

Flammability (solid, gas)

Flammability (solid, gas)

Flammability (solid, gas)

Flammability (solid, gas)

Flammability (solid, gas) No information
Flammability Limits in Air
upper flammability limit No information

upper flammability limitNo information availablelower flammability limitNo information availableVapor pressureNo information available

Vapor density No information available

Specific Gravity 0.767

Water solubility Practically insoluble
Partition coefficient: n-octanol/waterNo information available
Autoignition temperature No information available
Decomposition temperature No information available
Viscosity No information available
Explosive properties No information available

Other information

VOC Content(%) 100

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Extremes of temperature and direct sunlight.

Incompatible Materials

Strong acids, alkalis, or oxidizing agents.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation Harmful by inhalation. Avoid breathing vapors or mists.

Eye contact Irritating to eyes. Avoid contact with eyes.

Skin contact Irritating to skin. Repeated exposure may cause skin dryness or cracking. Prolonged skin

contact may defat the skin and produce dermatitis. Avoid contact with skin.

Ingestion May be harmful or fatal if swallowed. Aspiration into the lungs during swallowing may

cause serious lung damage which may be fatal.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
PETROLEUM DISTILLATES 64742-89-8	-	= 3000 mg/kg(Rabbit)	-
XYLENE 1330-20-7	= 3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h
ETHYL BENZENE 100-41-4	-	= 15400 mg/kg(Rabbit)	-

Information on toxicological effects

Symptoms Harmful if swallowed. May be fatal if swallowed and enters airways. May cause skin and

eve irritation.

Revision Date 29-May-2015

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritationIrritating to skin.Eye damage/irritationIrritating to eyes.

Irritation Irritating to eyes and skin.

Sensitization None known.
Germ Cell Mutagenicity None known.

Carcinogenicity The table below indicates whether each agency has evaluated a listed ingredient as a

carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
XYLENE	-	Group 3	-	-
1330-20-7				
ETHYL BENZENE	A3	Group 2B	-	-
100-41-4		•		

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive toxicity

Specific target organ systemic toxicity (single exposure)

Specific target organ systemic toxicity (repeated exposure)

Chronic toxicity

This product does not contain any known or suspected reproductive hazards.

None under normal use conditions.

None under normal use conditions.

Chronic hydrocarbon abuse has been associated with irregular heart rhythms and potential

cardiac arrest. Prolonged skin contact may defat the skin and produce dermatitis.

Target Organ Effects Central nervous system, Eyes, Respiratory system, Skin.

Neurological effects Intentional misuse by deliberately concentrating and inhaling contents may be harmful or

fatal.

Aspiration hazard May be fatal if swallowed and enters airways.

Numerical measures of toxicity - Product Information

Unknown Acute Toxicity 0% of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 14583 mg/kg
ATEmix (dermal) 4583 mg/kg
ATEmix (inhalation-dust/mist) 5.2 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates
PETROLEUM DISTILLATES 64742-89-8	4700 mg/L EC50 Pseudokirchneriella subcapitata 72h	-	-	-

XYLENE	_	13.1 - 16.5 mg/L LC50	_	0.6 mg/L LC50 Gammarus
1330-20-7		Lepomis macrochirus 96h		lacustris 48h 3.82 mg/L
		flow-through 13.5 - 17.3		EC50 water flea 48h
		mg/L LC50 Oncorhynchus		
		mykiss 96h 2.661 - 4.093		
		mg/L LC50 Oncorhynchus		
		mykiss 96h static 23.53 -		
		29.97 mg/L LC50		
		Pimephales promelas 96h		
		static 30.26 - 40.75 mg/L		
		LC50 Poecilia reticulata 96h		
		static 7.711 - 9.591 mg/L		
		LC50 Lepomis macrochirus		
		96h static 13.4 mg/L LC50		
		Pimephales promelas 96h		
		flow-through 19 mg/L LC50		
		Lepomis macrochirus 96h		
		780 mg/L LC50 Cyprinus		
		carpio 96h semi-static 780		
		mg/L LC50 Cyprinus carpio		
		96h		
ETHYL BENZENE	4.6 mg/L EC50	11.0 - 18.0 mg/L LC50	-	1.8 - 2.4 mg/L EC50
100-41-4	Pseudokirchneriella	Oncorhynchus mykiss 96h		Daphnia magna 48h
	subcapitata 72h 438 mg/L	static 7.55 - 11 mg/L LC50		-
	EC50 Pseudokirchneriella	Pimephales promelas 96h		
	subcapitata 96h 2.6 - 11.3	flow-through 9.1 - 15.6 mg/L		
	mg/L EC50	LC50 Pimephales promelas		
	Pseudokirchneriella	96h static 32 mg/L LC50		
	subcapitata 72h static 1.7 -	Lepomis macrochirus 96h		
	7.6 mg/L EC50	static 4.2 mg/L LC50		
	Pseudokirchneriella	Oncorhynchus mykiss 96h		
	subcapitata 96h static	semi-static 9.6 mg/L LC50		
		Poecilia reticulata 96h static		

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical Name	log Pow
XYLENE 1330-20-7	3.15
ETHYL BENZENE 100-41-4	3.118

Other adverse effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment

Waste Disposal Methods This material, as supplied, is a hazardous waste according to federal regulations (40 CFR

261).

Contaminated packaging Do not re-use empty containers.

14. TRANSPORT INFORMATION

DOT Ground CONSUMER COMMODITY ORM-D

or

LIMITED QUANTITY

IATA UN1993, FLAMMABLE LIQUIDS, N.O.S (PETROLEUM DISTILLATES, XYLENE),3, PG II

IMDG UN1993, FLAMMABLE LIQUIDS, N.O.S (PETROLEUM DISTILLATES, XYLENE),3, PG II,

LTD. QTY.

15. REGULATORY INFORMATION

International Inventories

Chemical Name	TSCA	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
PETROLEUM DISTILLATES	Х	Х	Х	Not listed	Х	Х	Х	Х
XYLENE	Х	Х	Х	X	X	X	Х	Х
ETHYL BENZENE	Х	X	Х	X	Х	Х	Х	Х

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

CHINA - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %*	SARA 313 - Threshold Values %
XYLENE - 1330-20-7	1330-20-7	20-30	1.0
ETHYL BENZENE - 100-41-4	100-41-4	1-10	0.1

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	no
Reactive Hazard	no

Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
XYLENE 1330-20-7	100 lb			Х
ETHYL BENZENE 100-41-4	1000 lb	X	X	Х

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
XYLENE 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
ETHYL BENZENE 100-41-4	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

U.S. State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical Name	California Prop. 65	
ETHYL BENZENE - 100-41-4	Carcinogen	

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
PETROLEUM DISTILLATES 64742-89-8			Х
XYLENE 1330-20-7	X	Х	Х
ETHYL BENZENE 100-41-4	X	Х	Х

EPA Pesticide Registration Number Not applicable

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

16. OTHER INFORMATION

NFPA **Health Hazard** 2 Instability 0 Flammability 4 Physical and chemical hazards -

Health Hazard 2* Personal protection B Flammability 4 Physical Hazard 0

HMIS

Chronic Hazard Star Legend Chronic Health Hazard: Aromatic solvents Severe overexposure may cause liver or kidney damage Repeated or prolonged exposure may cause central nervous system damage

Prepared By Regulatory Affairs Issuing date 29-May-2015 **Revision Date** 29-May-2015

Revision Note

No information available

Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet